

Car Brite™ AIR FRESHENER

Version 1.3 Revision Date: 10/31/2017 SDS Number: 600000000076 Date of last issue: 04/18/2017
Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : Car Brite™ AIR FRESHENER

Product code : 569029

Manufacturer or supplier's details

Company name of supplier : Niteo Products,LLC

Address : Dallas TX 19162

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : ODOR ELIMINATOR

Restrictions on use : To be used only where there is a recognised need. Do not exceed the appropriate dose rates.

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable aerosols : Category 1

Eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after

Car Brite™ AIR FRESHENER

Version 1.3 Revision Date: 10/31/2017 SDS Number: 600000000076 Date of last issue: 04/18/2017
 Date of first issue: 05/23/2016

use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 17 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Substance name : HT-18045, 18060, 18065, 18070, 18075

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
ACETONE	67-64-1	>= 50 - < 70
LIQUIFIED PETROLEUM GASES, SWEETENED	68476-86-8	>= 10 - < 30

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : Move to fresh air.
 Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.

Car Brite™ AIR FRESHENER

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.3	10/31/2017	600000000076	Date of first issue: 05/23/2016

- If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.
Irritating to eyes.
May cause drowsiness or dizziness.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon oxides
Organic acids
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
-

Car Brite™ AIR FRESHENER

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.3	10/31/2017	600000000076	Date of first issue: 05/23/2016

- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Suppress (knock down) gases/vapours/mists with a water spray jet.
Comply with all applicable local, state and federal regulations.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Do not grind the product.
Do not heat the product.
Do not breathe vapours or spray mist.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
No smoking.
-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

- Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Car Brite™ AIR FRESHENER

Version 1.3 Revision Date: 10/31/2017 SDS Number: 600000000076 Date of last issue: 04/18/2017
 Date of first issue: 05/23/2016

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
 In the case of dust or aerosol formation use respirator with an approved filter.
- Hand protection
- Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear as appropriate:
 Impervious clothing
 Flame-resistant clothing
 Safety shoes
- Protective measures : When using do not eat, drink or smoke.
 Wear suitable protective equipment.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
 Avoid contact with skin, eyes and clothing.
 Do not inhale aerosol.
 Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : aerosol
- Colour : clear
- Odour : pleasant
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : -23 - 133 °F
 No data available
- Flash point : -96.11 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : 12.8 %(V)

Car Brite™ AIR FRESHENER

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.3	10/31/2017	600000000076	Date of first issue: 05/23/2016

Lower explosion limit	: 1.8 %(V)
Vapour pressure	: 307.9692 hPa (25 °C) The value is calculated
Density	: 0.7166 g/cm3
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Exposure to sunlight. Exposure to moisture Heat
Incompatible materials	: Acids Bases Amines Ammonia halogens isocyanates Peroxides Reducing agents Strong bases Strong oxidizing agents UV light.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Eye contact
Skin contact

Car Brite™ AIR FRESHENER

Version 1.3 Revision Date: 10/31/2017 SDS Number: 600000000076 Date of last issue: 04/18/2017
Date of first issue: 05/23/2016

Acute toxicity**Components:****ACETONE:**

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:**ACETONE:**

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

LIQUIFIED PETROLEUM GASES, SWEETENED:

Result: Possibly irritating to skin

Serious eye damage/eye irritation**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.
Causes serious eye irritation.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**ACETONE:**

Result: Irritating to eyes.

Assessment: Irritating to eyes.

LIQUIFIED PETROLEUM GASES, SWEETENED:

Result: Possibly irritating to eyes

STOT - single exposure**Components:****ACETONE:**

Exposure routes: Inhalation

Target Organs: Nervous system

Car Brite™ AIR FRESHENER

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.3	10/31/2017	600000000076	Date of first issue: 05/23/2016

Assessment: May cause drowsiness or dizziness.

Aspiration toxicity
Product:

No aspiration toxicity classification

Components:
ACETONE:

May be harmful if swallowed and enters airways.

Further information
Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION
SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION
International Regulations
IATA-DGR

UN/ID No.	:	UN 1950
Proper shipping name	:	Aerosols, flammable
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1
Packing instruction (cargo aircraft)	:	203
Packing instruction (passenger aircraft)	:	203

IMDG-Code

UN number	:	UN 1950
-----------	---	---------

Car Brite™ AIR FRESHENER

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.3	10/31/2017	600000000076	Date of first issue: 05/23/2016

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 1950

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

ERG Code : 126

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act**

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard

California Prop. 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

Car Brite™ AIR FRESHENER

Version
1.3

Revision Date:
10/31/2017


SDS Number:
600000000076

Date of last issue: 04/18/2017
Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	4
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 10/31/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN