

Version 1.3	Revision Date: 10/31/2017	•••	DS Number: 0000000076	Date of last issue: 04/18/2017 Date of first issue: 05/23/2016	
SECTIO	N 1. IDENTIFICATION				
Product name		:	Car Brite™ FRS⊦ FRESHENER	I AIR TOTAL RLS ODOR FOGGER AIR	
Proc	duct code	:	569112		
Mar	ufacturer or supplier's	deta	ails		
Company name of supplier		:	Niteo Products,Ll	.C	
Address		:	Dallas TX 19162		
Telephone		:	1-844-696-4836		
Emergency telephone num- ber		:	1-800-424-9300		
Recommended use of the chemical and restrictions on use					
Recommended use		:	ODOR ELIMINATOR		
Restrictions on use :		:	To be used only vertice of the approximation of the second	vhere there is a recognised need. Do not priate dose rates.	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable aerosols	: Category 1
Eye irritation	: Category 2A
Specific target organ toxicity - single exposure	: Category 3 (Central nervous system)
GHS label elements Hazard pictograms	
Signal word	: Danger
Hazard statements	 H222 Extremely flammable aerosol. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Precautionary statements	: Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces.



Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.3	10/31/2017	600000000076	Date of first issue: 05/23/2016
		P251 Pressuriz use. P261 Avoid bre P264 Wash skii P271 Use only P280 Wear eye Response: P304 + P340 + and keep comfo CENTER/docto P305 + P351 + for several minu to do. Continue P337 + P313 If tion. Storage: P403 + P233 S tightly closed. P405 Store lock P410 + P412 P tures exceeding Disposal:	eye irritation persists: Get medical advice/ atten- tore in a well-ventilated place. Keep container

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 17 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture	
Substance name	: HT-18045, 18060, 18065, 18070, 18075	

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
ACETONE	67-64-1	>= 50 - < 70
LIQUIFIED PETROLEUM GASES, SWEETENED	68476-86-8	>= 10 - < 30

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice

: Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.



Version 1.3	Revision Date: 10/31/2017	SDS Number: 600000000076			
If inhaled		If unconsc advice.	esh air. ohysician after significant exposure. ious, place in recovery position and seek medical ns persist, call a physician.		
In ca	ase of skin contact	: If on skin,	rinse well with water.		
In case of eye contact		Remove co Protect un Keep eye	Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.		
If swallowed :		Never give	e milk or alcoholic beverages. anything by mouth to an unconscious person. as persist, call a physician.		
	t important symptoms effects, both acute and yed	and ketosis Irritating to	ial (or a component) has produced hyperglycemia s following substantial ingestion. eyes. e drowsiness or dizziness.		

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Water spray Carbon dioxide (CO2) Dry chemical Alcohol-resistant foam	
Unsuitable extinguishing media	: High volume water jet	
Hazardous combustion prod- ucts	: Carbon oxides Organic acids	
Specific extinguishing meth- ods	: Product is compatible with standard fire-fighting agents.	
Further information	: Use extinguishing measures that are appropriate to local or cumstances and the surrounding environment. Use a water spray to cool fully closed containers.	cir-
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparate	us.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-	:	Use personal protective equipment.
tive equipment and emer-		Remove all sources of ignition.



Version 1.3	Revision Date: 10/31/2017	SDS Number: 600000000076	Date of last issue: 04/18/2017 Date of first issue: 05/23/2016		
gency procedures		Ensure adequate ventilation. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas. Evacuate personnel to safe areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.			
Environmental precautions		Prevent produce Do not flush in	leakage or spillage if safe to do so. et from entering drains. to surface water or sanitary sewer system. contaminates rivers and lakes or drains inform norities.		
	ods and materials for ainment and cleaning up	spray jet.	ck down) gases/vapours/mists with a water I applicable local, state and federal regulations.		

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. Do not spray on a naked flame or any incandescent material.
Advice on safe handling	:	Open drum carefully as content may be under pressure. Provide sufficient air exchange and/or exhaust in work rooms. Do not smoke. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Dispose of rinse water in accordance with local and national regulations. Container hazardous when empty. Smoking, eating and drinking should be prohibited in the ap- plication area. For personal protection see section 8. Do not grind the product. Do not heat the product. Do not breathe vapours or spray mist.
Conditions for safe storage	:	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. No smoking.



Version Revision Date: SDS Number: 1.3 10/31/2017 60000000076

Date of last issue: 04/18/2017 Date of first issue: 05/23/2016

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters					
Engineering measures	:	Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.			
Personal protective equipme	ent				
Respiratory protection	:	In the case of vapour formation use a respirator with an ap- proved filter. In the case of dust or aerosol formation use respirator with an approved filter.			
Hand protection					
Remarks	:	Wear resistant gloves (consult your safety equipment suppli- er). The suitability for a specific workplace should be dis- cussed with the producers of the protective gloves.			
Eye protection	:	Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.			
Skin and body protection	:	Choose body protection according to the amount and con- centration of the dangerous substance at the work place. Wear as appropriate: Impervious clothing Flame-resistant clothing Safety shoes			
Protective measures	:	When using do not eat, drink or smoke. Wear suitable protective equipment.			
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Do not inhale aerosol. Wash hands before breaks and at the end of workday.			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: aerosol
Colour	: clear
Odour	: pleasant
рН	: No data available
Melting point/freezing point	: No data available



Version 1.3	Revision Date: 10/31/2017		5 Number: 000000076	Date of last issue: 04/18/2017 Date of first issue: 05/23/2016	
Boiling point/boiling range		:	-23 - 133 °F No data available		
Flas	sh point	:	-96.11 °C	5	
Eva	poration rate	:	: No data available		
Fla	mmability (solid, gas)	:	No data available	9	
Upp	per explosion limit	:	12.8 %(V)		
Lower explosion limit		:	1.8 %(V)		
Vapour pressure		:	: 307.9692 hPa (25 °C) The value is calculated		
Der	nsity	:	0.7166 g/cm3		
	ubility(ies) Vater solubility	:	partly soluble		
	tition coefficient: n- anol/water	:	No data available	2	
	cosity /iscosity, dynamic	:	No data available	9	
١	iscosity, kinematic	:	No data available	9	
Oxidizing properties		:	No data available	9	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac- tions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Exposure to sunlight. Exposure to moisture Heat
Incompatible materials	: Acids Bases Amines Ammonia halogens isocyanates



Version	Revision Date:	SDS Number:	Date of last is
1.3	10/31/2017	60000000076	Date of first is

Date of last issue: 04/18/2017 Date of first issue: 05/23/2016

Peroxides Reducing agents Strong bases Strong oxidizing agents UV light.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Inhalation Eye contact Skin contact				
Acute toxicity				
<u>Components:</u> ACETONE: Acute oral toxicity	: LD50 (Rat, female): 5,800 mg/kg			
Acute inhalation toxicity	: LC50 (Rat, female): 76 mg/l Exposure time: 4 h Test atmosphere: vapour			
Acute dermal toxicity	: LD50 (Rabbit): > 7,426 mg/kg			

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

ACETONE:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

LIQUIFIED PETROLEUM GASES, SWEETENED:

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin. Causes serious eye irritation.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.



Version	Revision Date:	S
1.3	10/31/2017	6

SDS Number: Date of last issue: 04/18/2017 Date of first issue: 05/23/2016

Components:

ACETONE:

Result: Irritating to eyes. Assessment: Irritating to eyes.

LIQUIFIED PETROLEUM GASES, SWEETENED:

Result: Possibly irritating to eyes

STOT - single exposure

Components:

ACETONE:

Exposure routes: Inhalation Target Organs: Nervous system Assessment: May cause drowsiness or dizziness.

Aspiration toxicity

Product:

No aspiration toxicity classification

Components:

ACETONE:

May be harmful if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.



SDS Number:

60000000076

Version Revision Date: 1.3 10/31/2017

Date of last issue: 04/18/2017 Date of first issue: 05/23/2016

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	 UN 1950 Aerosols, flammable 2.1 Not assigned by regulation 2.1 203 203
IMDG-Code UN number Proper shipping name	: UN 1950 : AEROSOLS
Class Packing group Labels EmS Code Marine pollutant	 2.1 Not assigned by regulation 2.1 F-D, S-U no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR UN/ID/NA number Proper shipping name	: UN 1950 : AEROSOLS
Class Packing group Labels ERG Code Marine pollutant	 2.1 Not assigned by regulation 2.1 126 no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and	Community Right-to-Know Act
---------------------------------------	-----------------------------

SARA 311/312 Hazards	:	Fire Hazard Acute Health Hazard
California Prop. 65		This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other re- productive harm.



Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.3	10/31/2017	60000000076	Date of first issue: 05/23/2016

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information



Revision Date

: 10/31/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN