

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version            Revision Date:            SDS Number:            Date of last issue: 08/15/2018  
3.0                09/06/2018              600000000171        Date of first issue: 05/23/2016

---

### SECTION 1. IDENTIFICATION

Product name                                : RUBBERIZED AERO UNDERCOAT 16 FOZ UN  
Product code                                 : CBO1G012-18

#### Manufacturer or supplier's details

Company name of supplier                : Niteo Products, LLC  
Address                                        : Dallas TX 75225  
Email Address                                : EHS@niteoproducts.com  
Telephone                                     : 1-844-696-4836  
Emergency telephone number             : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use                          : COATING  
Restrictions on use                         : Use only outdoors or in a well-ventilated area.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable aerosols                        : Category 1  
Skin irritation                                : Category 2  
Eye irritation                                 : Category 2A  
Reproductive toxicity                      : Category 2  
Specific target organ toxicity             : Category 3 (Central nervous system)  
- single exposure  
Specific target organ toxicity             : Category 2  
- repeated exposure  
Aspiration hazard                          : Category 1

#### GHS label elements

**Car Brite™ RUBBERIZED AEROSOL  
UNDERCOATING Undercoating Spray**

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

---

Hazard pictograms

:



Signal word

:

Danger

Hazard statements

:

Extremely flammable aerosol.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

:

**Prevention:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
IF ON SKIN: Wash with plenty of soap and water.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 20 - <= 40
Toluene	108-88-3	>= 10 - <= 20
Propane	74-98-6	>= 10 - <= 20
Xylene	1330-20-7	>= 2.5 - <= 10
Limestone	1317-65-3	>= 2.5 - <= 10
Carbon Black	1333-86-4	>= 1 - <= 2.5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs

## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2018
3.0	09/06/2018	600000000171	Date of first issue: 05/23/2016

---

may initiate cardiac arrhythmias in persons exposed to this material.

This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated exposure.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Remove all sources of ignition.  
Ensure adequate ventilation.  
Avoid breathing dust.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Evacuate personnel to safe areas.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.

## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

Prevent product from entering drains.  
Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.  
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm	OSHA Z-1

**SAFETY DATA SHEET**



**Car Brite™ RUBBERIZED AEROSOL  
UNDERCOATING Undercoating Spray**

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

			2,400 mg/m3	
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
Propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Carbon Black	1333-86-4	TWA (Inhalable fraction)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0

**Hazardous components without workplace control parameters**

Components	CAS-No.
Xylene	1330-20-7

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
 Date of first issue: 05/23/2016

				shift (As soon as possible after exposure ceases)		BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.  
 In the case of dust or aerosol formation use respirator with an approved filter.

**Hand protection**

**Remarks** : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

**Eye protection** : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

**Skin and body protection** : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
 Wear as appropriate:  
 Impervious clothing  
 Flame-resistant clothing  
 Safety shoes

**Hygiene measures** : Handle in accordance with good industrial hygiene and safety practice.

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

---

When using do not smoke.  
When using do not eat or drink.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : black

Odour : solvent-like

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : estimated 51.84 °C

Flash point : estimated -104 °C  
Value for Component

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : 11.2 %(V)

Lower explosion limit / Lower flammability limit : 2.2 %(V)  
No data available

Vapour pressure : estimated 2,757 hPa (21 °C)

Density : estimated 0.865 g/cm3

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

---



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2018
3.0	09/06/2018	600000000171	Date of first issue: 05/23/2016

---

Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Acids halogens Strong oxidizing agents Fluorine
Hazardous decomposition products	:	Carbon oxides

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Eye contact  
Ingestion

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: 59.27 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

#### Components:

##### Acetone:

Acute oral toxicity	:	LD50 (Rat, female): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, female): 76 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): > 7,426 mg/kg

##### Toluene:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, males): 25.7 mg/l Exposure time: 4 h

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

---

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

### **Xylene:**

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

### **Limestone:**

Acute oral toxicity : LD50 (Rat): 6,450 mg/kg

### **Carbon Black:**

Acute oral toxicity : LD50 (Rat): 8,000 mg/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Product:**

Remarks: May cause skin irritation and/or dermatitis.

### **Components:**

#### **Acetone:**

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

#### **Toluene:**

Result: Irritating to skin.

#### **Xylene:**

Assessment: Irritating to skin.

Result: Irritating to skin.

#### **Limestone:**

Result: Possibly irritating to skin

#### **Carbon Black:**

Species: Rabbit

Result: No skin irritation

**Car Brite™ RUBBERIZED AEROSOL  
UNDERCOATING Undercoating Spray**

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

---

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Components:****Acetone:**

Result: Irritating to eyes.  
Assessment: Irritating to eyes.

**Toluene:**

Result: Irritating to eyes.

**Xylene:**

Result: Irritating to eyes.

**Limestone:**

Result: Possibly irritating to eyes

**Carbon Black:**

Species: Rabbit  
Result: No eye irritation

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Carbon Black:**

Test Type: Buehler Test  
Species: Guinea pig  
Assessment: Does not cause skin sensitisation.  
Method: OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Propane:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

---

Result: negative

### Carbon Black:

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Result: negative

### Carcinogenicity

Not classified based on available information.

**IARC** Group 2B: Possibly carcinogenic to humans

Carbon Black 1333-86-4

### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

### NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Suspected of damaging the unborn child.

### Components:

#### Toluene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

### STOT - single exposure

May cause drowsiness or dizziness.

### Components:

#### Acetone:

Exposure routes: Inhalation  
Target Organs: Nervous system  
Assessment: May cause drowsiness or dizziness.

#### Toluene:

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

#### Xylene:

Assessment: May cause drowsiness or dizziness., May cause respiratory irritation.

### STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

---

### **Product:**

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### **Components:**

#### **Toluene:**

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Components:**

#### **Acetone:**

May be harmful if swallowed and enters airways.

#### **Toluene:**

May be fatal if swallowed and enters airways.

#### **Xylene:**

May be fatal if swallowed and enters airways.

### **Further information**

#### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

---

## SECTION 12. ECOLOGICAL INFORMATION

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

### SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

##### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

UN/ID/NA number : UN 1950  
Proper shipping name : Aerosols  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know Act

##### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	1000
Xylene	1330-20-7	100	100 (F003)

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000171      Date of last issue: 08/15/2018  
Date of first issue: 05/23/2016

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene	108-88-3	>= 20 - < 30 %
---------	----------	----------------


### California Prop. 65

WARNING: This product can expose you to chemicals including Carbon Black, which is/are known to the State of California to cause cancer, and Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

# SAFETY DATA SHEET



## Car Brite™ RUBBERIZED AEROSOL UNDERCOATING Undercoating Spray

Version	Revision Date:	SDS Number:	Date of last issue: 08/15/2018
3.0	09/06/2018	600000000171	Date of first issue: 05/23/2016

---

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN