

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

### SECTION 1. IDENTIFICATION

Product name : VP&C LIGHT BIEGE DYE HT201 12/1  
Product code : 851627

#### Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC  
Address : Dallas TX 75225  
Email Address : EHS@niteoproducts.com  
Telephone : 1-844-696-4836  
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

#### Recommended use of the chemical and restrictions on use

Recommended use : DYES  
Restrictions on use : Use only outdoors or in a well-ventilated area.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Flammable aerosols : Category 1  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Respiratory system, Central nervous system)  
Specific target organ toxicity - repeated exposure : Category 2 (Auditory system)  
Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))

#### GHS label elements

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: Extremely flammable aerosol.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Suspected of causing cancer.  
Suspected of damaging the unborn child.  
May cause damage to organs (Auditory system) through prolonged or repeated exposure.  
May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
IF ON SKIN: Wash with plenty of soap and water.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/ attention.  
If skin irritation occurs: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.

**Storage:**  
Store in a well-ventilated place. Keep container tightly closed. Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	$\geq 30 - \leq 40$
Toluene	108-88-3	$\geq 10 - \leq 20$
Methyl ethyl ketone	78-93-3	$\geq 1 - \leq 10$
Butanol normal	71-36-3	$\geq 1 - \leq 10$
Xylene	1330-20-7	$\geq 1 - \leq 10$
Titanium dioxide	13463-67-7	$\geq 1 - \leq 10$
Limestone	1317-65-3	$\geq 1 - \leq 10$
Ethylbenzene	100-41-4	$\geq 0.1 - \leq 1$
Methyl isobutyl ketone	108-10-1	$\geq 0.1 - \leq 1$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.  
Remove contaminated clothing. If irritation develops, get medical attention.  
If on skin, rinse well with water.  
Wash contaminated clothing before re-use.  
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.

## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version	Revision Date:	SDS Number:	Date of last issue: 05/25/2018
3.0	09/06/2018	600000000844	Date of first issue: 05/23/2016

---

May cause drowsiness or dizziness.  
 Suspected of causing cancer.  
 Suspected of damaging the unborn child.  
 May cause damage to organs through prolonged or repeated exposure.  
 Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.  
 This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

---

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical  
 Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
 Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
 Remove all sources of ignition.  
 Ensure adequate ventilation.  
 Avoid breathing dust.  
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
 Evacuate personnel to safe areas.  
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.  
 Prevent product from entering drains.

## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version	Revision Date:	SDS Number:	Date of last issue: 05/25/2018
3.0	09/06/2018	600000000844	Date of first issue: 05/23/2016

Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Keep away from open flames, hot surfaces and sources of ignition.  
Use only explosion-proof equipment.  
Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapours/dust.  
Do not smoke.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
Dispose of rinse water in accordance with local and national regulations.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm	OSHA Z-1

**SAFETY DATA SHEET**



**Car Brite™ VP&C LIGHT BEIGE DYE DYES**

Version  
3.0

Revision Date:  
09/06/2018

SDS Number:  
600000000844

Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

			2,400 mg/m3	
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
Methyl ethyl ketone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	OSHA P0
		STEL	300 ppm 885 mg/m3	OSHA P0
Butanol normal	71-36-3	TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m3	NIOSH REL
		TWA	100 ppm 300 mg/m3	OSHA Z-1
		C	50 ppm 150 mg/m3	OSHA P0
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL

**SAFETY DATA SHEET**



**Car Brite™ VP&C LIGHT BEIGE DYE DYES**

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
 Date of first issue: 05/23/2016

		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA P0
		STEL	125 ppm 545 mg/m3	OSHA P0
Methyl isobutyl ketone	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		ST	75 ppm 300 mg/m3	NIOSH REL
		TWA	50 ppm 205 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	50 ppm 205 mg/m3	OSHA P0
		STEL	75 ppm 300 mg/m3	OSHA P0

**Hazardous components without workplace control parameters**

Components	CAS-No.
Xylene	1330-20-7

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As	0.3 mg/g Creatinine	ACGIH BEI

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
 Date of first issue: 05/23/2016

				soon as possible after exposure ceases)		
Methyl ethyl ketone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
Methyl isobutyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.  
 In the case of dust or aerosol formation use respirator with an approved filter.

**Hand protection**

**Remarks** : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

**Eye protection** : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

**Skin and body protection** : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
 Wear as appropriate:  
 Impervious clothing  
 Flame-resistant clothing  
 Safety shoes

**Hygiene measures** : Handle in accordance with good industrial hygiene and safety



# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

practice.  
When using do not smoke.  
When using do not eat or drink.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : coloured

Odour : hydrocarbon-like

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : -97 °C  
Value for Component

Evaporation rate : > 1

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : 12.8 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapour pressure : 85.0000 mmHg (60.00 °F)

Density : 0.834 g/cm<sup>3</sup>

Solubility(ies)  
Water solubility : practically insoluble

Partition coefficient: n-octanol/water : No data available

Viscosity  
Viscosity, dynamic : No data available  
Viscosity, kinematic : No data available

Oxidizing properties : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

---

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

Possibility of hazardous reactions : No decomposition if stored and applied as directed.  
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents

Hazardous decomposition products : Carbon oxides

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: 4,668 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 53.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

#### Components:

##### Acetone:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

##### Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

##### Methyl ethyl ketone:

Acute oral toxicity : LD50 (Rat): 2,300 - 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 23,500 mg/m3

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

Exposure time: 8 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

### **Butanol normal:**

Acute oral toxicity : LD50 (Rat): 790 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 17.76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 3,400 mg/kg

### **Xylene:**

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

### **Titanium dioxide:**

Acute oral toxicity : LD50 (Rat): > 24,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 10,000 mg/kg

### **Limestone:**

Acute oral toxicity : LD50 (Rat): 6,450 mg/kg

### **Ethylbenzene:**

Acute oral toxicity : LD50 (Rat): ca. 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 17,800 mg/kg

### **Methyl isobutyl ketone:**

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

Acute oral toxicity : LD50 (Rat): 2,080 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 8.2 - 16.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 3.0 g/kg

### **Skin corrosion/irritation**

Causes skin irritation.

### **Product:**

Remarks: May cause skin irritation and/or dermatitis.

### **Components:**

#### **Acetone:**

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

#### **Toluene:**

Result: Irritating to skin.

#### **Methyl ethyl ketone:**

Result: No skin irritation

#### **Butanol normal:**

Assessment: Irritating to skin.

Result: Irritating to skin.

#### **Xylene:**

Assessment: Irritating to skin.

Result: Irritating to skin.

#### **Titanium dioxide:**

Result: Possibly irritating to skin

#### **Limestone:**

Result: Possibly irritating to skin

#### **Ethylbenzene:**

Result: Irritating to skin.

#### **Methyl isobutyl ketone:**

Species: Rabbit

Method: OECD Test Guideline 404

## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version	Revision Date:	SDS Number:	Date of last issue: 05/25/2018
3.0	09/06/2018	600000000844	Date of first issue: 05/23/2016

---

Result: No skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Product:**

Result: Irritating to eyes.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

#### **Components:**

##### **Acetone:**

Result: Irritating to eyes.

Assessment: Irritating to eyes.

##### **Toluene:**

Result: Irritating to eyes.

##### **Methyl ethyl ketone:**

Result: Irritating to eyes.

##### **Butanol normal:**

Result: Irreversible effects on the eye

##### **Xylene:**

Result: Irritating to eyes.

##### **Titanium dioxide:**

Result: Possibly irritating to eyes

##### **Limestone:**

Result: Possibly irritating to eyes

##### **Ethylbenzene:**

Result: Irritating to eyes.

##### **Methyl isobutyl ketone:**

Result: Irritating to eyes.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

**Car Brite™ VP&C LIGHT BEIGE DYE DYES**

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
 Date of first issue: 05/23/2016

**Components:**
**Methyl isobutyl ketone:**

Test Type: Maximisation Test  
 Species: Guinea pig  
 Assessment: Did not cause sensitisation on laboratory animals.  
 Method: OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:**
**Methyl isobutyl ketone:**

Genotoxicity in vitro : Test Type: Ames test  
 Test system: Salmonella typhimurium  
 Metabolic activation: with and without metabolic activation  
 Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)  
 Result: negative

Genotoxicity in vivo : Species: Mouse  
 Cell type: Bone marrow  
 Method: OECD Test Guideline 474  
 Result: negative

**Carcinogenicity**

Suspected of causing cancer.

**Components:**
**Titanium dioxide:**

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

**Ethylbenzene:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

**IARC**

Group 2B: Possibly carcinogenic to humans

Titanium dioxide                      13463-67-7

Ethylbenzene                            100-41-4

Methyl isobutyl ketone                108-10-1

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Car Brite™ VP&C LIGHT BEIGE DYE DYES**

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

**Reproductive toxicity**

Suspected of damaging the unborn child.

**Components:**

**Toluene:**

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure**

May cause respiratory irritation.  
May cause drowsiness or dizziness.

**Components:**

**Acetone:**

Exposure routes: Inhalation  
Target Organs: Nervous system  
Assessment: May cause drowsiness or dizziness.

**Toluene:**

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

**Methyl ethyl ketone:**

Assessment: May cause drowsiness or dizziness.

**Butanol normal:**

Target Organs: Respiratory system  
Assessment: May cause respiratory irritation.

Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

**Xylene:**

Assessment: May cause drowsiness or dizziness., May cause respiratory irritation.

**Methyl isobutyl ketone:**

Exposure routes: Inhalation  
Target Organs: Respiratory Tract  
Assessment: May cause respiratory irritation.

**STOT - repeated exposure**

May cause damage to organs (Auditory system) through prolonged or repeated exposure.  
May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

**Components:**

**Toluene:**

Exposure routes: Inhalation

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0	Revision Date: 09/06/2018	SDS Number: 600000000844	Date of last issue: 05/25/2018 Date of first issue: 05/23/2016
----------------	------------------------------	-----------------------------	---

---

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

### **Ethylbenzene:**

Target Organs: Auditory system

Assessment: May cause damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration toxicity classification

### **Components:**

#### **Acetone:**

May be harmful if swallowed and enters airways.

#### **Toluene:**

May be fatal if swallowed and enters airways.

#### **Methyl ethyl ketone:**

May be harmful if swallowed and enters airways.

#### **Xylene:**

May be fatal if swallowed and enters airways.

#### **Ethylbenzene:**

May be fatal if swallowed and enters airways.

#### **Methyl isobutyl ketone:**

May be harmful if swallowed and enters airways.

### **Further information**

#### **Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

---

## SECTION 12. ECOLOGICAL INFORMATION

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and



# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

---

federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

### SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

#### International Regulations

##### IATA-DGR

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

##### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### National Regulations

##### 49 CFR

UN/ID/NA number : UN 1950  
Proper shipping name : Aerosols  
  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
ERG Code : 126  
Marine pollutant : no

---

### SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version 3.0      Revision Date: 09/06/2018      SDS Number: 600000000844      Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	1000
Xylene	1330-20-7	100	100 (F003)

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene	108-88-3	>= 10 - <= 20 %
Butanol normal	71-36-3	>= 1 - <= 10 %
Ethylbenzene	100-41-4	>= 0.1 - <= 1 %
Methyl isobutyl ketone	108-10-1	>= 0.1 - <= 1 %

### California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, Methyl isobutyl ketone, which is/are known to the State of California to cause cancer, and Toluene, Methyl isobutyl ketone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# SAFETY DATA SHEET



## Car Brite™ VP&C LIGHT BEIGE DYE DYES

Version  
3.0

Revision Date:  
09/06/2018


SDS Number:  
600000000844

Date of last issue: 05/25/2018  
Date of first issue: 05/23/2016

### SECTION 16. OTHER INFORMATION

#### Further information

#### NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN