

ASHLAND®		Page: 1
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Car Brite™ KOLOR KOTE - DARK BLUE METALLIC
Aerosol Carpet & Vinyl Dye

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America EHS Customer Requests@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable aerosols : Category 1

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 1

Reproductive toxicity : Category 2

Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ systemic toxicity - repeated exposure : Category 2 (Auditory system)

Specific target organ systemic toxicity - repeated exposure (Inhalation) : Category 2 (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on colour vision))

GHS Label element

ASHLAND®		Page: 2
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

Extremely flammable aerosol.
Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Auditory system) through prolonged or repeated exposure.
May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on colour vision)) through prolonged or repeated exposure if inhaled.

Precautionary Statements :

Prevention:
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

ASHLAND®		Page: 3
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Aspiration hazard
 Chemical nature : Static Accumulator
 Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
ACETONE	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	34.99
TOLUENE	108-88-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Repr. 2; H361 STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304	19.99
METHYL ETHYL KETONE	78-93-3	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	9.99

SAFETY DATA SHEET

Revision Date: 05/22/2015

Print Date: 7/24/2015

SDS Number: R0411195

 Car Brite™ KOLOR KOTE - DARK BLUE METALLIC
 Aerosol Carpet & Vinyl Dye

Version: 1.0

CBO1G014-0012

BUTANOL NORMAL	71-36-3	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335, H336	4.99
XYLENE	1330-20-7	Flam. Liq. 3; H226 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335, H336 Asp. Tox. 1; H304	4.99
TALC	14807-96-6	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	4.99
LIMESTONE	1317-65-3		4.99
ETHYL BENZENE	100-41-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT RE 2; H373 Asp. Tox. 1; H304	2.49

ASHLAND®		Page: 5
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

--	--	--	--

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If unconscious place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Obtain medical attention.
Do NOT induce vomiting.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.
Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
redness of the skin
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Cough
discomfort in the chest

ASHLAND®		Page: 6
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

temporary changes in mood and behavior
 effects on memory
 Blurred vision
 Shortness of breath
 confusion
 irregular heartbeat
 Harmful if swallowed.
 Causes skin irritation.
 Causes serious eye damage.
 May cause drowsiness or dizziness.
 Suspected of damaging fertility or the unborn child.
 May cause damage to organs through prolonged or repeated exposure.
 May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO2)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 toxic fumes
 Aldehydes
 calcium oxide
- Specific extinguishing methods :
 Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must

ASHLAND®		Page: 7
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and

ASHLAND®		Page: 8
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

kept upright to prevent leakage.
 Observe label precautions.
 No smoking.
 Electrical installations / working materials must comply with
 the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ACETONE	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		REL	250 ppm 590 mg/m3	NIOSH/GUIDE
		PEL	1,000 ppm 2,400 mg/m3	OSHA_TRANS
		TWA	250 ppm	ACGIHLIS_P
		STEL	500 ppm	ACGIHLIS_P
		TWA	750 ppm 1,800 mg/m3	Z1A
TOLUENE	108-88-3	STEL	1,000 ppm 2,400 mg/m3	Z1A
		TWA	20 ppm	ACGIH
		REL	100 ppm 375 mg/m3	NIOSH/GUIDE
		STEL	150 ppm 560 mg/m3	NIOSH/GUIDE
		TWA	200 ppm	OSHA/Z2
		Ceiling	300 ppm	OSHA/Z2
		MAX. CONC	500 ppm	OSHA/Z2
METHYL ETHYL KETONE	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		REL	200 ppm 590 mg/m3	NIOSH/GUIDE
		STEL	300 ppm 885 mg/m3	NIOSH/GUIDE
		PEL	200 ppm 590 mg/m3	OSHA_TRANS
BUTANOL NORMAL	71-36-3	TWA	20 ppm	ACGIH
		Ceil_Time	50 ppm 150 mg/m3	NIOSH/GUIDE
		PEL	100 ppm 300 mg/m3	OSHA_TRANS
XYLENE	1330-20-7	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH

SAFETY DATA SHEET

Revision Date: 05/22/2015

Print Date: 7/24/2015

SDS Number: R0411195

Version: 1.0

 Car Brite™ KOLOR KOTE - DARK BLUE METALLIC
 Aerosol Carpet & Vinyl Dye

CBO1G014-0012

		PEL	100 ppm 435 mg/m3	OSHA_TRANS
		REL	100 ppm 435 mg/m3	NIOSH/GUIDE
		STEL	150 ppm 655 mg/m3	NIOSH/GUIDE
TALC	14807-96-6	TWA	2 mg/m3 Respirable fraction.	ACGIH
		REL	2 mg/m3 Respirable.	NIOSH/GUIDE
		TWA	0.1 mg/m3 Respirable.	Z3
		TWA	0.3 mg/m3 Total dust.	Z3
LIMESTONE	1317-65-3	REL	10 mg/m3 Total	NIOSH/GUIDE
		REL	5 mg/m3 Respirable.	NIOSH/GUIDE
		PEL	5 mg/m3 Respirable fraction.	OSHA_TRANS
		PEL	15 mg/m3 Total dust.	OSHA_TRANS
		TWA	15 mg/m3 Total dust.	Z1A
		TWA	5 mg/m3 Respirable fraction.	Z1A
ETHYL BENZENE	100-41-4	TWA	20 ppm	ACGIH
		REL	100 ppm 435 mg/m3	NIOSH/GUIDE
		STEL	125 ppm 545 mg/m3	NIOSH/GUIDE
		PEL	100 ppm 435 mg/m3	OSHA_TRANS

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
ACETONE	67-64-1	acetone	Urine	Sampling time: End of shift.	50 mg/l	
Remarks:	Nonspecific					
TOLUENE	108-88-3	o-Cresol, with hydrolysis	Creatinine in urine	Sampling time: End of shift.	0.3 mg/g	
Remarks:	Background					
		toluene	Urine	Sampling	0.03 mg/l	

ASHLAND®		Page: 10
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

				g time: End of shift.		
		toluene	Blood	Samplin g time: Prior to last shift of work week.	0.02 mg/l	
METHYL ETHYL KETONE	78-93-3	methylEthyl Ketone	Urine	Samplin g time: End of shift.	2 mg/l	ACGIH BEI
Remarks:	Nonspecific					
XYLENE	1330-20-7	Methylhippu ric acids	Creatinine in urine	Samplin g time: End of shift.	1.5 g/g	
ETHYL BENZENE	100-41-4	Sum of mandelic acid and phenylglyox ylic acid	Creatinine in urine	Samplin g time: End of shift.	0.15 g/g	ACGIH BEI
Remarks:	Nonspecific					

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles and face shield when there is

ASHLAND®		Page: 11
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

potential for exposure of the eyes or face to liquid, vapor or mist.
Maintain eye wash station in immediate work area.

Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : aerosol

Colour : coloured

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

: No data available

: No data available

Flash point : -155 °F / -104 °C
Value for Component

Evaporation rate : > 1
n-Butyl Acetate

Flammability (solid, gas) :

: No data available

Flammability (liquids) : Static Accumulating liquid

Flammability (liquids) : Static Accumulating liquid

Flammability (liquids) :

Upper explosion limit : 12.8 %(V)

ASHLAND®		Page: 12
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Lower explosion limit : 1.0 %(V)

Vapour pressure : 85.0000 mmHg (60.00 °F)

Relative vapour density : > 1(Air = 1.0)

Relative density : No data available

Density : < 1 g/cm3 (15.5 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
excessive heat

Incompatible materials : Acids
Alkali metals
alkalis
ammonium salts
aluminum
aluminum salts
Amines
Ammonia
Copper

ASHLAND		Page: 13
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Copper alloys
 Fluorine
 halogens
 Lead
 peroxides
 Reducing agents
 strong alkalis
 Strong oxidizing agents

Hazardous decomposition
 products

calcium oxide
 carbon dioxide and carbon monoxide
 Hydrocarbons
 toxic fumes

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
 Skin contact
 Eye Contact
 Ingestion

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : LD50 : 636 mg/kg

Acute inhalation toxicity : LC50 : 23500 ppm

Components:

ACETONE:

Acute oral toxicity : LD 50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC 50 (Rat, female): 76 mg/l
 Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): > 7,426 mg/kg

TOLUENE:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 8000 ppm
 Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): 12,124 mg/kg

METHYL ETHYL KETONE:

Acute oral toxicity : LD 50 (Rat): 2,300 - 3,500 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5 g/kg

ASHLAND®		Page: 14
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

BUTANOL NORMAL:

Acute oral toxicity : LD 50 (Rat): 790 mg/kg

Acute inhalation toxicity : LC 50 (Rat): > 24 mg/l
Exposure time: 4 h
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): 3,400 mg/kg

XYLENE:

Acute oral toxicity : LD 50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 6700 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rabbit): 1,700 mg/kg

LIMESTONE:

Acute oral toxicity : LD 50 (Rat): 6,450 mg/kg

ETHYL BENZENE:

Acute oral toxicity : LD 50 (Rat): ca. 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rabbit): 17,800 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

Components:

ACETONE:

Result: Mildly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

TOLUENE:

Result: Irritating to skin

METHYL ETHYL KETONE:

Result: Not irritating to skin

BUTANOL NORMAL:

Result: Irritating to skin

ASHLAND®		Page: 15
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

XYLENE:

Result: Irritating to skin

TALC:

Result: Possibly irritating to skin

LIMESTONE:

Result: Possibly irritating to skin

ETHYL BENZENE:

Result: Irritating to skin

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

ACETONE:

Result: Irritating to eyes

TOLUENE:

Result: Irritating to eyes

METHYL ETHYL KETONE:

Result: Irritating to eyes

BUTANOL NORMAL:

Result: Corrosive to eyes

XYLENE:

Result: Irritating to eyes

TALC:

Result: Possibly irritating to eyes

LIMESTONE:

Result: Possibly irritating to eyes

ETHYL BENZENE:

Result: Irritating to eyes

Remarks: Exposure to a concentration of 5000 ppm causes intolerable irritation of the eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

ASHLAND®		Page: 16
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Components:

TOLUENE:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ACETONE:

Exposure routes: Inhalation
Target Organs: Nervous system
Assessment: May cause drowsiness or dizziness.

TOLUENE:

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

METHYL ETHYL KETONE:

Assessment: May cause drowsiness or dizziness.

BUTANOL NORMAL:

Target Organs: Respiratory system
Assessment: May cause respiratory irritation.

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

XYLENE:

Assessment: May cause respiratory irritation., May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Auditory system) through prolonged or repeated exposure.
May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on colour vision)) through prolonged or repeated exposure if inhaled.

Components:

TOLUENE:

Exposure routes: Inhalation
Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on colour vision)
Assessment: May cause damage to organs through prolonged or repeated exposure.

ETHYL BENZENE:

Target Organs: Auditory system
Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

ACETONE:

ASHLAND®		Page: 17
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

May be harmful if swallowed and enters airways.

TOLUENE:

May be fatal if swallowed and enters airways.

METHYL ETHYL KETONE:

May be harmful if swallowed and enters airways.

XYLENE:

May be fatal if swallowed and enters airways.

ETHYL BENZENE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

METHYL ETHYL KETONE:

Remarks: Central nervous system

ETHYL BENZENE:

Remarks: Central nervous system

Carcinogenicity:

IARC

Group 2B: Possibly carcinogenic to humans

TALC 14807-96-6

ETHYL BENZENE 100-41-4

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

ACETONE:

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 4,740 - 6,330 mg/l

ASHLAND®		Page: 18
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Exposure time: 96 h
Test Type: static test

LC 50 (Fathead minnow (*Pimephales promelas*)): 8,733 - 9,482 mg/l

Exposure time: 96 h
Test Type: flow-through test

Toxicity to algae : NOEC (*Microcystis aeruginosa*): 530 mg/l
Exposure time: 8 d
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): 2,112 mg/l
Exposure time: 28 d
Test Type: flow-through test

TOLUENE:

Toxicity to fish : LC50 (*Oncorhynchus kisutch* (coho salmon)): 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Ceriodaphnia dubia*): 3.78 mg/l
Exposure time: 48 h
Remarks: Mortality

Toxicity to algae : EC50 (*Pseudokirchneriella subcapitata* (microalgae)): > 433 mg/l
End point: Growth inhibition
Exposure time: 96 h

NOEC (*Scenedesmus quadricauda* (Green algae)): > 400 mg/l
End point: Growth inhibition
Exposure time: 7 d

Toxicity to fish (Chronic toxicity) : NOEC (*Oncorhynchus mykiss* (rainbow trout)): 1.39 mg/l
Exposure time: 40 d
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Ceriodaphnia dubia*): 0.74 mg/l
Exposure time: 7 d

METHYL ETHYL KETONE:

Toxicity to fish : LC 50 (*Fathead minnow* (*Pimephales promelas*)): 3,130 - 3,320 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (*Water flea* (*Daphnia magna*)): 4,025 - 6,440 mg/l
Exposure time: 48 h
Test Type: static test

ASHLAND®		Page: 19
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Remarks: Intoxication

BUTANOL NORMAL:

Toxicity to fish : LC 50 (Bluegill (*Lepomis macrochirus*)): > 100 - 500 mg/l
 Exposure time: 96 h
 Test Type: static test
 Method: Static
 Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (*Daphnia magna*)): 1,897 - 2,072 mg/l
 Exposure time: 48 h
 Test Type: static test
 Method: Static
 Remarks: Intoxication

XYLENE:

Toxicity to fish : LC 50 (Fathead minnow (*Pimephales promelas*)): 23.53 - 29.97 mg/l
 Exposure time: 96 h
 Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (*Daphnia magna*)): > 100 - < 1,000 mg/l
 Exposure time: 24 h
 Test Type: static test

ETHYL BENZENE:

Toxicity to fish : LC 50 (Fathead minnow (*Pimephales promelas*)): 9.1 - 15.6 mg/l
 Exposure time: 96 h
 Test Type: static test

LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*)): 4.2 mg/l
 Exposure time: 96 h
 Test Type: Renewal

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (*Daphnia magna*)): 1.37 - 4.4 mg/l
 Exposure time: 48 h
 Test Type: static test

Toxicity to algae : (*Pseudokirchneriella subcapitata* (green algae)): 3.6 mg/l
 End point: EC 50
 Exposure time: 96 h
 Test Type: Growth inhibition

Persistence and degradability

Components:

ACETONE:

Biodegradability : Result: Readily biodegradable
 Biodegradation: 90.9 %
 Exposure time: 28 d

ASHLAND®		Page: 20
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Method: OECD Test Guideline 301B

TOLUENE:

Biodegradability : Result: Readily biodegradable

BUTANOL NORMAL:

Biodegradability : Result: Readily biodegradable
Biodegradation: 98 %
Exposure time: 19 d
Method: OECD Test Guideline 301E

Biochemical Oxygen Demand (BOD) : Theoretical oxygen demand
2.59 mg/g

Chemical Oxygen Demand (COD) : 2.45 mg/g
Method: Chemical oxygen demand

XYLENE:

Physico-chemical removability : Remarks: The product evaporates readily.

ETHYL BENZENE:

Biodegradability : Result: Readily biodegradable
Biodegradation: 70 - 80 %
Exposure time: 28 d

Bioaccumulative potential

Components:

ACETONE:

Partition coefficient: n-octanol/water : log Pow: -0.24

TOLUENE:

Bioaccumulation : Species: Ide, silver or golden orfe (Leuciscus idus)
Bioconcentration factor (BCF): 94
Exposure time: 3 d
Concentration: 0.05 mg/l
Method: Not reported

Partition coefficient: n-octanol/water : log Pow: 2.73

METHYL ETHYL KETONE:

Partition coefficient: n-octanol/water : log Pow: 0.29

BUTANOL NORMAL:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 0.38
Exposure time: 24 h

ASHLAND®		Page: 21
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Concentration: 921 mg/l
Method: Static

Partition coefficient: n-octanol/water : log Pow: 0.88

XYLENE:
Partition coefficient: n-octanol/water : log Pow: 3.16

ETHYL BENZENE:
Partition coefficient: n-octanol/water : log Pow: 3.15

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

**International transport regulations
REGULATION**

SAFETY DATA SHEET

Revision Date: 05/22/2015

Print Date: 7/24/2015

SDS Number: R0411195

Version: 1.0

Car Brite™ KOLOR KOTE - DARK BLUE METALLIC
Aerosol Carpet & Vinyl Dye

CBO1G014-0012

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

	ORM-D, CONSUMER COMMODITY	ORM			
--	---------------------------	-----	--	--	--

U.S. DOT - RAIL

	ORM-D, CONSUMER COMMODITY	ORM			
--	---------------------------	-----	--	--	--

U.S. DOT - INLAND WATERWAYS

	ORM-D, CONSUMER COMMODITY	ORM			
--	---------------------------	-----	--	--	--

TRANSPORT CANADA - ROAD

UN	1950 AEROSOLS	2.1			LIMITED QUANTITY
----	---------------	-----	--	--	------------------

TRANSPORT CANADA - RAIL

UN	1950 AEROSOLS	2.1			LIMITED QUANTITY
----	---------------	-----	--	--	------------------

TRANSPORT CANADA - INLAND WATERWAYS

UN	1950 AEROSOLS	2.1			LIMITED QUANTITY
----	---------------	-----	--	--	------------------

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1950 AEROSOLS	2.1			LIMITED QUANTITY
----	---------------	-----	--	--	------------------

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1950 Aerosols, flammable	2.1			
----	--------------------------	-----	--	--	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1950 Aerosols, flammable	2.1			
----	--------------------------	-----	--	--	--

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1950 AEROSOLS	2			
----	---------------	---	--	--	--

ASHLAND®		Page: 23
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
XYLENE	1330-20-7	100	2000.040001

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)

TOLUENE	108-88-3	19.99 %
BUTANOL NORMAL	71-36-3	4.99 %
XYLENE	1330-20-7	4.99 %
ETHYL BENZENE	100-41-4	2.49 %

Pennsylvania Right To Know

CONTENTS PARTIALLY UNKNOWN	Not Assigned	30.00 - 50.00 %
ACETONE	67-64-1	30.00 - 50.00 %
LIQUIFIED PETROLEUM GASES, SWEETENED	68476-86-8	20.00 - 30.00 %
TOLUENE	108-88-3	10.00 - 20.00 %
METHYL ETHYL KETONE	78-93-3	5.00 - 10.00 %
BUTANOL NORMAL	71-36-3	1.00 - 5.00 %
XYLENE	1330-20-7	1.00 - 5.00 %
TALC	14807-96-6	1.00 - 5.00 %

SAFETY DATA SHEET

Revision Date: 05/22/2015

Print Date: 7/24/2015

SDS Number: R0411195

Car Brite™ KOLOR KOTE - DARK BLUE METALLIC
Aerosol Carpet & Vinyl Dye

Version: 1.0

CBO1G014-0012

LIMESTONE 1317-65-3 1.00 - 5.00 %

ETHYL BENZENE 100-41-4 1.00 - 5.00 %

New Jersey Right To Know

CONTENTS PARTIALLY UNKNOWN Not Assigned 30.00 - 50.00 %

ACETONE 67-64-1 30.00 - 50.00 %

LIQUIFIED PETROLEUM GASES,
SWEETENED 68476-86-8 20.00 - 30.00 %

TOLUENE 108-88-3 10.00 - 20.00 %

METHYL ETHYL KETONE 78-93-3 5.00 - 10.00 %

BUTANOL NORMAL 71-36-3 1.00 - 5.00 %

XYLENE 1330-20-7 1.00 - 5.00 %

TALC 14807-96-6 1.00 - 5.00 %

LIMESTONE 1317-65-3 1.00 - 5.00 %

ETHYL BENZENE 100-41-4 1.00 - 5.00 %

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

ETHYL BENZENE 100-41-4

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

TOLUENE 108-88-3

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.

AUSTR : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECL : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

ASHLAND®		Page: 25
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 05/22/2015

<p>NFPA:</p> <p style="text-align: center;">Flammability</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">Health 2</div> <div style="text-align: center;"> </div> <div style="text-align: center;">Instability 0</div> </div> <p style="text-align: center;">Special hazard.</p>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white; text-align: center;">HEALTH</td> <td style="text-align: center;">2*</td> </tr> <tr> <td style="background-color: red; color: white; text-align: center;">FLAMMABILITY</td> <td style="text-align: center;">4</td> </tr> <tr> <td style="background-color: yellow; text-align: center;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2*	FLAMMABILITY	4	PHYSICAL HAZARD	0
HEALTH	2*						
FLAMMABILITY	4						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Not applicable

Full text of H-Statements referred to under sections 2 and 3.

- H225 Highly flammable liquid and vapor.
- H226 Flammable liquid and vapor.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

Sources of key data used to compile the Safety Data Sheet
 Ashland internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

ASHLAND®		Page: 26
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System

ASHLAND®		Page: 27
SAFETY DATA SHEET		Revision Date: 05/22/2015
		Print Date: 7/24/2015
		SDS Number: R0411195
Car Brite™ KOLOR KOTE - DARK BLUE METALLIC Aerosol Carpet & Vinyl Dye		Version: 1.0
CBO1G014-0012		