Ozium® AIR SANITIZER SPRAY CARBON BLACK

Version Revision Date: SDS Number: Date of last issue: 04/09/2024 1.7 04/10/2024 600000001961 Date of first issue: 09/30/2019

SECTION 1. IDENTIFICATION

Product name : AC OZIUM 3.50Z CARB BLK 48/4

Product code : OZM-26

Manufacturer or supplier's details

Company name of supplier : OZIUM Holdings, LLC

Address : 5949 Sherry Lane, Suite 540, Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-800-678-1910

Emergency telephone num-

ber

: 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : SANITIZER

EPA Reg. No. 51838-2

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : Flammable aerosol.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause drowsiness or dizziness.

Ozium® AIR SANITIZER SPRAY CARBON BLACK

Version Revision Date: SDS Number: Date of last issue: 04/09/2024 1.7 04/10/2024 600000001961 Date of first issue: 09/30/2019

Precautionary statements

Prevention:

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding $50 \, ^{\circ}\text{C} / 122 \, ^{\circ}\text{F}$.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Isopropanol	67-63-0	>= 30 - < 50
1,1-Difluoroethane	75-37-6	>= 5 - < 10
Petroleum gases, liquefied, sweetened	68476-86-8	>= 20 - < 30
Propylene glycol	57-55-6	>= 1 - < 5
(E)-2-benzylideneoctanal	165184-98-5	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

Ozium® AIR SANITIZER SPRAY CARBON BLACK

Version Revision Date: SDS Number: Date of last issue: 04/09/2024 1.7 04/10/2024 600000001961 Date of first issue: 09/30/2019

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

Carbon oxides

Halogenated compounds

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Ozium® AIR SANITIZER SPRAY CARBON BLACK

Version Revision Date: SDS Number: Date of last issue: 04/09/2024 1.7 04/10/2024 600000001961 Date of first issue: 09/30/2019

for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 $^{\circ}$ C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

olace.

Containers which are opened must be carefully resealed and

Ozium® AIR SANITIZER SPRAY CARBON BLACK

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/09/2024

 1.7
 04/10/2024
 600000001961
 Date of first issue: 09/30/2019

kept upright to prevent leakage. Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isopropanol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm 1,225 mg/m3	OSHA P0
1,1-Difluoroethane	75-37-6	TWA	1,000 ppm	US WEEL
Propylene glycol	57-55-6	TWA	10 mg/m3	US WEEL

Hazardous components without workplace control parameters

Components	CAS-No.
(E)-2-benzylideneoctanal	165184-98-5

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Isopropanol	67-63-0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

Ozium® AIR SANITIZER SPRAY CARBON **BLACK**

Version **Revision Date:** SDS Number: Date of last issue: 04/09/2024 04/10/2024 60000001961 Date of first issue: 09/30/2019 1.7

Hand protection

Remarks Wear resistant gloves (consult your safety equipment suppli-

> er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance aerosol

Colour yellow

Odour pleasant

Odour Threshold not determined

рΗ not determined

Melting point/freezing point not determined

Boiling point/boiling range not determined

32 °C Flash point

Method: closed cup

Evaporation rate not determined

Flammability (solid, gas) Flammable aerosol.

Self-ignition not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower : not determined

flammability limit

Ozium® AIR SANITIZER SPRAY CARBON **BLACK**

Version **Revision Date:** SDS Number: Date of last issue: 04/09/2024 04/10/2024 60000001961 Date of first issue: 09/30/2019 1.7

Vapour pressure not determined

Relative vapour density not determined

Density not determined

Solubility(ies)

not determined Water solubility

Partition coefficient: n-

octanol/water

not determined

Decomposition temperature not determined

Viscosity

not determined Viscosity, dynamic

Viscosity, kinematic not determined

Molecular weight No data available

VOC % By Weight 69.28 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity No decomposition if stored and applied as directed.

Chemical stability No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents

Hazardous decomposition

products

Carbon oxides

Halogenated compounds

Hazardous decomposition

products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

Eye contact Skin contact

Ingestion

Acute toxicity

Not classified based on available information.

Product:

Ozium® AIR SANITIZER SPRAY CARBON BLACK

Version Revision Date: SDS Number: Date of last issue: 04/09/2024 1.7 04/10/2024 600000001961 Date of first issue: 09/30/2019

Acute dermal toxicity : Remarks: Skin absorption of this material (or a component)

may be increased through injured skin.

Components:

Isopropanol:

Acute oral toxicity : LD50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

1,1-Difluoroethane:

Acute inhalation toxicity : LC50 (Rat): 437500 ppm

Exposure time: 4 h Test atmosphere: gas

Propylene glycol:

Acute oral toxicity : LD50 (Rat): 21.0 - 33.7 g/kg

Acute dermal toxicity : LD50 (Rabbit): 28 g/kg

(E)-2-benzylideneoctanal:

Acute oral toxicity : LD50 (Rat): 3,100 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Method: OECD Test Guideline 402

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Isopropanol:

Result: Possibly irritating to skin

Ozium® AIR SANITIZER SPRAY CARBON BLACK

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/09/2024

 1.7
 04/10/2024
 600000001961
 Date of first issue: 09/30/2019

Propylene glycol:

Assessment: No skin irritation Result: No skin irritation

(E)-2-benzylideneoctanal:

Result: Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Isopropanol:

Result: Irritating to eyes.

Propylene glycol:

Result: Possibly irritating to eyes

(E)-2-benzylideneoctanal:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: May cause allergic skin reaction.

Components:

(E)-2-benzylideneoctanal:

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1-Difluoroethane:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Ozium® AIR SANITIZER SPRAY CARBON BLACK

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/09/2024

 1.7
 04/10/2024
 600000001961
 Date of first issue: 09/30/2019

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Isopropanol:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Ozium® AIR SANITIZER SPRAY CARBON BLACK

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/09/2024

 1.7
 04/10/2024
 600000001961
 Date of first issue: 09/30/2019

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Packing instruction (cargo : 203

aircraft)

Packing instruction : 203

(passenger aircraft)

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 ERG Code : 126 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
------------	---------	--------------	-----------------------

Ozium® AIR SANITIZER SPRAY CARBON BLACK

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/09/2024

 1.7
 04/10/2024
 600000001961
 Date of first issue: 09/30/2019

		(lbs)	(lbs)
Hydrochloric acid	7647-01-0	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Hydrochloric acid	7647-01-0	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation Respiratory or skin sensitisation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Isopropanol 67-63-0 >= 30 - < 50 %

California Prop. 65


This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard

Ozium® AIR SANITIZER SPRAY CARBON BLACK

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04/09/2024

 1.7
 04/10/2024
 600000001961
 Date of first issue: 09/30/2019

Revision Date : 04/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN