NITE()	Page 1
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Car Brite™ BUTTER WAX™

Creme Wax

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data **Emergency telephone number** CHEMTREC DIRECT 1-800-424-9300 sheet Niteo Products, LLC P.O. Box 191629 **Product Information** Dallas TX 75219 1-844-696-4836 United States of America

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin sensitization : Category 1

Carcinogenicity : Category 1A

Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms







Signal Word : Danger

Hazard Statements : Flammable liquid and vapor.

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Precautionary Statements : Prevention:

Obtain special instructions before use.

NITE()	Page 2
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/ attention.

If skin irritation or rash occurs: Get medical advice/ attention.

Wash contaminated clothing before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static Accumulating liquid

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 3; H226	10.02
		STOT SE 3; H336	
		Asp. Tox. 1; H304	
OCTAMETHYLCYCLOTETRASIL	556-67-2	Flam. Liq. 3; H226	5.60

NITE()	Page 3
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

OXANE		Repr. 2; H361	
ALKOXY-TERMINATED AMINOALKYL-FUNCTIONAL SILOXANE	67923-07-3	Eye Irrit. 2A; H319	1.01
QUARTZ (SiO2)	14808-60-7	Carc. 1A; H350 STOT RE 1; H372	0.14
5-CHLORO-2-METHYL-4- ISOTHIAZOLIN-3-ONE	26172-55-4	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	0.00

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

Wash contaminated clothing before re-use.

If on clothes, remove clothes.

NITE()	Page 4
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

Signs and symptoms of exposure to this material through

breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Lung irritation confusion

irregular heartbeat Convulsions

May cause an allergic skin reaction.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

NITE()	Page 5
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

courses.

Hazardous combustion

products

: aluminum oxides silicon oxides

carbon dioxide and carbon monoxide

Hydrocarbons formaldehyde

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.
 Remove all sources of ignition.
 Use personal protective equipment.

Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Other information : Comply with all applicable federal, state, and local regulations.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.

Avoid formation of aerosol.

NITE()	Page 6
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage

: Keep container tightly closed in a dry and well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Observe label precautions. No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	200 mg/m3 Non-aerosol (as total hydrocarbon vapor)	ACGIH
		REL	100 mg/m3	NIOSH/GUID E
QUARTZ (SiO2)	14808-60-7	TWA	0.025 mg/m3 Respirable fraction.	ACGIH
		REL	0.05 mg/m3 Respirable dust.	NIOSH/GUID E
		TWA	0.1 mg/m3 Respirable.	Z3
		TWA	0.3 mg/m3 Total dust.	Z3
		TWA	0.1 mg/m3 Respirable dust.	TN OEL

NITE()	Page
SAFETY DATA SHEET	Revision Date: 08/05/20
	Print Date: 08/23/20
	SDS Number: 60000000069
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

: In the case of vapour formation use a respirator with an

approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not

provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate: impervious clothing Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear.

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : yellow

Odour : like fruit

Odour Threshold : No data available

NITE()	Page 8
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

pH : No data available

: No data available

Boiling point/boiling range : 150 °F / 66 °C

(1013.33 hPa)

Flash point : 120 °F / 49 °C

Evaporation rate : No data available

Flammability (solid, gas) :

No data available

Flammability (liquids) : Static Accumulating liquid

Flammability (liquids)

Upper explosion limit : 6 %(V)

GLP: Calculated Explosive Limit

Lower explosion limit : 1 %(V)

GLP: Calculated Explosive Limit

Vapour pressure : 23.3333333 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 1.04 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Oxidizing properties : No data available

NITE()	Page 9
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

strong reducing agents

Hazardous decomposition

products

carbon dioxide and carbon monoxide

formaldehyde Hydrocarbons silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

: Inhalation Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:
Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5.28 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

OCTAMETHYLCYCLOTETRASILOXANE:

Acute oral toxicity : LD 50 (Rat): > 4,800 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Acute inhalation toxicity : LC50 (Rat): 36 mg/l

NITEC PRODUCTS	Page 10
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,400 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

Acute oral toxicity

Assessment: The component/mixture is classified as acute

oral toxicity, category 3.

Acute inhalation toxicity : Assessment: The component/mixture is classified as acute

inhalation toxicity, category 3.

Acute dermal toxicity : Assessment: The component/mixture is classified as acute

dermal toxicity, category 3.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Mildly irritating to skin

OCTAMETHYLCYCLOTETRASILOXANE:

Species: Rabbit

Result: Not irritating to skin

ALKOXY-TERMINATED AMINOALKYL-FUNCTIONAL SILOXANE:

Result: Not irritating to skin

QUARTZ (SiO2):

Result: Possibly irritating to skin

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

Result: Corrosive to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Mildly irritating to eyes

NITEC PRODUCTS	Page 11
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

OCTAMETHYLCYCLOTETRASILOXANE:

Species: Rabbit

Result: Slightly irritating to eyes

ALKOXY-TERMINATED AMINOALKYL-FUNCTIONAL SILOXANE:

Result: Irritating to eyes

QUARTZ (SiO2):

Result: Possibly irritating to eyes

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

Result: Corrosive to eyes

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

OCTAMETHYLCYCLOTETRASILOXANE: Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE: Assessment: May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:

OCTAMETHYLCYCLOTETRASILOXANE:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

May cause cancer.

Components:
QUARTZ (SiO2):

Carcinogenicity - : Human carcinogen.

Assessment

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

OCTAMETHYLCYCLOTETRASILOXANE:

Reproductive toxicity - : Some evidence of adverse effects on sexual function and

Assessment fertility, based on animal experiments.

STOT - single exposure

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

NITE()	Page 12
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

QUARTZ (SiO2):

Exposure routes: inhalation (dust/mist/fume)
Target Organs: Respiratory system, Kidney

Assessment: Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

Components:

QUARTZ (SiO2): Remarks: Lung

Carcinogenicity:

IARC Group 1: Carcinogenic to humans

QUART Z / SAND 14808-60-7

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP Known to be human carcinogen

QUART 2 / SAND 14808-60-7

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

OCTAMETHYLCYCLOTETRASILOXANE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.022 mg/l

Exposure time: 96 h

NITE()	Page 13
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

Test Type: flow-through test

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates

: NOEC (Daphnia magna (Water flea)): >= 0.015 mg/l

Exposure time: 48 h

Test Type: flow-through test

Remarks: No toxicity at the limit of solubility

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): >

0.022 mg/l

End point: Growth inhibition Exposure time: 96 h

Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic

toxicity)

: NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l

Exposure time: 93 d

Test Type: flow-through test

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia (water flea)): 0.0079 mg/l

Exposure time: 21 d
Test Type: flow-through test

Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

Toxicity to fish : LC 50 (Oncorhynchus mykiss (rainbow trout)): 0.19 mg/l

Exposure time: 96 h

Test Type: flow-through test

Persistence and degradability

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Biodegradability : Result: Inherently biodegradable

Biodegradation: 58.6 % Exposure time: 28 d

Method: OECD Test Guideline 301F

OCTAMETHYLCYCLOTETRASILOXANE:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 3.7 % Exposure time: 29 d

Method: OECD Test Guideline 310

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

Biodegradability : Biodegradation: 30 %

Exposure time: 28 d

Method: OECD Test Guideline 301B Remarks: Not readily biodegradable.

NITE()	Page 14
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

Bioaccumulative potential

OCTAMETHYLCYCLOTETRASILOXANE:

Bioaccumulation : Species: Fathead minnow (Pimephales promelas)

Bioconcentration factor (BCF): 14,261

Exposure time: 28 d

Concentration: 0.00016 mg/l Method: Flow through

Partition coefficient: n-

: log Pow: 6.488 (25 °C)

octanol/water

Method: OECD Test Guideline 123

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

N	iTE			Page 15
SAFI	ETY D	ATA SHEET		Revision Date: 08/05/2015
				Print Date: 08/23/2016
				SDS Number: 600000000695
	ite™ BUT 0A007-03	TER WAX™ Creme Wax		Version: 1.1
UN	1993	Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
U.S. DO	T - RAIL			
UN	1993	Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
U.S. DO	T - INLAI	ND WATERWAYS		
UN	1993	Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
TRANS	PORT CA	NADA - ROAD		
UN	1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
TDANS		NADA - RAIL		
UN	1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
TRANS	PORT CA	NADA - INLAND WATERWAYS		
UN	1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
INTERN	IATIONAI	_ MARITIME DANGEROUS GOO	DS.	
UN	1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
INTERN	IATIONAI	_ AIR TRANSPORT ASSOCIATIO	ON - CAPGO	
UN	1993	Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
INITERS	IATIONA	AID TO ANGROOF ACCORDATION	ON DACCENCED	
UN	1993	L AIR TRANSPORT ASSOCIATION Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	ON - PASSENGER 3	III
		-,		

NITE()	Page 16
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1993	LIQUIDO INFLAMABLE, N.E.P.	3	III
		(ALIPHATIC PETROLEUM		
		DISTILLATES)		

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

SARA 313

Component(s)SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

QUARTZ / SAND 14808-60-7

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm.

METHANOL 67-56-1

ETHYLENE GLYCOL 109-86-4

MONOMETHYL ETHER

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

NITE()	Page 17
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 08/05/2015



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

Full text of H-Statements referred to under sections 2 and 3.

NITE()	Page 18
SAFETY DATA SHEET	Revision Date: 08/05/2015
	Print Date: 08/23/2016
	SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03	Version: 1.1

H226	Flammable liquid and vapor.	
H301	Toxic if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H313	May be harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H336	May cause drowsiness or dizziness.	
H350	May cause cancer.	
H361	Suspected of damaging fertility or the unborn child.	
H361f	Suspected of damaging fertility.	

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit

NITE()		Page 19
SAFETY DATA SHEET		Revision Date: 08/05/2015
		Print Date: 08/23/2016
		SDS Number: 60000000695
Car Brite™ BUTTER WAX™ Creme Wax CBOOA007-03		Version: 1.1

P-Statement : Precautionary Statement PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System