

Version 3.0	Revision Date: 09/06/2018		DS Number: 00000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016				
SECTION 1. IDENTIFICATION								
Pro	oduct name	:	SURFACE CLARIFIER 4/1 GA					
Pro	Product code		CBOOE111-03					
	nufacturer or supplier's mpany name of supplier			LC				
Ad	dress	:	Dallas TX 75225					
En	ail Address	:	EHS@niteoprodu	icts.com				
Те	lephone	:	1-844-696-4836					
En be	nergency telephone num-	:	1-800-424-9300 /	1-703-741-5970				

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200							
Corrosive to metals	:	Category 1					
Acute toxicity (Dermal)	:	Category 3					
Skin corrosion	:	Category 1					
Serious eye damage	:	Category 1					
GHS label elements							
Hazard pictograms	:						
Signal word	:	Danger					
Hazard statements	:	May be corrosive to metals. Toxic in contact with skin. Causes severe skin burns and eye damage.					
Precautionary statements	:	Prevention: Keep only in original container. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye protection/ face protection.					



rsion)	Revision Date: 09/06/2018	SDS Number: 600000000769		t issue: 04/29/2018 tt issue: 05/23/2016				
		IF ON SKIN (o clothing. Rinse IF INHALED: F for breathing. I	r hair): Take of skin with wate Remove person mmediately cal	th. Do NOT induce vomiting. f immediately all contaminated r/shower. to fresh air and keep comfortab II a POISON CENTER/doctor. with water for several minutes.				
		Remove conta rinsing. Immec Take off conta	ct lenses, if pre liately call a PC minated clothin	aterial damage.				
		Storage: Store locked up. Store in corrosive resistant container with a resistant inner liner Disposal: Dispose of contents/ container to an approved waste disposal plant.						
Othe	r hazards							
	known.							
Subst	ance / Mixture	FORMATION ON INC : Mixture	GREDIENTS					
	rdous components							
	nical name		S-No.	Concentration (% w/w)				
	phoric acid		4-38-2	>= 30 - < 50				
	ols, C9-11, ethoxylate		39-46-3 4-39-3	>= 1 - < 3 >= 1 - < 3				

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.
If inhaled	:	Move to fresh air. IF INHALED: Call a POISON CENTER/ doctor if you feel un- well. If unconscious, place in recovery position and seek medical advice. Keep patient warm and at rest. If symptoms persist, call a physician.
In case of skin contact	:	Take off contaminated clothing and shoes immediately.



Version 3.0	Revision Date: 09/06/2018	SDS Number: 600000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016
		If on skin, rin Immediately cool running clothing while washing, app areas. (Note flushing until into the affect skin contami every 15 min calcium gluce soaked in ice (Zephiran ch prevent frost towels should ride solution Compresses tinued until p neither calciu able, use an fate (Epsom or ice water. of pain indica attention as s conate gel ca calcium gluce Johnson). A used, it shou contaminatio	ian or poison control centre immediately. se well with water. flush contaminated skin with large quantities of water for 5 minutes. Remove contaminated e flushing contaminated skin. Immediately after oly 2.5% calcium gluconate gel to all affected ski e: If gel is not prepared within 5 minutes, continue gel is prepared.) The gel should be massaged ted skin by personnel wearing gloves to prevent nation during first aid. Gel should be applied utes and massaged continuously. Instead of onate treatment, the affected areas may be ed 0.13% benzalkonium chloride solution loride). Use ice cubes rather than shaved ice to bite. If it is not practical to immerse affected are d be soaked with iced 0.13% benzalkonium chlo and used as compresses for the burned area. should be changed every 2-3 minutes and con- ain is relieved or victim is seen by a physician. If in gluconate nor benzalkonium chloride is avail- iced saturated water solution of magnesium sul- salts), or if that is not available, iced 70% alcoho Local anesthetics should be avoided since relie ates success of the treatment. ***Get medical soon as possible.*** ::::NOTE::::Calcium glu- an be prepared by mixing a 10 milliliter ampule of conate with a 2-ounce tube of K-Y jelly (Johnson of fter a jar of this mixture has been opened and ld be discarded to prevent bacterial or chemical n. ninated clothing before re-use. on persists, call a physician.
In cas	se of eye contact	of water and Continue rins Remove con Protect unha	
lf swa	allowed	Do NOT indu Rinse mouth Do not give r Never give a	
	important symptoms iffects, both acute and ed	Causes seve This product fects from HI treated or ex can cause de	ous eye damage.



Versio 3.0	n Revision Date: 09/06/2018		0S Number: 0000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016
vascular effects. Exposure of >5% of the t with any concentration of HF may predisp development of hypocalcemia. Chronic ex acutely toxic amounts of HF is a low toxici				or significant inhalation can cause severe including electrolyte (calcium, magnesium, cid-base abnormalities with resulting cardio- Exposure of >5% of the body surface area ation of HF may predispose the patient to ypocalcemia. Chronic exposure to less than unts of HF is a low toxicity hazard. Repeat- absorption of 10-80 mg of fluoride per day
SECT	ION 5. FIREFIGHTING MEA	SU	RES	
S	uitable extinguishing media	:	Water spray Carbon dioxide (C	202)
	nsuitable extinguishing nedia	:	High volume wate	er jet
	pecific hazards during fire- ghting	:	Do not allow run-o courses.	off from fire fighting to enter drains or water
	azardous combustion prod- cts	:	Oxides of phosph Carbon oxides Hydrogen fluoride	
	pecific extinguishing meth- ds	:	Product is compa	tible with standard fire-fighting agents.
F	urther information	:		measures that are appropriate to local cir- he surrounding environment.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Avoid breathing dust. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).



Version 3.0	Revision Date: 09/06/2018		DS Number: 00000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016
			Keep in suitable,	closed containers for disposal.
SECTION	7. HANDLING AND ST	OR	AGE	
	ce on protection against nd explosion	:	Normal measures	s for preventive fire protection.
Advic	ce on safe handling	:	Do not breathe va Do not smoke. Avoid contact with When diluting, alw water to the produce Dispose of rinse variable regulations. Container hazard Smoking, eating a plication area.	air exchange and/or exhaust in work rooms. apours/dust. h skin and eyes. ways add the product to water. Never add uct. water in accordance with local and national
Cond	litions for safe storage	:	place.	ecautions.
	er information on stor- stability	:	No decomposition	n if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Phosphoric acid	7664-38-2	TWA	1 mg/m3	ACGIH
		STEL	3 mg/m3	ACGIH
		TWA	1 mg/m3	NIOSH REL
		ST	3 mg/m3	NIOSH REL
		TWA	1 mg/m3	OSHA Z-1
		TWA	1 mg/m3	OSHA P0
		STEL	3 mg/m3	OSHA P0
Hydrofluoric acid	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm 2.5 mg/m3	NIOSH REL
		С	6 ppm 5 mg/m3	NIOSH REL



rsion	Revision Date: 09/06/2018		DS Number: 00000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016				
1		I		TWA	3 ppm	OSHA Z-2		
				TWA	3 ppm (Fluorine)	OSHA PO		
				STEL	6 ppm (Fluorine)	OSHA P0		
Hazaı	rdous components wit	thou	ıt workplace c	ontrol param	eters			
Comp	onents		CAS-No.	1				
Alcoh	ols, C9-11, ethoxylated		68439-46-3]				
Engir	neering measures	:	ventilation to	maintain expo	al (general and/or lo sure below exposure that cause known, se	e guidelines (if		
Perso	onal protective equipm	nent						
	iratory protection	:		vapour forma	tion use a respirator	with an ap-		
Hand	protection							
Re	emarks	:	er). The suita cussed with t	bility for a spe he producers o	sult your safety equip cific workplace shou of the protective glov noles, or signs of we	ld be dis- ves. Discard		
Eye p	protection	:		/ear chemical splash goggles and face shield when there is otential for exposure of the eyes or face to liquid, vapor or hist.				
Skin a	and body protection	:	 Choose body protection according to the amount and concentration of the dangerous substance at the work place. Wear as appropriate: Impervious clothing Safety shoes Remove and wash contaminated clothing before re-use. 					
Hygiene measures : Handle in acc practice. Avoid contac When using o Wash hands the product.				t with skin, eye to not smoke.	good industrial hygie es and clothing. and immediately aft rink			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	colourless
Odour	:	pungent
рН	:	< 1



Ver 3.0	sion	Revision Date: 09/06/2018		S Number: 0000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016
	Malting		_		
	weiting	point/freezing point	:	No data available	3
	Boiling	point/boiling range	:	100 °C (1,013 hPa) The value is calc	ulated
	Flash p	point	:	> 93.4 °C Method: Tag clos	
	Evapor	ation rate	:	No data available	
	Flamm	ability (solid, gas)	:	No data available	
	Self-ig	nition	:	No data available)
		explosion limit / Upper bility limit	:	10.6 %(V) The value is calc	ulated
		explosion limit / Lower bility limit	:	1.1 %(V) The value is calc	ulated
	Vapour	pressure	:	23.33333333 hPa The value is calc	
	Density	/	:	1.20 g/cm3	
	Solubili Wat	ty(ies) er solubility	:	soluble	
	Partitio octanol	n coefficient: n- /water	:	No data available)
	Viscosi Visc	ty cosity, dynamic	:	No data available)
	Visc	cosity, kinematic	:	No data available	
	Oxidizi	ng properties	:	No data available	9

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed. Hazardous polymerisation does not occur.
Conditions to avoid	:	No data available
Incompatible materials	:	Aluminium Copper Copper alloys Fluorine



ersion 0	Revision Date: 09/06/2018	SDS Number: 600000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016
		Metals organic nitro c Organic mater Strong bases Strong oxidizir Strong reducir Sulphides sulphites Do not use wit 49C or 120 de	ials ng agents ng agents h aluminum equipment at temperatures above
Hazar produc	dous decomposition cts	: Carbon oxides Hydrogen fluo Oxides of pho	ride

Inhalation Skin contact Eye contact Ingestion		
Acute toxicity		
Toxic in contact with skin.		
Product:		
Acute oral toxicity	:	Acute toxicity estimate: 3,093 mg/kg Method: Calculation method
		Remarks: Causes digestive tract burns.
Acute inhalation toxicity	:	Acute toxicity estimate: 35.75 mg/l Exposure time: 4 h Test atmosphere: vapour
		Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: 342.39 mg/kg Method: Calculation method
Components:		
Phosphoric acid:		
Acute oral toxicity	:	LD50 (Rat): ca. 2,600 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): 2,740 mg/kg
Alcohols, C9-11, ethoxylated	:	
Acute oral toxicity	:	LD50 (Rat): 500 - 2,000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 5 g/kg



Version 3.0	Revision Date: 09/06/2018		DS Number: 00000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016
Hydro	ofluoric acid:			
Acute	oral toxicity	:	Assessment: The gestion.	component/mixture is toxic after single in-
Acute	inhalation toxicity	:	: Assessment: The component/mixture is highly toxic term inhalation.	
Acute	dermal toxicity	:	LDLo (Mouse): 50 Assessment: The single contact wit	component/mixture is extremely toxic after

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks: Both the liquid and vapor can cause severe burns which may not be immediately painful or visible. Pain may become gradually more severe, possibly taking 1-24 hours to become noticable. These burns can be very deep, possibly causing bone damage, and are very slow to heal. Even solutions containing 2% or less hydrogen fluoride or other inorganic fluoride compounds can cause burns and tissue damage.

Components:

Phosphoric acid:

Species: Rabbit Result: Corrosive after 1 to 4 hours of exposure

Alcohols, C9-11, ethoxylated:

Result: Mild skin irritation

Hydrofluoric acid:

Result: Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:

Phosphoric acid:

Result: Irreversible effects on the eye Assessment: Corrosive

Alcohols, C9-11, ethoxylated:

Result: Irreversible effects on the eye

SAFETY DATA SHEET



Car Brite[™] SURFACE CLARIFIER Concentrated Water Spot Remover

Version 3.0	Revision Date: 09/06/2018	SDS Number: 60000000769	Date of last issue: 04/29/2018 Date of first issue: 05/23/2016						
Resu	rofluoric acid: Ilt: Irreversible effects or essment: Corrosive	n the eye							
Res	Respiratory or skin sensitisation								
-	sensitisation	able information.							
•	biratory sensitisation classified based on avail	able information.							
	Germ cell mutagenicity								
Not o	Not classified based on available information.								
Carc	Carcinogenicity								
Not o IAR	classified based on avail C	No component of th	is product present at levels greater than or ntified as probable, possible or confirmed by IARC.						
OSH	A		is product present at levels greater than or OSHA's list of regulated carcinogens.						
NTF	NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.								
•	roductive toxicity classified based on avail	able information.							
	STOT - single exposure Not classified based on available information.								

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION



Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
3.0	09/06/2018	60000000769	Date of first issue: 05/23/2016

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR UN/ID No.		UN 3264
Proper shipping name	:	Corrosive liquid, acidic, inorganic, n.o.s. (PHOSPHORIC ACID)
Class	:	8
Packing group	:	II
Labels	:	8
Packing instruction (cargo aircraft)	:	855
Packing instruction (passenger aircraft)	:	851
IMDG-Code		
UN number	:	UN 3264
Proper shipping name	:	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (PHOSPHORIC ACID)
Class	:	8
Packing group	:	II
Labels	:	8
EmS Code	:	F-A, S-B
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR		
UN/ID/NA number	:	UN 3264
Proper shipping name	:	Corrosive liquid, acidic, inorganic, n.o.s. (PHOSPHORIC ACID)
Class	:	8
Packing group	:	II
Labels	:	8
ERG Code	:	154
Marine pollutant	:	no



Version	Revision Date:	SDS Number:
3.0	09/06/2018	60000000769

Date of last issue: 04/29/2018 Date of first issue: 05/23/2016

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Phosphoric acid	7664-38-2	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Hydrofluoric acid	7664-39-3	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

Components	CAS-No.	Component TPQ (lbs)	
Hydrofluoric acid	7664-39-3	100	
SARA 311/312 Hazards :	Corrosive to metals Acute toxicity (any route of exposure) Skin corrosion or irritation Serious eye damage or eye irritation		
SARA 313 :	tablished by SARA Title III, Section 313:		
	Hydrofluoric acid	7664-39-3 >= 1 - < 5 %	

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.


SAFETY DATA SHEET



Car Brite[™] SURFACE CLARIFIER Concentrated Water Spot Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
3.0	09/06/2018	60000000769	Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION



Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN