NITEC PRODUCTS	Page 1
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Car Brite™ SAP REMOVER

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data	Emergency telephone number
sheet	CHEMTREC DIRECT 1-800-424-9300
Niteo Products, LLC	
P.O. Box 191629	Product Information
Dallas TX 75219	1-844-696-4836
United States of America	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Eye irritation : Category 2A

Specific target organ systemic toxicity - single

exposure

: Category 3 (Central nervous system)

GHS Label element

Hazard pictograms





Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

NITE()	Page 2
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use only outdoors or in a well-ventilated area.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

Wash skin thoroughly after handling.

Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Aspiration hazard

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
ISOPROPANOL	67-63-0	Flam. Liq. 2; H225	99.25
		Eye Irrit. 2A; H319	
		STOT SE 3; H336	

NITEC PRODUCTS	Page 3
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Call a POISON CENTRE or doctor/physician if exposed or

you feel unwell.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If unconscious place in recovery position and seek medical

advice.

Consult a physician after significant exposure.

In case of skin contact : If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Administration of high doses of isopropanol in combination with known hepatotoxic chemicals resulted in enhanced liver

toxicity in experimental animals.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

confusion

lung edema (fluid buildup in the lung tissue)

Causes serious eye irritation.

May cause drowsiness or dizziness.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

NITE()	Page 4
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite

explosively.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Specific extinguishing

methods

:

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated

: Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.
 Remove all sources of ignition.
 Use personal protective equipment.

Ensure adequate ventilation.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

NITE()	Page 5
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

local / national regulations (see section 13).

Other information : Comply with all applicable federal, state, and local regulations.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.

Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty.

Take precautionary measures against static discharges. Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Container may be opened only under exhaust ventilation

hood.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components with workplace control parameters				
Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
ISOPROPANOL	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		REL	400 ppm	NIOSH/GUID
			980 mg/m3	E
		STEL	500 ppm	NIOSH/GUID
			1,225 mg/m3	E
		PEL	400 ppm	OSHA_TRA

NITEC PRODUCTS	Page 6
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

	980 mg/m3	NS
TWA	400 ppm	TN OEL
	980 mg/m3	
STEL	500 ppm	TN OEL
	1,225 mg/m3	

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
ISOPROPANOL	67-63-0	acetone	Urine	Sampling time: End of shift at end of work week.	40 mg/l	
Remarks:	Nonspecifi	c, Background	•	•	•	•

Engineering measures

: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

: In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:

impervious clothing

Safety shoes

Flame-resistant clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Wear resistant gloves (consult your safety equipment

supplier).

NITE()	Page 7
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

Hygiene measures : Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : colourless

Odour : like fruit

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 150 °F / 66 °C

(1013.33 hPa)

Flash point : 68 °F / 20 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 12 %(V)

GLP: Calculated Explosive Limit

Lower explosion limit : 2.5 %(V)

GLP: Calculated Explosive Limit

Vapour pressure : 60.52728 hPa (25 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.788 g/cm3 (25 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

NITEC	Page 8
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids

Aldehydes alkalis Amines

Ethylene oxide

halogenated hydrocarbons

halogens isocyanates

Strong oxidizing agents

Do not use with aluminum equipment at temperatures above

49C or 120 degrees F.

Hazardous decomposition

products carbon dioxide and carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Inhalation Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

ISOPROPANOL:

Acute oral toxicity : LD 50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC 50 (Rat): 16000 ppm

NITE()	Page 9
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rabbit): 12,800 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

Components:

ISOPROPANOL:

Result: Slightly irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

ISOPROPANOL:

Result: Irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

NITE()	Page 10
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

ISOPROPANOL:

Remarks: Central nervous system

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHANo component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

ISOPROPANOL:

Toxicity to fish : LC 50 (Fathead minnow (Pimephales promelas)): 5,770 -

7,450 mg/l

Exposure time: 96 h

Test Type: flow-through test

Toxicity to daphnia and other

aquatic invertebrates

: LC 50 (Water flea (Daphnia magna)): > 10,000 mg/l

Exposure time: 24 h Test Type: static test

Persistence and degradability

Components:

No data available

Bioaccumulative potential

Components:

ISOPROPANOL:

Partition coefficient: n-

: log Pow: 0.05

octanol/water

Mobility in soil

Components:

No data available

Other adverse effects

No data available

NITEC	Page 11
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

Product:

Additional ecological

information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

UN	1993	Flammable liquids, n.o.s. (ISOPROPANOL)	3	II

U.S. DOT - RAIL

UN	1993	Flammable liquids, n.o.s. (ISOPROPANOL)	3	11

U.S. DOT - INLAND WATERWAYS

UN	1993	Flammable liquids, n.o.s. (ISOPROPANOL)	3	II

TRANSPORT CANADA - ROAD

Ni	TE			Page 12
PRC		ATA SHEET		Revision Date: 07/31/2015
OAI L	_ 1 1 //	ATA STILLT		Print Date: 11/24/2016
				SDS Number: 60000000774
	te™ SAP F013-03	REMOVER		Version: 1.1
UN	1993	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)	3	II
RANSI	PORT CA	NADA - RAIL		
UN	1993	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)	3	II
RANSI	PORT CA	.NADA - INLAND WATERWAYS		
UN	1993	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)	3	II
NTERN	ATIONAL	_ MARITIME DANGEROUS GOO	DDS	
UN	1993	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)	3	II
NTERN	ATIONAL	_ AIR TRANSPORT ASSOCIATI	ON - CA	RGO
UN	1993	Flammable liquid, n.o.s. (ISOPROPANOL)	3	II
NTFRN	ΔΤΙΟΝΔΙ	_ AIR TRANSPORT ASSOCIATI	ON - PAS	SSENGER
UN	1993	Flammable liquid, n.o.s. (ISOPROPANOL)	3	II
MEXICA VASTE		LATION FOR THE LAND TRAN	SPORT (OF HAZARDOUS MATERIALS AND
UN	1993	LIQUIDO INFLAMABLE, N.E.P (ISOPROPANOL)	. 3	II
ORM =	ORM-D,	CBL = COMBUSTIBLE LIQUID		
M	arine poll	utant no		
	·			
	ions that			ot reflect quantity, end-use or region-specific nts for descriptions that are specific to the

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

NITE()	Page 13
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

ISOPROPANOL 67-63-0 90.00 -

100.00 %

New Jersey Right To Know

ISOPROPANOL 67-63-0 90.00 -

100.00 %

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

NITE()	Page 14
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2015



NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IB

Full text of H-Statements referred to under sections 2 and 3.

H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H333 May be harmful if inhaled.

Sources of key data used to compile the Safety Data Sheet Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

NITE()	Page 15
SAFETY DATA SHEET	Revision Date: 07/31/2015
	Print Date: 11/24/2016
	SDS Number: 60000000774
Car Brite™ SAP REMOVER CBOOF013-03	Version: 1.1

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System