

SAFETY DATA SHEET



Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : WORKOUT 2000 4/1 GA

Product code : CBOOA045-03

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.

SAFETY DATA SHEET



Car Brite™ WORKOUT 2000™ Finishing Polish

Version: 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
Date of first issue: 05/23/2016

Precautionary statements :

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash skin thoroughly after handling.
Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Mineral Spirits Odorless	8052-41-3	>= 10 - < 20
Hydrotreated heavy naphtha	64742-48-9	>= 5 - < 10
Glycerin	56-81-5	>= 1 - < 5
Solvent naphtha (petroleum)	64742-88-7	>= 1 - < 5
Morpholine	110-91-8	>= 1 - < 3
Propylene glycol monopropyl ether	1569-01-3	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Car Brite™ WORKOUT 2000™ Finishing Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2018
2.0	09/06/2018	600000000703	Date of first issue: 05/23/2016

SECTION 4. FIRST AID MEASURES

- | | | |
|---|---|---|
| General advice | : | Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended. |
| If inhaled | : | If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician. |
| In case of skin contact | : | If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician. |
| In case of eye contact | : | Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : | Obtain medical attention.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : | May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation. |

SECTION 5. FIREFIGHTING MEASURES

- | | | |
|---------------------------------------|---|--|
| Suitable extinguishing media | : | Water spray
Carbon dioxide (CO ₂)
Dry chemical
Alcohol-resistant foam |
| Unsuitable extinguishing media | : | High volume water jet |
| Specific hazards during fire-fighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | Carbon oxides |
| Specific extinguishing methods | : | Product is compatible with standard fire-fighting agents. |

Car Brite™ WORKOUT 2000™ Finishing Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2018
2.0	09/06/2018	600000000703	Date of first issue: 05/23/2016

- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.

SAFETY DATA SHEET



Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
 Date of first issue: 05/23/2016

Avoid contact with skin and eyes.
 Dispose of rinse water in accordance with local and national regulations.
 Container hazardous when empty.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Mineral Spirits Odorless	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Glycerin	56-81-5	TWA (mist, respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (mist, total dust)	15 mg/m3	OSHA Z-1
		TWA (Mist - total dust)	10 mg/m3	OSHA P0
		TWA (Mist - respirable fraction)	5 mg/m3	OSHA P0
Morpholine	110-91-8	TWA	20 ppm	ACGIH
		TWA	20 ppm 70 mg/m3	NIOSH REL
		ST	30 ppm 105 mg/m3	NIOSH REL
		TWA	20 ppm 70 mg/m3	OSHA Z-1
		TWA	20 ppm 70 mg/m3	OSHA P0
		STEL	30 ppm 105 mg/m3	OSHA P0

Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
 Date of first issue: 05/23/2016

Hazardous components without workplace control parameters

Components	CAS-No.
Hydrotreated heavy naphtha	64742-48-9
Solvent naphtha (petroleum)	64742-88-7
Propylene glycol monopropyl ether	1569-01-3

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear as appropriate:
 Impervious clothing
 Flame-resistant clothing
 Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
 When using do not smoke.
 When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : off-white

Odour : like fruit

pH : No data available

Melting point/freezing point : 0 °C

Boiling point/boiling range : > 65 °C

Flash point : 50 °C
 Method: Pensky-Martens closed cup

Evaporation rate : No data available

SAFETY DATA SHEET



Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
Date of first issue: 05/23/2016

Flammability (solid, gas) : No data available

Self-ignition : 216 °C

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 23.33 hPa (20 °C)
The value is calculated

Density : ca. 0.968 g/cm³ (20 °C)

Solubility(ies)
Water solubility : partly soluble

Partition coefficient: n-octanol/water : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids
acrylates
Alcohols
Aldehydes
Bases
glycols
Halogenated compounds
Iron
isocyanates
Ketones
Metals
Nitrous acid and other nitrosating agents
organic anhydrides
Reducing agents

Car Brite™ WORKOUT 2000™ Finishing Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2018
2.0	09/06/2018	600000000703	Date of first issue: 05/23/2016

Strong bases
Strong oxidizing agents

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 199.39 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Mineral Spirits Odorless:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Glycerin:

Acute oral toxicity : LD50 (Rat): 12,600 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 570 mg/m³
Exposure time: 1 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 10 g/kg

Solvent naphtha (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l
Exposure time: 4 h

Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
 Date of first issue: 05/23/2016

Test atmosphere: vapour
 Method: OECD Test Guideline 403
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Morpholine:

Acute oral toxicity : LD50 (Rat): ca. 1,900 mg/kg
 Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): ca. 500 mg/kg

Propylene glycol monopropyl ether:

Acute oral toxicity : LD50 (Rat, male): 4,330 mg/kg
 Method: OECD Test Guideline 401

LD50 (Rat, female): 2,490 mg/kg
 Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male): > 1725 ppm
 Exposure time: 4 h
 Test atmosphere: vapour
 Method: OECD Test Guideline 403
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit, male): 3,775 mg/kg
 Method: OECD Test Guideline 402

LD50 (Rabbit, female): 4,330 mg/kg
 Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Mineral Spirits Odorless:

Result: Mild skin irritation

Hydrotreated heavy naphtha:

Assessment: Irritating to skin.

Car Brite™ WORKOUT 2000™ Finishing Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2018
2.0	09/06/2018	600000000703	Date of first issue: 05/23/2016

Result: Irritating to skin.

Glycerin:

Assessment: No skin irritation

Result: No skin irritation

Solvent naphtha (petroleum):

Species: Rabbit

Result: Skin irritation

Morpholine:

Result: Corrosive after 3 minutes or less of exposure

Propylene glycol monopropyl ether:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Mineral Spirits Odorless:

Result: Possibly irritating to eyes

Hydrotreated heavy naphtha:

Result: Irritating to eyes.

Assessment: Irritating to eyes.

Glycerin:

Result: Possibly irritating to eyes

Solvent naphtha (petroleum):

Species: Rabbit

Result: No eye irritation

Morpholine:

Result: Irreversible effects on the eye

Propylene glycol monopropyl ether:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
 Date of first issue: 05/23/2016

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

Genotoxicity in vitro : Test Type: Ames test
 Test system: Salmonella typhimurium
 Metabolic activation: with and without metabolic activation
 Result: negative

Morpholine:

Genotoxicity in vitro : Test Type: unscheduled DNA synthesis assay
 Test system: rat hepatocytes
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 482
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Test system: mouse lymphoma cells
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 476
 Result: positive

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET



Car Brite™ WORKOUT 2000™ Finishing Polish

Version	Revision Date:	SDS Number:	Date of last issue: 05/02/2018
2.0	09/06/2018	600000000703	Date of first issue: 05/23/2016

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

Hydrotreated heavy naphtha:

Assessment: May cause respiratory irritation.

Solvent naphtha (petroleum):

Exposure routes: inhalation (vapour)

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Mineral Spirits Odorless:

May be fatal if swallowed and enters airways.

Hydrotreated heavy naphtha:

May be fatal if swallowed and enters airways.

Solvent naphtha (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

SAFETY DATA SHEET



Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
Date of first issue: 05/23/2016

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
-

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

- UN/ID No. : UN 1993
Proper shipping name : Flammable liquid, n.o.s.
(ALIPHATIC PETROLEUM DISTILLATES)
Class : 3
Packing group : III
Labels : 3
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(ALIPHATIC PETROLEUM DISTILLATES)
Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

- UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(ALIPHATIC PETROLEUM DISTILLATES)
Class : 3
Packing group : III
Labels : 3
ERG Code : 128

SAFETY DATA SHEET



Car Brite™ WORKOUT 2000™ Finishing Polish

Version: 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
Date of first issue: 05/23/2016

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Amyl acetate	628-63-7	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Aspiration hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, Benzene, which is/are known to the State of California to cause cancer, and Benzene, Ethylene glycol monomethyl ether, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SAFETY DATA SHEET




Car Brite™ WORKOUT 2000™ Finishing Polish

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000703 Date of last issue: 05/02/2018
Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN