

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version Revision Date: SDS Number: Date of last issue: 04/25/2018
2.0 09/06/2018 600000001078 Date of first issue: 08/22/2017

SECTION 1. IDENTIFICATION

Product name : FAST WAX 1GA UNIT- NEW

Product code : CBO1A036I03

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : WAX

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 4

Eye irritation : Category 2B

GHS label elements

Signal word : Warning

Hazard statements : Combustible liquid.
Causes eye irritation.

Precautionary statements : **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Wash skin thoroughly after handling.
Wear protective gloves/ eye protection/ face protection.

Response:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000001078 Date of last issue: 04/25/2018
Date of first issue: 08/22/2017

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum)	64742-48-9	>= 10 - < 20
Solvent naphtha (petroleum)	64742-96-7	>= 5 - < 10

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes eye irritation.

SECTION 5. FIREFIGHTING MEASURES

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000001078 Date of last issue: 04/25/2018
Date of first issue: 08/22/2017

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Aldehydes
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000001078 Date of last issue: 04/25/2018
Date of first issue: 08/22/2017

during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Do not spray on a naked flame or any incandescent material.

- Advice on safe handling : Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
- Further information on storage stability : No decomposition if stored and applied as directed.
-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Hazardous components without workplace control parameters

Components	CAS-No.
Naphtha (petroleum)	64742-48-9
Solvent naphtha (petroleum)	64742-96-7

- Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

- Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves.

- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000001078 Date of last issue: 04/25/2018
Date of first issue: 08/22/2017

Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : cream
Colour : yellow
Odour : like fruit
pH : 8 - 9
Flash point : > 61 °C
Relative density : 0.983 (25 °C)
Viscosity
Viscosity, kinematic : > 7000 mm²/s (40 °C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : No decomposition if stored and applied as directed.
Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.
Conditions to avoid : Heat, flames and sparks.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Naphtha (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version Revision Date: SDS Number: Date of last issue: 04/25/2018
2.0 09/06/2018 600000001078 Date of first issue: 08/22/2017

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Solvent naphtha (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May irritate skin.

Components:

Naphtha (petroleum):

Result: Mild skin irritation

Solvent naphtha (petroleum):

Species: Rabbit
Result: Irritating to skin.

Serious eye damage/eye irritation

Causes eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Naphtha (petroleum):

Result: Mild eye irritation

Solvent naphtha (petroleum):

Species: Rabbit
Result: Possibly irritating to eyes

Car Brite™ FAST WAX Liquid Wax

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000001078 Date of last issue: 04/25/2018
Date of first issue: 08/22/2017

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

Test Type: Buehler Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Rat
Cell type: Bone marrow
Method: OECD Test Guideline 475
Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

Assessment: May cause drowsiness or dizziness.

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000001078 Date of last issue: 04/25/2018
Date of first issue: 08/22/2017

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 09/06/2018

SAFETY DATA SHEET



Car Brite™ FAST WAX Liquid Wax

Version	Revision Date:	SDS Number:	Date of last issue: 04/25/2018
2.0	09/06/2018	600000001078	Date of first issue: 08/22/2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN