

Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : EASIOFF YELLOW PASTE WX 12/16 OC

Product code : CBOOA010-01

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : WAX

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : Causes skin irritation.

May cause drowsiness or dizziness.

Precautionary statements : Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

Response:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum)	64742-88-7	>= 0 - <= 80
Raffinates (petroleum), sorption process	64741-85-1	>= 0 - <= 80

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on clothes, remove clothes.

Seek medical advice.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delaved

Causes skin irritation.

May cause drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air

and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the

point of release.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

Carbon oxides Silicon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Keep in suitable, closed containers for disposal.



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Take measures to prevent the build up of electrostatic charge.

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid creating dust.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : Ke

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Solvent naphtha (petroleum)	64742-88-7	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

Hazardous components without workplace control parameters

Components	CAS-No.
Raffinates (petroleum), sorp-	64741-85-1
tion process	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Provide appropriate exhaust ventilation at places where dust

is formed.

Personal protective equipment

Respiratory protection : In the case of dust or aerosol formation use respirator with an

approved filter.



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 60000000824 Date of first issue: 05/23/2016

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Safety glasses

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate:

Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

Avoid breathing dust. When using do not smoke. When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : yellow

Odour : pleasant

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 35 °C

(1,013 hPa)

The value is calculated

Flash point : 73.8 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

r : 7 %(V)

flammability limit

The value is calculated

Lower explosion limit / Lower :

flammability limit

0.7 %(V)

The value is calculated

Vapour pressure : 6.67 hPa (20 °C)

The value is calculated

Density : 0.871 g/cm3

Solubility(ies)



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Hazardous polymerisation does not occur.

Conditions to avoid : No data available

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Carbon oxides Silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Eye contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: 3,125 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 2,778 mg/kg

Method: Calculation method

Components:

Solvent naphtha (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.28 mg/l

Exposure time: 4 h
Test atmosphere: vapour



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

Method: OECD Test Guideline 403

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: No adverse effect has been observed in acute

dermal toxicity tests.

Raffinates (petroleum), sorption process:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Solvent naphtha (petroleum):

Species: Rabbit Result: Skin irritation

Raffinates (petroleum), sorption process:

Result: Repeated exposure may cause skin dryness or cracking.

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Product dust may be irritating to eyes, skin and respiratory system.

Components:

Solvent naphtha (petroleum):

Species: Rabbit

Result: No eye irritation

Raffinates (petroleum), sorption process:

Result: No eye irritation



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Solvent naphtha (petroleum):

Exposure routes: inhalation (vapour)
Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 3 with narcotic effects.

Raffinates (petroleum), sorption process:

Exposure routes: Inhalation



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Solvent naphtha (petroleum):

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Raffinates (petroleum), sorption process:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good



Car Brite™ EASI-OFF YELLOW Paste Wax

Version Revision Date: SDS Number: Date of last issue: 09/06/2018 3.0 09/13/2018 600000000824 Date of first issue: 05/23/2016

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Skin corrosion or irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.



Car Brite™ EASI-OFF YELLOW Paste Wax


 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/06/2018

 3.0
 09/13/2018
 600000000824
 Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 09/13/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN