

SAFETY DATA SHEET



Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : BLACK PEARL LIGHT CMPD 12/32 FOZ
Product code : CBOOBP03-02

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : POLISH
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3
Skin irritation : Category 2
Skin sensitisation : Category 1
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :  

Signal word : Warning

Hazard statements : Flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.

Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

May cause drowsiness or dizziness.

Precautionary statements :

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
If skin irritation or rash occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-47-8	>= 10 - < 20
Distillates (petroleum)	64742-47-8	>= 5 - < 10
Aluminum oxide	1344-28-1	>= 5 - < 10
White mineral oil	8042-47-5	>= 1 - < 5
Isopropanol	67-63-0	>= 1 - < 5
Glycerin	56-81-5	>= 1 - < 5
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-	4719-04-4	>= 0.1 - < 1

SAFETY DATA SHEET



Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

triazine

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO2)
Dry chemical
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Silicon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version	Revision Date:	SDS Number:	Date of last issue: 08/22/2018
3.0	09/06/2018	600000000678	Date of first issue: 05/23/2016

- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment : In the event of fire, wear self-contained breathing apparatus for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.

Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

Avoid contact with skin and eyes.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
Aluminum oxide	1344-28-1	ST (Mist)	10 mg/m ³	NIOSH REL
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total dust)	10 mg/m ³	OSHA P0
White mineral oil	8042-47-5	TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
		TWA (Respirable fraction)	1 mg/m ³ (Aluminium)	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL

Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

		ST (Mist)	10 mg/m ³	NIOSH REL
Isopropanol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm 980 mg/m ³	OSHA P0
		STEL	500 ppm 1,225 mg/m ³	OSHA P0
Glycerin	56-81-5	TWA (mist, respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (mist, total dust)	15 mg/m ³	OSHA Z-1
		TWA (Mist - total dust)	10 mg/m ³	OSHA P0
		TWA (Mist - respirable fraction)	5 mg/m ³	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Distillates (petroleum)	64742-47-8
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine	4719-04-4

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Isopropanol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

SAFETY DATA SHEET



Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

- gloves that show tears, pinholes, or signs of wear.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : yellow
- Odour : like fruit
- pH : 8
- Melting point/freezing point : 20 °C
- Boiling point/boiling range : 82.5 °C
(1,013.25 hPa)
The value is calculated
- Flash point : 35 °C
Method: Tag closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Flammability (liquids) : Static-accumulating flammable liquid.
- Self-ignition : >
236 °C
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapour pressure : 60.53 hPa (25 °C)
The value is calculated

SAFETY DATA SHEET



Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

Density : 1.02 g/cm³

Solubility(ies)
Water solubility : partly soluble

Partition coefficient: n-
octanol/water : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 10000 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-
tions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids
Aldehydes
Bases
Amines
halogens
Ethylene oxide
Halogenated compounds
Iron
isocyanates
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition : Carbon oxides
products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

**Car Brite™ BLACK PEARL™ LIGHT
COMPOUND VOC Compliant Body Shop-Safe**

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Distillates (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

White mineral oil:

Acute oral toxicity : LD50 (Rat): 50,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Isopropanol:

Acute oral toxicity : LD50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

Glycerin:

Acute oral toxicity : LD50 (Rat): 12,600 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 570 mg/m³
Exposure time: 1 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 10 g/kg

Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:

SAFETY DATA SHEET



Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

Acute oral toxicity : LD50 (Rat, female): 1,956 mg/kg
Acute inhalation toxicity : LC50 (Rat): 0.371 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 (Rat): > 2 g/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Distillates (petroleum):

Result: Irritating to skin.

Distillates (petroleum):

Result: Repeated exposure may cause skin dryness or cracking.

Aluminum oxide:

Result: Possibly irritating to skin

White mineral oil:

Assessment: No skin irritation

Result: No skin irritation

Isopropanol:

Result: Possibly irritating to skin

Glycerin:

Assessment: No skin irritation

Result: No skin irritation

Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

**Car Brite™ BLACK PEARL™ LIGHT
COMPOUND VOC Compliant Body Shop-Safe**

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

Components:

Distillates (petroleum):

Result: Possibly irritating to eyes

Aluminum oxide:

Result: Possibly irritating to eyes

White mineral oil:

Result: No eye irritation
Assessment: No eye irritation

Isopropanol:

Result: Irritating to eyes.

Glycerin:

Result: Possibly irritating to eyes

Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks: May cause allergic skin reaction.

Components:

Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:

Species: Guinea pig
Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

SAFETY DATA SHEET



Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0	Revision Date: 09/06/2018	SDS Number: 600000000678	Date of last issue: 08/22/2018 Date of first issue: 05/23/2016
----------------	------------------------------	-----------------------------	---

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Distillates (petroleum):

Assessment: May cause drowsiness or dizziness.

Distillates (petroleum):

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

Isopropanol:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version	Revision Date:	SDS Number:	Date of last issue: 08/22/2018
3.0	09/06/2018	600000000678	Date of first issue: 05/23/2016

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

- UN/ID No. : UN 1993
- Proper shipping name : Flammable liquid, n.o.s.
(HYDROTREATED PETROLEUM DISTILLATES,
ISOPROPANOL)
- Class : 3
- Packing group : III
- Labels : 3
- Packing instruction (cargo aircraft) : 366
- Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 1993
- Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(HYDROTREATED PETROLEUM DISTILLATES,
ISOPROPANOL)
- Class : 3
- Packing group : III
- Labels : 3
- EmS Code : F-E, S-E
- Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

- UN/ID/NA number : UN 1993
- Proper shipping name : Flammable liquids, n.o.s.
(HYDROTREATED PETROLEUM DISTILLATES,
ISOPROPANOL)
- Class : 3

SAFETY DATA SHEET



Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

Packing group : III
Labels : 3
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Safrole	94-59-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Skin corrosion or irritation
Respiratory or skin sensitisation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Aluminum oxide 1344-28-1 >= 5 - < 10 %

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, beta-Myrcene, Safrole, Ethyl Acrylate, Methyl Eugenol, Diethanolamine, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SAFETY DATA SHEET




Car Brite™ BLACK PEARL™ LIGHT COMPOUND VOC Compliant Body Shop-Safe

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000678 Date of last issue: 08/22/2018
Date of first issue: 05/23/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN