

Version 2.0	Revision Date: 09/06/2018		DS Number: 00000000679	Date of last issue: 05/06/2018 Date of first issue: 05/23/2016
SECTIO	ON 1. IDENTIFICATION			
Pro	oduct name	:	BLACK PEARL F	REMIUM POLISH 12/32 FOZ
Pro	oduct code	:	CBOOBP04-02	
	nufacturer or supplier's			
Co	mpany name of supplier	:	Niteo Products, L	LC
Ad	dress	:	Dallas TX 75225	
Err	ail Address	:	EHS@niteoprodu	icts.com
Te	ephone	:	1-844-696-4836	
Em bei	ergency telephone num-	:	1-800-424-9300 /	1-703-741-5970
Re	commended use of the c	hen	nical and restriction	ons on use
Re	commended use	:	POLISH	
Re	strictions on use	:	Use only outdoor	s or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accord Flammable liquids	dan :	ce with 29 CFR 1910.1200 Category 3
Skin sensitisation	:	Category 1
Specific target organ toxicity - single exposure	:	Category 3 (Central nervous system)
GHS label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Flammable liquid and vapour. May cause an allergic skin reaction. May cause drowsiness or dizziness.

SAFETY DATA SHEET

Car Brite[™] BLACK PEARL[™] PREMIUM POLISH VOC Compliant Body Shop-Safe



Precautiona			
Version 2.0 Revision Date: 09/06/2018 Precautionary statements	smoking. Keep container tig Ground/bond con Use explosion-pro Use only non-spa Take precautiona Avoid breathing d Use only outdoors Contaminated wo workplace.	tainer and receiving equipment. pof electrical/ ventilating/ lighting equipment.	
		clothing. Rinse sk IF INHALED: Ren for breathing. Call If skin irritation or Wash contaminat	air): Take off immediately all contaminated tin with water/shower. nove person to fresh air and keep comfortable I a POISON CENTER/doctor if you feel unwell. rash occurs: Get medical advice/ attention. ed clothing before reuse. te dry sand, dry chemical or alcohol-resistant h.
			ntilated place. Keep container tightly closed. ntilated place. Keep cool.
		Disposal: Dispose of conter plant.	nts/ container to an approved waste disposal

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum)	64742-47-8	>= 10 - < 20
Distillates (petroleum)	64742-47-8	>= 5 - < 10
Aluminum oxide	1344-28-1	>= 1 - < 5
Isopropanol	67-63-0	>= 1 - < 5
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s- triazine	4719-04-4	>= 0.1 - < 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES



Version 2.0	Revision Date: 09/06/2018	SDS Number: 600000000679	Date of last issue: 05/06/2018 Date of first issue: 05/23/2016
Ge	neral advice	Show this sa	dangerous area. afety data sheet to the doctor in attendance. e the victim unattended.
lf ir	nhaled	If unconscio advice.	sh air. hysician after significant exposure. us, place in recovery position and seek medical persist, call a physician.
In o	case of skin contact	Remove cor ical attention If on skin, rin Wash conta	a, remove clothes. htaminated clothing. If irritation develops, get med- h. hse well with water. minated clothing before re-use. on persists, call a physician.
In o	case of eye contact	Remove con Protect unha	with water as a precaution. htact lenses. armed eye. ide open while rinsing.
lf s	wallowed	Never give a	milk or alcoholic beverages. anything by mouth to an unconscious person. persist, call a physician.
and	st important symptoms d effects, both acute and ayed		an allergic skin reaction. drowsiness or dizziness.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Carbon dioxide (CO2) Dry chemical Alcohol-resistant foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	Carbon oxides Silicon oxides
Specific extinguishing meth- ods	:	Product is compatible with standard fire-fighting agents.
Further information	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

SAFETY DATA SHEET

Car Brite[™] BLACK PEARL[™] PREMIUM POLISH VOC Compliant Body Shop-Safe



Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2018
2.0	09/06/2018	60000000679	Date of first issue: 05/23/2016

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Remove all sources of ignition. Avoid breathing dust. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas. Evacuate personnel to safe areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Environmental precautions :	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for : containment and cleaning up	Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precau- tions may be necessary to dissipate static electricity for non- conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protec- tion Association document NFPA 77. Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. Do not spray on a naked flame or any incandescent material.
Advice on safe handling	:	Open drum carefully as content may be under pressure. Avoid formation of aerosol. Provide sufficient air exchange and/or exhaust in work rooms. Do not breathe vapours/dust. Do not smoke. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Dispose of rinse water in accordance with local and national



Version 2.0	Revision Date: 09/06/2018	SDS Number: 60000000679	Date of last issue: 05/06/2018 Date of first issue: 05/23/2016
Cor	nditions for safe storage	Smoking, eatir plication area. For personal p : Keep containe place. Containers wh	ardous when empty. ng and drinking should be prohibited in the ap- protection see section 8. r tightly closed in a dry and well-ventilated ich are opened must be carefully resealed and prevent leakage. precautions.
	ther information on stor- stability	: No decomposi	tion if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Distillates (petroleum)	64742-47-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
Aluminum oxide	1344-28-1	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWÁ (respir- able fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respir- able dust fraction)	5 mg/m3	OSHA P0
		TWA (Res- pirable frac- tion)	1 mg/m3 (Aluminium)	ACGIH
Isopropanol	67-63-0	TWÁ	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m3	NIOSH REL
		ST	500 ppm 1,225 mg/m3	NIOSH REL
		TWA	400 ppm 980 mg/m3	OSHA Z-1
		TWA	400 ppm 980 mg/m3	OSHA P0
		STEL	500 ppm	OSHA P0

Components with workplace control parameters



sion	Revision Date: 09/06/2018	-	-	umber:)000679	Date of las			
						1,225 mg	g/m3	
Haza	rdous components	witho	ut wo	rkplace cont	rol paramet	ers		
	oonents			S-No.				
	ates (petroleum)			42-47-8				
	hydro-1,3,5-tris(2- xyethyl)-s-triazine		4719	9-04-4				
Biolo	gical occupational	expos	ure li	mits				
Comp	ponents	CAS-N	lo.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Isopro	opanol	67-63	·0	Acetone	Urine	End of shift at end of work- week	40 mg/l	ACGIH BEI
-	neering measures	ipmen	ver app app	tilation to mai	ntain exposu low levels that	ire below e	nd/or local exh exposure guide nown, suspecte	lines (if
	iratory protection	:	In t	he case of vap ved filter.	oour formatic	on use a re	spirator with ar	n ap-
Hand	protection							
Re	emarks	:	er). cus	The suitability	y for a specif producers of	ic workplace the protect	ety equipment s ce should be di ive gloves. Dis is of wear.	is-
Eye p	protection	:	pro				use. Wear spl misted or spla	
Skin a	and body protection	:	cer We Imp Fla		dangerous s iate: ng		e amount and c at the work plac	
Hygie	ene measures	:	pra Wh	ndle in accord ctice. en using do n en using do n	ot smoke.		al hygiene and	safety

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid



Revision Date: 09/06/2018			Date of last issue: 05/06/2018 Date of first issue: 05/23/2016
	:	light grey	
	:	like fruit	
	:	8	
point/freezing point	:	No data available	9
point/boiling range	:	82.5 °C (1,013.23 hPa)	
oint	:	The value is calc 40 °C	ulated
ation rate	:	No data available	9
ability (solid, gas)	:	No data available	9
ability (liquids)	:	Static-accumulat	ing flammable liquid.
nition	:	No data available	9
explosion limit / Upper bility limit	:	12 %(V) The value is calc	ulated
explosion limit / Lower bility limit	•	0.6 %(V) The value is calc	ulated
pressure	:	60.53 hPa (25 °C The value is calc	
	:	1.019 g/cm3 (20	°C)
ty(ies) er solubility	:	No data available	9
n coefficient: n- /water	:	No data available	9
ty osity, dynamic	:	No data available	9
osity, kinematic	:	> 10000 mm2/s ((40 °C)
ng properties	:	No data available	9
	09/06/2018 point/freezing point point/boiling range oint ation rate ability (solid, gas) ability (liquids) nition explosion limit / Upper bility limit explosion limit / Lower bility limit pressure ty(ies) er solubility n coefficient: n- /water ty osity, kinematic	09/06/2018600	09/06/201860000000679:light grey:like fruit:8point/freezing point:No data availablepoint/boiling range:82.5 °C (1,013.23 hPa) The value is calcoint:40 °Cation rate:No data availableability (solid, gas):No data availableability (liquids):Static-accumulatnition:No data availableexplosion limit / Upper:12 %(V) The value is calcpressure:0.6 %(V) The value is calcpressure:60.53 hPa (25 °C The value is calcity (ies):No data availableer solubility:No data availablein coefficient: n- (water:No data availableosity, kinematic:No data availableosity, kinematic:>::No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reac- tions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.



Version 2.0	Revision Date: 09/06/2018	SDS Number: 60000000679	Date of last issue: 05/06/2018 Date of first issue: 05/23/2016
Con	ditions to avoid	: Heat, flames a	nd sparks.
Inco	mpatible materials	: Acids Aldehydes Bases Amines halogens Ethylene oxide Halogenated c isocyanates Strong oxidizin Strong reducin	ompounds g agents
	ardous decomposition lucts	: Carbon oxides Silicon oxides	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes Inhalation Skin contact Eye contact Ingestion	s of	exposure
Acute toxicity		
Not classified based on availa	able	information.
Product:		
Acute inhalation toxicity	:	Acute toxicity estimate: > 200 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
Components:		
Distillates (petroleum):		
Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, male and female): Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: No adverse effect has been observed in acute dermal toxicity tests.
Isopropanol:		
Acute oral toxicity	:	LD50 (Rat): 5.84 g/kg

SAFETY DATA SHEET



Car Brite[™] BLACK PEARL[™] PREMIUM POLISH VOC Compliant Body Shop-Safe

Version 2.0	Revision Date: 09/06/2018	SDS Number: 60000000679	Date of last issue: 05/06/2018 Date of first issue: 05/23/2016
Acu	te inhalation toxicity	: LC50 (Rat): 16 Exposure time Test atmosphe	: 4 h
Acu	te dermal toxicity	: LD50 (Rabbit):	: 12,800 mg/kg
	a hydro-1,3,5-tris(2-hyd te oral toxicity		e: nale): 1,956 mg/kg
Acu	te inhalation toxicity	: LC50 (Rat): 0. Exposure time Test atmosphe	: 4 h
Acu	te dermal toxicity	: LD50 (Rat): >	2 g/kg
-	n corrosion/irritation classified based on avail	able information.	
Pro	duct:		
Ren	narks: May irritate skin.		
<u>Cor</u>	nponents:		
	tillates (petroleum): sult: Repeated exposure i	may cause skin dryne	ess or cracking.
	tillates (petroleum): sult: Irritating to skin.		
	minum oxide: sult: Possibly irritating to s	skin	
100			
-	oropanol: oult: Possibly irritating to s	skin	
	ahydro-1,3,5-tris(2-hyd sult: Possibly irritating to s		e:
	ious eye damage/eye ir classified based on avail		
	<u>duct:</u> narks: Vapours may caus	se irritation to the eye	es, respiratory system and the skin.
Cor	nponents:		
Dist	tillates (petroleum):		
Res	ult: Possibly irritating to e	eyes	



Version Re 2.0 09

Revision Date: 09/06/2018

SDS Number: 60000000679

Date of last issue: 05/06/2018 Date of first issue: 05/23/2016

Aluminum oxide:

Result: Possibly irritating to eyes

Isopropanol: Result: Irritating to eyes.

Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation Not classified based on available information.

Product:

Remarks: May cause allergic skin reaction.

Components:

Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine:

Species: Guinea pig Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.



Date of last issue: 05/06/2018 Date of first issue: 05/23/2016

Car Brite[™] BLACK PEARL[™] PREMIUM POLISH VOC Compliant Body Shop-Safe

Version	Revision Date:	SDS Number:
2.0	09/06/2018	60000000679

Components:

Distillates (petroleum):

Target Organs: Central nervous system Assessment: May cause drowsiness or dizziness.

Distillates (petroleum):

Assessment: May cause drowsiness or dizziness.

Isopropanol:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Distillates (petroleum):

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.



Version Revis 2.0 09/06

Revision Date: 09/06/2018

SDS Number: 60000000679 Date of last issue: 05/06/2018 Date of first issue: 05/23/2016

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR		
UN/ID No.	:	UN 1993
Proper shipping name	:	Flammable liquid, n.o.s. (ISOPROPANOL, SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC)
Class	:	3
Packing group	:	III
Labels	:	3
Packing instruction (cargo aircraft)	:	366
Packing instruction (passenger aircraft)	:	355
IMDG-Code		
UN number	:	UN 1993
Proper shipping name	:	FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC)
Class	:	3
Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>
Marine pollutant	:	no
Transport in bulk according	to	Annex II of MARPOL 73/78 and the IBC Code
Not applicable for product as	sup	plied.
National Regulations		
49 CFR		

UN/ID/NA number	:	UN 1993
Proper shipping name	:	Flammable liquids, n.o.s. (ISOPROPANOL, SOLVENT NAPHTHA (PETROLEUM), HEAVY ALIPHATIC)
Class	:	3
Packing group	:	III
Labels	:	3
ERG Code	:	128
Marine pollutant	:	no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity



Version 2.0	Revision Date: 09/06/2018	SDS Number: 60000000679	Date of last issue: Date of first issue:	
Comp	onents	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Dietha	anolamine	111-42-2	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity


This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards :	Flammable (gases, aerosols, liquids, or solids) Hazard not otherwise classified (physical hazards) Respiratory or skin sensitisation Specific target organ toxicity (single or repeated exposure)
SARA 313 :	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, Diethanolamine, which is/are known to the State of California to cause cancer, and Ethylene Glycol, Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION





Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2018
2.0	09/06/2018	60000000679	Date of first issue: 05/23/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN