

## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

Version Revision Date: SDS Number: Date of last issue: 05/06/2018 2.0 09/06/2018 600000000753 Date of first issue: 05/23/2016

#### **SECTION 1. IDENTIFICATION**

Product name : SELECT NONACD WHL TRE CLNR VOC PL 5GA-CA

Product code : 777791C

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

: 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Corrosive to metals : Category 1

Skin corrosion : Category 1

Serious eye damage : Category 1

**GHS** label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : May be corrosive to metals.

Causes severe skin burns and eye damage.

Precautionary statements : Prevention:

Keep only in original container.



## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

Version Revision Date: SDS Number: Date of last issue: 05/06/2018 2.0 09/06/2018 600000000753 Date of first issue: 05/23/2016

Wash skin thoroughly after handling.

Wear protective gloves/ protective clothing/ eye protection/ face

protection.

## Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

#### Storage:

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

#### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

## **Hazardous components**

| Chemical name                   | CAS-No.   | Concentration (% w/w) |
|---------------------------------|-----------|-----------------------|
| Sodium hydroxide                | 1310-73-2 | >= 5 - < 10           |
| Ethylene glycol monobutyl ether | 111-76-2  | >= 1 - < 5            |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.

If on skin, rinse well with water.

Wash contaminated clothing before re-use.



## **SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant**

Version Revision Date: SDS Number: Date of last issue: 05/06/2018 09/06/2018 60000000753 Date of first issue: 05/23/2016 2.0

If skin irritation persists, call a physician.

In case of eye contact In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If swallowed Get medical attention immediately.

> Do NOT induce vomiting. Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Causes serious eye damage.

Causes severe burns.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions Prevent further leakage or spillage if safe to do so.



## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

Version Revision Date: SDS Number: Date of last issue: 05/06/2018 2.0 09/06/2018 600000000753 Date of first issue: 05/23/2016

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : Ke

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

| Components                      | CAS-No.   | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis     |
|---------------------------------|-----------|-------------------------------------|--|-----------|
| Sodium hydroxide                | 1310-73-2 | С                                   | 2 mg/m3  | ACGIH     |
|                                 |           | С                                   | 2 mg/m3  | NIOSH REL |
|                                 |           | TWA                                 | 2 mg/m3  | OSHA Z-1  |
|                                 |           | С                                   | 2 mg/m3  | OSHA P0   |
| Ethylene glycol monobutyl ether | 111-76-2  | TWA                                 | 20 ppm   | ACGIH     |
|                                 |           | TWA                                 | 5 ppm<br>24 mg/m3                              | NIOSH REL |
|                                 |           | TWA                                 | 50 ppm<br>240 mg/m3                            | OSHA Z-1  |
|                                 |           | TWA                                 | 25 ppm<br>120 mg/m3                            | OSHA P0   |



## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2018

 2.0
 09/06/2018
 600000000753
 Date of first issue: 05/23/2016

## **Biological occupational exposure limits**

| Components                           | CAS-No.  | Control parameters              | Biological specimen | Sam-<br>pling<br>time  | Permissible concentra-tion | Basis        |
|--------------------------------------|----------|---------------------------------|---------------------|--|----------------------------|--------------|
| Ethylene glycol mono-<br>butyl ether | 111-76-2 | Butoxyace-<br>tic acid<br>(BAA) | Urine               | End of<br>shift (As<br>soon as<br>possible<br>after<br>exposure<br>ceases) | 200 mg/g<br>Creatinine     | ACGIH<br>BEI |

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

## Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles and face shield when there is

potential for exposure of the eyes or face to liquid, vapor or

mist.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing

Safety shoes

Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : brown

Odour : ammoniacal

pH : ca. 13

Melting point/freezing point : No data available



## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

Version Revision Date: SDS Number: Date of last issue: 05/06/2018 2.0 09/06/2018 600000000753 Date of first issue: 05/23/2016

Boiling point/boiling range : 100 °C

(1,013 hPa)

The value is calculated

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

: 10.6 %(V)

The value is calculated

Lower explosion limit / Lower

flammability limit

1.1 %(V)

The value is calculated

Vapour pressure : 23.33 hPa (20 °C)

The value is calculated

Density : ca. 1.095 g/cm3 (20 °C)

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Hazardous polymerisation does not occur.

Conditions to avoid : Do not allow evaporation to dryness.

Exposure to sunlight. Exposure to moisture

Incompatible materials : Acids

Aluminium Amines Ammonia Bases chlorates



## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2018

 2.0
 09/06/2018
 600000000753
 Date of first issue: 05/23/2016

Chlorine

Halogenated compounds

Metals

organic nitro compounds salts of strong bases Strong oxidizing agents

water

Hazardous decomposition

products

Carbon oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation Skin contact Eye contact Ingestion

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Remarks: Causes digestive tract burns.

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

**Components:** 

Sodium hydroxide:

Acute oral toxicity : LDLo (Rabbit): 500 mg/kg

Ethylene glycol monobutyl ether:

Acute oral toxicity : LD50 (Guinea pig): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Guinea pig): > 633 ppm

Exposure time: 1 h

Test atmosphere: dust/mist

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2,000 mg/kg

Assessment: The component/mixture is moderately toxic after

single contact with skin.



## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2018

 2.0
 09/06/2018
 600000000753
 Date of first issue: 05/23/2016

#### Skin corrosion/irritation

Causes severe burns.

#### **Product:**

Remarks: Causes severe skin burns and eye damage. The feeling of irritation or pain may be delayed.

## **Components:**

## Sodium hydroxide:

Result: Corrosive after 3 minutes or less of exposure

## Ethylene glycol monobutyl ether:

Result: Irritating to skin.

## Serious eye damage/eye irritation

Causes serious eye damage.

#### **Product:**

Remarks: May cause irreversible eye damage.

## **Components:**

## Sodium hydroxide:

Result: Irreversible effects on the eye

Assessment: Corrosive

## Ethylene glycol monobutyl ether:

Result: Irritating to eyes. Assessment: Irritating to eyes.

## Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

## Respiratory sensitisation

Not classified based on available information.

## **Components:**

## Sodium hydroxide:

Exposure routes: Skin contact

Species: Humans Result: negative

#### Germ cell mutagenicity

Not classified based on available information.

## **Components:**

## Ethylene glycol monobutyl ether:



## SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant

Version Revision Date: SDS Number: Date of last issue: 05/06/2018 2.0 09/06/2018 600000000753 Date of first issue: 05/23/2016

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

**Further information** 

**Product:** 

Remarks: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.



## **SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2018

 2.0
 09/06/2018
 600000000753
 Date of first issue: 05/23/2016

#### **SECTION 14. TRANSPORT INFORMATION**

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## International Regulations

**IATA-DGR** 

UN/ID No. : UN 1824

Proper shipping name : SODIUM HYDROXIDE SOLUTION

Class : 8
Packing group : II
Labels : 8
Packing instruction (cargo : 855

aircraft)

Packing instruction : 851

(passenger aircraft)

**IMDG-Code** 

UN number : UN 1824

Proper shipping name : SODIUM HYDROXIDE SOLUTION

Class : 8
Packing group : II
Labels : 8
EmS Code : F-A, S-

EmS Code : F-A, S-B Marine pollutant : no

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**49 CFR** 

UN/ID/NA number : UN 1824

Proper shipping name : SODIUM HYDROXIDE SOLUTION

Class : 8
Packing group : II
Labels : 8
ERG Code : 154
Marine pollutant : no

## **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

## **CERCLA Reportable Quantity**

| Components       | CAS-No.   | Component RQ | Calculated product RQ |  |
|------------------|-----------|--------------|-----------------------|--|
|                  |           | (lbs)        | (lbs)                 |  |
| Sodium hydroxide | 1310-73-2 | 1000         | *                     |  |

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.



## **SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2018

 2.0
 09/06/2018
 600000000753
 Date of first issue: 05/23/2016

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Corrosive to metals

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Ethylene glycol mono-

111-76-2

>= 1 - < 5 %

butyl ether


## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **SECTION 16. OTHER INFORMATION**

## **Further information**

#### NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



# **SELECT NONACID WHEEL & TIRE CLNR VOC- VOC Compliant**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2018

 2.0
 09/06/2018
 600000000753
 Date of first issue: 05/23/2016

US / EN