

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : BLACK ENGINE PAINT 4/1 GA
Product code : CBOOG002-03

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC
Address : Dallas TX 75225
Email Address : EHS@niteoproducts.com
Telephone : 1-844-696-4836
Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : Paint
Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2A
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))
Aspiration hazard : Category 1

GHS label elements

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging the unborn child.
May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Precautionary statements

: **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
 Date of first issue: 05/23/2016

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Toluene	108-88-3	>= 30 - < 50
Isopropanol	67-63-0	>= 20 - < 30
Acetone	67-64-1	>= 10 - < 20
n-Butyl acetate	123-86-4	>= 5 - < 10
Xylene	1330-20-7	>= 5 - < 10
Ethyl acetate	141-78-6	>= 5 - < 10

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Symptoms of poisoning may appear several hours later.
 Do not leave the victim unattended.
- If inhaled : Move to fresh air.
 Consult a physician after significant exposure.
 If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : If on clothes, remove clothes.
 Remove contaminated clothing. If irritation develops, get medical attention.
 If on skin, rinse well with water.
 Wash contaminated clothing before re-use.
 If skin irritation persists, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.
 Do NOT induce vomiting.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.

Car Brite™ BLACK ENGINE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 05/11/2018
3.0	09/06/2018	600000000823	Date of first issue: 05/23/2016

Most important symptoms and effects, both acute and delayed :

- May be fatal if swallowed and enters airways.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Suspected of damaging the unborn child.
- May cause damage to organs through prolonged or repeated exposure if inhaled.
- Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
- This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.
- This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Further information : Do not use a solid water stream as it may scatter and spread fire.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Car Brite™ BLACK ENGINE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 05/11/2018
3.0	09/06/2018	600000000823	Date of first issue: 05/23/2016

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid breathing dust.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.
Keep away from open flames, hot surfaces and sources of ignition.
Use only explosion-proof equipment.
Do not spray on a naked flame or any incandescent material.
- Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Take precautionary measures against static discharges.
Avoid contact with skin and eyes.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
 Date of first issue: 05/23/2016

Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 No smoking.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m ³	OSHA P0
Isopropanol	67-63-0	STEL	150 ppm 560 mg/m ³	OSHA P0
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm 980 mg/m ³	OSHA P0
Acetone	67-64-1	STEL	500 ppm 1,225 mg/m ³	OSHA P0
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m ³	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
n-Butyl acetate	123-86-4	TWA	150 ppm 710 mg/m ³	NIOSH REL
		ST	200 ppm 950 mg/m ³	NIOSH REL

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version
3.0

Revision Date:
09/06/2018

SDS Number:
600000000823

Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

		TWA	150 ppm 710 mg/m3	OSHA Z-1
		TWA	150 ppm 710 mg/m3	OSHA P0
		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
Ethyl acetate	141-78-6	TWA	400 ppm	ACGIH
		TWA	400 ppm 1,400 mg/m3	NIOSH REL
		TWA	400 ppm 1,400 mg/m3	OSHA Z-1
		TWA	400 ppm 1,400 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Xylene	1330-20-7

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Isopropanol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

Car Brite™ BLACK ENGINE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 05/11/2018
3.0	09/06/2018	600000000823	Date of first issue: 05/23/2016

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.
- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Flame-resistant clothing
Safety shoes
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Colour : black
- Odour : solvent-like
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 56 - 143 °C
- Flash point : -3.8 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Flammability (liquids) : Static-accumulating flammable liquid.
- Self-ignition : No data available

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

Upper explosion limit / Upper flammability limit : 13.0 %(V)

Lower explosion limit / Lower flammability limit : 1.2 %(V)

Vapour pressure : 180 hPa (20 °C)

Density : 0.9615 g/cm³

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids
Aldehydes
Bases
Aluminium
Amines
Ammonia
Ethylene oxide
Halogenated compounds
halogens
isocyanates
Nitrous acid and other nitrosating agents
Combustible material
Peroxides
Reducing agents
Strong bases
Strong oxidizing agents
Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.

Hazardous decomposition products : Carbon oxides

Car Brite™ BLACK ENGINE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 05/11/2018
3.0	09/06/2018	600000000823	Date of first issue: 05/23/2016

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Eye contact
Skin contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 61.66 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Remarks: Breathing air containing n-butyl acetate, which results from its use in aerosol applications, may cause delayed lung injury.

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**Toluene:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Isopropanol:

Acute oral toxicity : LD50 (Rat): 5.84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

Acetone:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l
Exposure time: 4 h
Test atmosphere: vapour

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

n-Butyl acetate:

Acute oral toxicity : LD50 (Rat, female): 10.8 g/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 14,112 mg/kg
Method: OECD Test Guideline 402

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 - 8,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 6700 ppm
Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 1,700 mg/kg

Ethyl acetate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC0 (Rat): > 6000 ppm
Exposure time: 6 h
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Components:

Toluene:

Result: Irritating to skin.

Isopropanol:

Result: Possibly irritating to skin

Car Brite™ BLACK ENGINE PAINT

Version	Revision Date:	SDS Number:	Date of last issue: 05/11/2018
3.0	09/06/2018	600000000823	Date of first issue: 05/23/2016

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

Xylene:

Assessment: Irritating to skin.

Result: Irritating to skin.

Ethyl acetate:

Species: Rabbit

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

Toluene:

Result: Irritating to eyes.

Isopropanol:

Result: Irritating to eyes.

Acetone:

Result: Irritating to eyes.

Assessment: Irritating to eyes.

n-Butyl acetate:

Species: Rabbit

Result: Possibly irritating to eyes

Method: OECD Test Guideline 405

Xylene:

Result: Irritating to eyes.

Ethyl acetate:

Species: Rabbit

Result: Possibly irritating to eyes

Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Ethyl acetate:**

Test Type: Maximisation Test

Result: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:**n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Cell type: Bone marrow
Method: OECD Test Guideline 474
Result: negative

Ethyl acetate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Toluene:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Toluene:

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

Isopropanol:

Assessment: May cause drowsiness or dizziness.

Acetone:

Exposure routes: Inhalation
Target Organs: Nervous system
Assessment: May cause drowsiness or dizziness.

n-Butyl acetate:

Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

Xylene:

Assessment: May cause drowsiness or dizziness., May cause respiratory irritation.

Ethyl acetate:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

Components:

Toluene:

Exposure routes: Inhalation
Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)
Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version 3.0 Revision Date: 09/06/2018 SDS Number: 600000000823 Date of last issue: 05/11/2018
Date of first issue: 05/23/2016

Components:

Toluene:

May be fatal if swallowed and enters airways.

Acetone:

May be harmful if swallowed and enters airways.

Xylene:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
-

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

- UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : II
Labels : 3
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version Revision Date: SDS Number: Date of last issue: 05/11/2018
 3.0 09/06/2018 600000000823 Date of first issue: 05/23/2016

UN number : UN 1263
 Proper shipping name : PAINT

Class : 3
 Packing group : II
 Labels : 3
 EmS Code : F-E, S-E
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1263
 Proper shipping name : Paint

Class : 3
 Packing group : II
 Labels : 3
 ERG Code : 128
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	2000
Xylene	1330-20-7	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Hazard not otherwise classified (physical hazards)
 Skin corrosion or irritation
 Serious eye damage or eye irritation
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)
 Aspiration hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene 108-88-3 >= 30 - < 50 %

SAFETY DATA SHEET



Car Brite™ BLACK ENGINE PAINT

Version
3.0

Revision Date:
09/06/2018

SDS Number:
600000000823

Date of last issue: 05/11/2018
Date of first issue: 05/23/2016


California Prop. 65

WARNING: This product can expose you to chemicals including Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN