

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

 TROPHY WAX Cleaner & Glaze
 CBWPA056-03-U

Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION
Product identifier

 Trade name : TROPHY WAX
 Cleaner & Glaze

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300 Product Information 1-844-696-4836
--	---

SECTION 2. HAZARDS IDENTIFICATION
GHS Classification

 Flammable liquids : Category 3
 Carcinogenicity : Category 1A
 Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

GHS Label element

 Hazard pictograms :   

Signal Word : Danger

 Hazard Statements : Flammable liquid and vapor.
 May cause drowsiness or dizziness.
 May cause cancer.

 Precautionary Statements : **Prevention:**
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 IF exposed or concerned: Get medical advice/ attention.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static Accumulating liquid

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
 Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304	24.15
WHITE MINERAL OIL	8042-47-5	Not a hazardous	2.29

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

		substance or mixture.	
HYDROTREATED HEAVY NAPHTHA	64742-48-9	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 Asp. Tox. 1; H304	2.22
GLYCERIN	56-81-5	Not a hazardous substance or mixture.	1.00
QUARTZ (SiO ₂)	14808-60-7	Carc. 1A; H350 STOT RE 1; H372	0.10

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
If unconscious place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

If swallowed : Obtain medical attention.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)

Lung irritation

confusion

irregular heartbeat

Convulsions

May cause drowsiness or dizziness.

May cause cancer.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water spray

Foam

Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
aluminum oxides
silicon oxides
formaldehyde
Hydrogen chloride gas
carbon
sulfur oxides
Aldehydes
nitrogen oxides (NOx)
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

 TROPHY WAX Cleaner & Glaze
 CBWPA056-03-U

Version: 1.1

Other information : Comply with all applicable federal, state, and local regulations.
 Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.
 Avoid formation of aerosol.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Container hazardous when empty.
 Take precautionary measures against static discharges.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Observe label precautions.
 No smoking.
 Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	200 mg/m ³ Non-aerosol (as total hydrocarbon vapor)	ACGIH
		REL	100 mg/m ³	NIOSH/GUID E
WHITE MINERAL OIL	8042-47-5	REL	5 mg/m ³ Mist.	NIOSH/GUID E
		STEL	10 mg/m ³ Mist.	NIOSH/GUID E

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

		PEL	5 mg/m3 Mist.	OSHA_TRANS
		TWA	5 mg/m3 Mist.	TN OEL
		TWA	5 mg/m3 Inhalable fraction.	ACGIH
HYDROTREATED HEAVY NAPHTHA	64742-48-9	TWA	100 ppm	SUPLR EXP

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

Appearance : viscous

Physical state : liquid

Colour : light orange

Odour : like fruit

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : 32 °F / 0 °C
No data available

Boiling point/boiling range : > 150 °F / 66 °C
(1013.33 hPa)

Flash point : 133.9 °F / 56.6 °C
Method: Pensky Martens closed cup

Evaporation rate : 0.66

Flammability (solid, gas) :
No data available

Flammability (liquids) : Static Accumulating liquid

Flammability (liquids) :
Upper explosion limit : 11.2 %(V)

Lower explosion limit : 2 %(V)

Vapour pressure : 23.3333333 hPa (20 °C)
Calculated Vapor Pressure

Relative vapour density : > 10

Relative density : No data available

Density : +/- 0.005 0.957 g/cm3 (20 °C)

Solubility(ies)
Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : > 100 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
excessive heat
Exposure to sunlight.

Incompatible materials : alkalis
Iron
reducing agents
steel
Strong acids
Strong bases
Strong oxidizing agents

Hazardous decomposition products : acrolein
Aldehydes
carbon dioxide and carbon monoxide
formaldehyde
Hydrocarbons
Hydrogen chloride gas
silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

WHITE MINERAL OIL:

Acute oral toxicity : LD 50 (Rat): 50,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.

GLYCERIN:

Acute oral toxicity : LD 50 (Rat): 12,600 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC 50 (Rat): > 570 mg/m³
Exposure time: 1 h
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 10 g/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Mildly irritating to skin

WHITE MINERAL OIL:

Result: Not irritating to skin

HYDROTREATED HEAVY NAPHTHA:

Result: Irritating to skin

GLYCERIN:

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

esult: Not irritating to skin

QUARTZ (SiO₂):

Result: Possibly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Mildly irritating to eyes

WHITE MINERAL OIL:

Result: Not irritating to eyes

HYDROTREATED HEAVY NAPHTHA:

Result: Irritating to eyes

GLYCERIN:

Result: Mildly irritating to eyes

QUARTZ (SiO₂):

Result: Possibly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

Components:

QUARTZ (SiO₂):

Carcinogenicity - : Human carcinogen.

Assessment

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Assessment: May cause drowsiness or dizziness.

HYDROTREATED HEAVY NAPHTHA:

Assessment: May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

QUARTZ (SiO₂):

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

Exposure routes: inhalation (dust/mist/fume)
Target Organs: Respiratory system, Kidney
Assessment: Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

HYDROTREATED HEAVY NAPHTHA:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

QUARTZ (SiO₂):

Remarks: Lung

Carcinogenicity:

IARC

Group 1: Carcinogenic to humans

QUARTZ / SAND 14808-60-7

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Known to be human carcinogen

QUARTZ / SAND 14808-60-7

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

GLYCERIN:

Toxicity to fish : LC 50 (Goldfish (Carassius auratus)): > 5,000 mg/l
Exposure time: 24 h
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 24 h
Method: Static
Remarks: Mortality

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

Persistence and degradability

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Biodegradability : Result: Inherently biodegradable
Biodegradation: 58.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

HYDROTREATED HEAVY NAPHTHA:

Biodegradability : Remarks: Not readily biodegradable.

Bioaccumulative potential

GLYCERIN:

Partition coefficient: n-
octanol/water : log Pow: -1.76

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological
information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and
federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste
handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International transport regulations****REGULATION**

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

UN 1993	Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	--	---	--	-----	--

U.S. DOT - RAIL

UN 1993	Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	--	---	--	-----	--

U.S. DOT - INLAND WATERWAYS

UN 1993	Flammable liquids, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	--	---	--	-----	--

TRANSPORT CANADA - ROAD

UN 1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	---	---	--	-----	--

TRANSPORT CANADA - RAIL

UN 1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	---	---	--	-----	--

TRANSPORT CANADA - INLAND WATERWAYS

UN 1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	---	---	--	-----	--

INTERNATIONAL MARITIME DANGEROUS GOODS

UN 1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	---	---	--	-----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN 1993	Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3		III	
---------	---	---	--	-----	--

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
----	------	--	---	-----

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	1993	LIQUIDO INFLAMABLE, N.E.P. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
----	------	--	---	-----

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard
Chronic Health Hazard
Acute Health Hazard

SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65 WARNING! This product contains a chemical known to the State of California to cause cancer.
QUARTZ / SAND 14808-60-7
BENZENE 71-43-2
WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
ETHYLENE GLYCOL 109-86-4
MONOMETHYL ETHER
BENZENE 71-43-2

The components of this product are reported in the following inventories:
TSCA : On TSCA Inventory

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

- DSL : All components of this product are on the Canadian DSL.
- AICS : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 08/01/2015

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p> <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	2	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	2						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

Full text of H-Statements referred to under sections 2 and 3.

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H313	May be harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

SAFETY DATA SHEET

Revision Date: 08/01/2015

Print Date: 06/02/2017

SDS Number: 600000000707

TROPHY WAX Cleaner & Glaze
CBWPA056-03-U

Version: 1.1

PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System