

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product form : Mixture

Product name : AQUASHINE SPRAYABLE POLYMER SEALANT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Automoblie Wax

1.3. Details of the supplier of the safety data sheet

ULTRA-LOOK CORP. 3903 Progress Drive Lakeland, FL 33811 Phone: 863-607-6700 www.carcandy.com

1.4. Emergency telephone number

Emergency number : 1-800-535-5053 INFOTRAC

### SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

### **Classification (GHS-US)**

Flam. Liq. 3 H226 - Flammable liquid and vapour Muta. 1B H340 - May cause genetic defects Carc. 1B H350 - May cause cancer

Full text of H-phrases: see section 16

#### 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)



02 GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor H340 - May cause genetic defects

H350 - May cause cancer

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 - Keep container tightly closed P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower

P308+P313 - If exposed or concerned: Get medical advice/attention

P370+P378 - In case of fire: Use ... to extinguish P403+P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

P501 - Dispose of contents/container to ...

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

09/02/2017 ULTRA-LOOK CORP. EN (English US) Page 1

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
solvent naphtha (petroleum), light aromatic	(CAS No) 64742-95-6	5 - 10	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
naphtha (petroleum), hydrotreated heavy	(CAS No) 64742-48-9	1 - 5	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If not breathing, give artificial

respiration. Obtain medical attention.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash skin thoroughly with mild soap

and water. Call a physician immediately. Wash clothing before re-using.

First-aid measures after eye contact : Rinse thoroughly with plenty of water for at least 20 minutes and take medical advice.

First-aid measures after ingestion : Do NOT induce vomiting. Obtain medical attention. Never give anything by mouth to an

unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquids.

Explosion hazard : Take precautionary measures against static discharge during blending and transfer operations.

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

#### 5.3. Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool down the

containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact

between the water and the product.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

Other information : Combustion produces irritating gases. Carbon oxides (CO, CO2). Silicon oxides.

Formaldehyde. Nitrogen oxides.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep public away.

### 6.1.1. For non-emergency personnel

Protective equipment : Use chemically protective clothing.

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable

protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8 Exposure controls/personal protection" ".

09/02/2017 ULTRA-LOOK CORP. EN (English US) 2/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 8: Exposure-controls/personal protection"".

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed

essed : This product is hazardous.

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area

must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke

when using this product. Always wash hands after handling the product. Wash clothing before

re-using.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up. Keep away from heat and direct

sunlight. Inspect frequently to identify any sing of warping or leak of the containers. No

smokina

Special rules on packaging : Always keep in containers made of the same material as the supply container.

### SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Hand protection : Impermeable protective gloves. Wear long sleeves. Use protective clothing.

Eye protection : Safety glasses. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear respiratory protection.

Environmental exposure controls : Avoid release to the environment.

Other information : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Clear amber to Orange to opaque Light Orange when shaken

Odor : Mild Alcohol and petroleum odour

Odor threshold : No data available pH : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available : No data available

Flash point : ≈ 29 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available

09/02/2017 ULTRA-LOOK CORP. EN (English US) 3/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Explosion limits** : No data available Explosive properties : No data available Oxidizing properties No data available Vapor pressure : No data available : No data available Relative density Relative vapor density at 20 °C No data available Solubility : No data available Log Pow No data available Auto-ignition temperature : No data available : No data available Decomposition temperature : No data available Viscosity Viscosity, kinematic : No data available Viscosity, dynamic : No data available

9.2. Other information

VOC content : < 15 %

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Keep away from: strong acids, strong bases and oxidation agents.

### 10.6. Hazardous decomposition products

irritating gases.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Likely routes of exposure : Skin contact.; Eyes contact.; Inhalation; Ingestion.

Acute toxicity : Not classified

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : May cause genetic defects.

Carcinogenicity : May cause cancer.

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Other information : CNS depression.

09/02/2017 ULTRA-LOOK CORP. EN (English US) 4/7

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Do not discharge into drains or the environment. Do not discharge into surface water.

#### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Log Pow	2.1 - 6

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Flammable vapors may accumulate in the container.

## **SECTION 14: Transport information**

#### **Department of Transportation (DOT)**

In accordance with DOT

Transport document description : NA1993 Combustible liquid, n.o.s., 3, III

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

Hazard Classes (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN

requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672).

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information : No supplementary information available.

09/02/2017 ULTRA-LOOK CORP. EN (English US) 5/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **TDG**

No additional information available

#### Transport by sea

UN-No. (IMDG) : 1993

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Air transport

UN-No.(IATA) : 1993

Proper Shipping Name (IATA) : FLAMMABLE LIQUID, N.O.S.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III - Minor Danger

### **SECTION 15: Regulatory information**

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

2-propanol	CAS No 67-63-0	1 - 5%

### 15.2. International regulations

#### **CANADA**

During the transition period (June 2015-June 2017), Canadian regulation requires that the supplier must provide a document that conforms to either *Controlled Products Regulations* (WHMIS 1988) or HPR (WHMIS 2015), and not a combination of both. This document conforms to the post June 2017 HPR (WHMIS 2015) for a specific controlled or hazardous product. The classification, label and (material) SDS fully complies with the specific regulation chosen by the supplier.

### **EU-Regulations**

No additional information available

#### **National regulations**

No additional information available

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

09/02/2017 ULTRA-LOOK CORP. EN (English US) 6/7

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### **SECTION 16: Other information**

#### Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1	
Carc. 1B	Carcinogenicity Category 1B	
Flam. Liq. 2	Flammable liquids Category 2	
Flam. Liq. 3	Flammable liquids Category 3	
Muta. 1B	Germ cell mutagenicity Category 1B	
H225	Highly flammable liquid and vapor	
H226	Flammable liquid and vapor	
H304	May be fatal if swallowed and enters airways	
H340	May cause genetic defects	
H350	May cause cancer	

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual

injury even if no treatment is given.

: 3 - Liquids and solids that can be ignited under almost all NFPA fire hazard

ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature

conditions. Includes flammable liquids with flash points below 73 F and boiling points above

100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

**Physical** : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

ACGIH: American Conference of Governmental Industrial Hygienists Legend:

NIOSH: National Institute of Occupational Safety and Health

CAS: Chemical Abstract Services CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System N/Ap: not applicable

NFPA: National Fire Protection Association IARC: International Agency for Research on Cancer PEL: Permissible Exposure Limit

N/Av: not available

OSHA: Occupational Safety and Health Administration STEL: Short Term Exposure Limit SARA: Superfund Amendments & Reauthorization Act TSCA: Toxic Substance Control Act

TLV: Threshold Limit Values

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

09/02/2017 ULTRA-LOOK CORP. EN (English US) 7/7