



SAFETY DATA SHEET.

Issuing date 30-Apr-2015

Revision Date 30-Apr-2015

Version 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name AR-4 RUSTEK PLUS 4

Recommended use of the chemical and restrictions on use

Stock No. AR-4

Product Type Extremely flammable aerosol
Synonyms None

Supplier's details

Recommended Use Penetrant.
Uses advised against No information available

Manufacturer:
Crest Industries, Inc.
1337 King Road
Trenton, MI 48183

Emergency telephone number Chemtel (800) 255-3924 International Calls: (813) 248-0585

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

GHS Label elements, including precautionary statements

Emergency Overview

DANGER

Hazard Statements

Causes skin irritation
 May cause respiratory irritation. May cause drowsiness or dizziness
 May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol

Odor Solvent

Precautionary Statements - Prevention

Wash hands thoroughly after handling
 Wear protective gloves
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash before reuse
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor/physician if you feel unwell
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Store in a well-ventilated place
 Do not expose to temperatures exceeding 122°F (50°C)

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

None

Other information

- Toxic to aquatic life with long lasting effects

0.00003% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
NAPHTHENIC OIL, SEVERLY HYDROT	64742-52-5	20-30
KEROSENE	8008-20-6	20-30
HYDROTREATED LIGHT DISTILLATES	64742-47-8	10-20
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	10-20
PETROLEUM DISTILLATES	64742-47-8	10-20
WHITE MINERAL OIL	8042-47-5	1-10

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES**First aid measures for different exposure routes**

General advice	Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.
Eye contact	Rinse immediately with plenty of water and seek medical advice.
Skin contact	Wash off immediately with plenty of water. Get medical attention immediately if symptoms occur.
Inhalation	Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.
Ingestion	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

Most important symptoms/effects, acute and delayed

Main Symptoms Causes skin irritation. May cause eye irritation. Inhalation causing Central Nervous System effects. Ingestion causing lung damage.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**water fog. Dry chemical. Carbon dioxide (CO₂). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Flammable or extremely flammable aerosol. Container may burst in fire.

Explosion Data**Sensitivity to Mechanical Impact** none.**Sensitivity to Static Discharge** Yes.**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use with adequate ventilation to keep the exposure levels below the OELS.

Environmental precautions

Environmental precautions Report spills as required by local and federal regulations.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Contain liquid and collect with an inter,non-combustible material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible products Store away from strong oxidizers and acids.

Aerosol Level 3

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
KEROSENE 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures Skin - potential significant contribution to overall exposure by the cutaneous route	-	TWA: 100 mg/m ³
HYDROTREATED LIGHT DISTILLATES 64742-47-8	TWA: 200 PPM 8 hours	-	-

PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6:TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	74-98-6:IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³ 106-97-8:TWA: 800 ppm TWA: 1900 mg/m ³ 75-28-5:TWA: 800 ppm TWA: 1900 mg/m ³
--	---	--	---

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

Engineering Measures Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Safety glasses with side-shields.
Skin and body protection	Chemical resistant apron. Protective gloves.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Aerosol	Odor	Solvent
Appearance	Clear	Odor Threshold	No information available
Color	Light Amber		
Property	Values	Remarks • Methods	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	No information available		
Flash Point	-96.4 °C / -141 °F	Based on propellant	
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
upper flammability limit	No information available		
lower flammability limit	No information available		
Vapor pressure	No information available		
Vapor density	No information available		
Specific Gravity	0.790		
Water solubility	Practically insoluble		
Partition coefficient: n-octanol/water	No information available		
Autoignition temperature	No information available	Not applicable	
Decomposition temperature	No information available		
Viscosity	No information available		
Explosive properties	No information available		

Other information

VOC Content(%) 48.9

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Store away from strong oxidizers and acids.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known information
Inhalation	Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness.
Eye contact	May cause slight irritation.
Skin contact	Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion	Not acutely toxic. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
KEROSENE 8008-20-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
HYDROTREATED LIGHT DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
PETROLEUM DISTILLATES 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
WHITE MINERAL OIL 8042-47-5	> 5000 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritating to respiratory system. Irritating to skin. May cause irritation to eyes. May be harmful or fatal if ingested.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.
Sensitization No information available.
Germ Cell Mutagenicity No information available.
Carcinogenicity There are no known carcinogenic chemicals in this product.

Reproductive toxicity	The ingredients are not reproductive hazards.
Specific target organ systemic toxicity (single exposure)	May cause respiratory irritation. may cause drowsiness and dizziness.
Specific target organ systemic toxicity (repeated exposure)	No information available.
Chronic toxicity	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis.
Target Organ Effects	Central nervous system, Eyes, Respiratory system, Skin.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.00003% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	920 mg/kg
ATEmix (dermal)	2501 mg/kg
ATEmix (inhalation-vapor)	106 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
NAPHTHENIC OIL, SEVERLY HYDROT 64742-52-5	-	5000 mg/L LC50 Oncorhynchus mykiss 96h	-	1000 mg/L EC50 Daphnia magna 48h
HYDROTREATED LIGHT DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
PETROLEUM DISTILLATES 64742-47-8	-	2.2 mg/L LC50 Lepomis macrochirus 96h static 2.4 mg/L LC50 Oncorhynchus mykiss 96h static 45 mg/L LC50 Pimephales promelas 96h flow-through	-	-
WHITE MINERAL OIL 8042-47-5	-	10000 mg/L LC50 Lepomis macrochirus 96h	-	-

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	log Pow
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	2.8
WHITE MINERAL OIL 8042-47-5	6

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment**Waste Disposal Methods** Dispose of in accordance with federal, state, and local regulations.**Contaminated packaging** Do not re-use empty containers.**14. TRANSPORT INFORMATION****DOT Ground** CONSUMER COMMODITY ORM-D
or
LIMITED QUANTITY**IATA** UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.**IMDG** UN1950, AEROSOLS, 2.1, LTD. QTY.**15. REGULATORY INFORMATION****International Inventories**

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
NAPHTHENIC OIL, SEVERLY HYDROT	X	X	X	X	X	X	X	X
KEROSENE	X	X	X	X	X	X	X	X
HYDROTREATED LIGHT DISTILLATES	X	X	X	X	X	X	X	X
PROPANE/ISOBUTA NE/N-BUTANE	X	X	X	Not listed	X	X	X	X
PETROLEUM DISTILLATES	X	X	X	X	X	X	X	X
WHITE MINERAL OIL	X	X	X	X	X	X	X	X

Legend:**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances**ENCS** - Japan Existing and New Chemical Substances**CHINA** - China Inventory of Existing Chemical Substances**KECL** - Korean Existing and Evaluated Chemical Substances**PICCS** - Philippines Inventory of Chemicals and Chemical Substances**AICS** - Australian Inventory of Chemical Substances**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes

Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

No warning required.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
KEROSENE 8008-20-6	X	X	X

EPA Pesticide Registration Number Not applicable

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<u>HMIS</u>	Health Hazard 2	Flammability 4	Physical Hazard 1	Personal protection B

Revision Date

30-Apr-2015

Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.