



SAFETY DATA SHEET

1. Identification

Product identifier BHCA-85 Urethane Clear Overall Activator - Slow

Other means of identification

Product Code BHCA-85

Recommended use Automotive Refinish Clearcoat Activator

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Crest Industries, Inc.
Address 1337 King Road
Trenton, MI 48183
United States

Telephone (734) 479-4141
Website www.crestauto.com
info@crestauto.com

E-mail

Emergency phone number ChemTel (800) 255-3924 International: (813) 248-0585

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Acute toxicity, oral Category 4
Acute toxicity, dermal Category 4
Acute toxicity, inhalation Category 4
Serious eye damage/eye irritation Category 2A
Sensitization, respiratory Category 1
Sensitization, skin Category 1
Germ cell mutagenicity Category 1B
Carcinogenicity Category 1B

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement

Flammable liquid and vapor. Harmful if swallowed. Harmful in contact with skin. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause genetic defects. May cause cancer. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response

If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Rinse mouth. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

73.92% of the mixture consists of component(s) of unknown acute oral toxicity. 76.71% of the mixture consists of component(s) of unknown acute dermal toxicity. 21.21% of the mixture consists of component(s) of unknown acute inhalation toxicity. 97.85% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 95.22% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
homopolymer of HDI		28182-81-2	50 to <60
1-Methoxy-2-propyl acetate		108-65-6	10 to <20
2-Butoxyethyl acetate		112-07-2	10 to <20
2-Heptanone		110-43-0	5 to <10
1,2,4-Trimethylbenzene		95-63-6	1 to <5
Trimethylbenzene		25551-13-7	1 to <5
Cumene		98-82-8	0.1 to <1
light aromatic solvent naphtha		64742-95-6	0.1 to <1
Other components below reportable levels			1 to <5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
2-Heptanone (CAS 110-43-0)	PEL	465 mg/m3
Cumene (CAS 98-82-8)	PEL	100 ppm 245 mg/m3 50 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	25 ppm
2-Butoxyethyl acetate (CAS 112-07-2)	TWA	20 ppm
2-Heptanone (CAS 110-43-0)	TWA	50 ppm
Cumene (CAS 98-82-8)	TWA	50 ppm
Trimethylbenzene (CAS 25551-13-7)	TWA	25 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1,2,4-Trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3
2-Butoxyethyl acetate (CAS 112-07-2)	TWA	25 ppm 33 mg/m3
2-Heptanone (CAS 110-43-0)	TWA	5 ppm 465 mg/m3
Cumene (CAS 98-82-8)	TWA	100 ppm 245 mg/m3 50 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1-Methoxy-2-propyl acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines**US - California OELs: Skin designation**

1-Methoxy-2-propyl acetate (CAS 108-65-6) Can be absorbed through the skin.
Cumene (CAS 98-82-8) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8) Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Cumene (CAS 98-82-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8) Can be absorbed through the skin.

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA).
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Clear colorless or nearly colorless
Odor	Solvent.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	304.7 °F (151.5 °C) estimated
Flash point	102.0 °F (38.9 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1 % estimated
Flammability limit - upper (%)	7.9 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	3.69 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	645 °F (340.56 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	8.61 lbs/gal
Flammability class	Combustible II estimated
Percent volatile	45 % estimated

Specific gravity	1.04
VOC	3.8 lb/gal Coating 3.8 lb/gal Material 455 g/l Material 455 g/l Coating

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin contact	Harmful in contact with skin. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. May cause an allergic skin reaction.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Acute		
Dermal		
LD50	Rabbit	> 3160 mg/kg
Inhalation		
LC50	Rat	> 2000 ppm, 48 Hours
Oral		
LD50	Rat	6 g/kg
2-Butoxyethyl acetate (CAS 112-07-2)		
Acute		
Dermal		
LD50	Rabbit	1500 mg/kg
Oral		
LD50	Rat	2400 mg/kg
2-Heptanone (CAS 110-43-0)		
Acute		
Dermal		
LD50	Rabbit	12600 mg/kg
Oral		
LD50	Mouse	730 mg/kg
	Rat	1.67 g/kg

Components	Species	Test Results
Cumene (CAS 98-82-8)		
Acute		
Inhalation		
LC50	Mouse	2000 ppm, 7 Hours 24.7 mg/l, 2 Hours
	Rat	8000 ppm, 4 Hours
Oral		
LD50	Rat	1400 mg/kg
Trimethylbenzene (CAS 25551-13-7)		
Acute		
Oral		
LD50	Rat	8970 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	May cause cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
1,2,4-Trimethylbenzene (CAS 95-63-6)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours
2-Heptanone (CAS 110-43-0)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 126 - 137 mg/l, 96 hours
Cumene (CAS 98-82-8)		
Aquatic		
Crustacea	EC50	Brine shrimp (Artemia sp.) 3.55 - 11.29 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss) 2.7 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Heptanone	1.98
Cumene	3.66

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information**DOT**

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242

IATA

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1263
UN proper shipping name	Paint, Paint Related Material
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, <u>S</u> -E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.
DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethyl acetate (CAS 112-07-2) Listed.
Cumene (CAS 98-82-8) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-Butoxyethyl acetate	112-07-2	10 to <20
1,2,4-Trimethylbenzene	95-63-6	1 to <5
Cumene	98-82-8	0.1 to <1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-Butoxyethyl acetate (CAS 112-07-2)

Cumene (CAS 98-82-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-Trimethylbenzene (CAS 95-63-6)
2-Butoxyethyl acetate (CAS 112-07-2)
Cumene (CAS 98-82-8)
light aromatic solvent naphtha (CAS 64742-95-6)
Trimethylbenzene (CAS 25551-13-7)

US. Massachusetts RTK - Substance List

1,2,4-Trimethylbenzene (CAS 95-63-6)
2-Heptanone (CAS 110-43-0)
Cumene (CAS 98-82-8)
Trimethylbenzene (CAS 25551-13-7)

US. New Jersey Worker and Community Right-to-Know Act

1,2,4-Trimethylbenzene (CAS 95-63-6)
2-Butoxyethyl acetate (CAS 112-07-2)
2-Heptanone (CAS 110-43-0)
Cumene (CAS 98-82-8)
Trimethylbenzene (CAS 25551-13-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)
2-Butoxyethyl acetate (CAS 112-07-2)
2-Heptanone (CAS 110-43-0)
Cumene (CAS 98-82-8)
Trimethylbenzene (CAS 25551-13-7)

US. Rhode Island RTK

1,2,4-Trimethylbenzene (CAS 95-63-6)
2-Butoxyethyl acetate (CAS 112-07-2)
Cumene (CAS 98-82-8)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8)

Listed: April 6, 2010

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-20-2015
Version # 01
HMIS® ratings Health: 2*
Flammability: 3
Physical hazard: 0

NFPA ratings

Health: 2
Flammability: 3
Instability: 0

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA BELIEVED TO BE RELIABLE AND THE MANUFACTURER DISCLAIMS ANY LIABILITY INCURRED FROM THE USE OR RELIANCE UPON THE SAME. THE INFORMATION GIVEN IS DESIGNED ONLY AS A GUIDANCE FOR SAFE HANDLING, USE, PROCESSING, STORAGE, TRANSPORTATION, DISPOSAL AND RELEASE AND IS NOT TO BE CONSIDERED A WARRANTY OR QUALITY SPECIFICATION. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This safety information is not a license to use this material as claimed by any patents of third parties. The user alone must finally determine whether a contemplated use of this material will infringe any such patents, and for obtaining any required licenses.