

Page: 1

Revision: 05/12/2014

1. Product and Company Identification

Product Code: CE-CB (H)

Product Name: Code Blue - Hardener

Company Name:Crest Industries, Inc.Phone Number:1337 King Road(734)479-4141

Trenton, MI 48183

Web site address: crestauto.com

Emergency Contact: Chemtel (800)255-3924

International Calls (813)248-0585

Stock Number(s): CE-CB

2. Hazards Identification

Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 4



GHS Signal Word: Warning

GHS Hazard Phrases: H302 - Harmful if swallowed.

H312 - Harmful in contact with skin.

GHS Precaution Phrases: P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

unwell.

P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P330 - Rinse mouth.

P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal

Phrases:

P501 - Dispose of contents/container to an approved treatment/storage/disposal facility

in accordance with local/regional/national and international regulations.

Potential Health Effects (Acute and Chronic):

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name) Concentration			
NA	Mercaptan Terminated Polymer	65.00 - 85.00 %		
65997-17-3	Fibrous glass	5.000 - 10.00 %		
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	5.000 - 15.00 %		
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	1.000 - 5.000 %		



Page: 2

Revision: 05/12/2014

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. Get medical

attention/advice if you feel unwell.

In Case of Skin Contact: In case of contact, immediately wash skin with soap and copious amounts of water.

In Case of Eye Contact: In case of contact, immediately flush eyes with copious amounts of water for at least 15

minutes. In case of contact with eyes, flush with copious amounts of water for at least 15

minutes. Assure adequate flushing by separating the eyelids with fingers. Call a

physician.

In Case of Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician.

5. Fire Fighting Measures

> 93.0 C (199 F) Method Used: Estimate Flash Pt:

UEL: **Explosive Limits:** LEL:

Autoignition Pt:

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or appropriate foam.

As in any fire, wear a self-contained breathing apparatus in pressure-demand, Fire Fighting Instructions:

MSHA/NIOSH (approved or equivalent), and full protective gear. Specific Hazard(s):

Flammable Properties and

Hazards:

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or

Spilled:

Use proper personal protective equipment as indicated in Section 8. Sweep up, place in a bag and hold for waste disposal. Avoid raising dust. Provide ventilation. Do not let

product enter drains.

7. Handling and Storage

Precautions To Be Taken in

Handling:

User Exposure: Do not breathe dust. Avoid contact with eyes, skin, and clothing. Do not

breathe vapor. Use with adequate ventilation.

Precautions To Be Taken in

Store in a cool, dry place.

Storing:

8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	Mercaptan Terminated Polymer			
65997-17-3	Fibrous glass		TLV: 1 f/cc (fibers)	
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol			
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica			

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant

respirator use.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to minimize contact with skin.

Use adequate ventilation to keep airborne concentrations low. **Engineering Controls**



Page: 3

Revision: 05/12/2014

	•						
1	"	0	ntı	lati	n	etc.	١.

Work/Hygienic/Maintenance Wash thoroughly after handling.

Practices:

	9. Physical and Chemical Properties
Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	White.
	sulfurous odor.
pH:	
Melting Point:	
Boiling Point:	- 135 C (275 F)
Flash Pt:	> 93.0 C (199 F) Method Used: Estimate
Evaporation Rate:	
Flammability (solid, gas):	
Explosive Limits:	LEL: UEL:
Vapor Pressure (vs. Air or	
mm Hg):	
Vapor Density (vs. Air = 1):	
Specific Gravity (Water = 1):	
Density:	1.064 G/CM3
Solubility in Water:	
Octanol/Water Partition	
Coefficient:	
Autoignition Pt:	
Decomposition Temperature:	
Viscosity:	
	10. Stability and Reactivity
Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	Incompatible materials, Excess heat.
Incompatibility - Materials To Avoid:	Strong oxidizing agents.
Hazardous Decomposition or	Hazardous decomposition products formed under fire conditions. Hazardous

Decomposition Products: silicon oxides. Carbon monoxide, Carbon dioxide, Nitrogen

Possibility of Hazardous Reactions:

oxides.

Will occur [] Will not occur [X]

Conditions To Avoid -

Byproducts:

Hazardous Reactions:



Page: 4

Revision: 05/12/2014

11. Toxicological Information

Toxicological Information:

CAS#		Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
	NA	Mercaptan Terminated Polymer	n.a.	n.a.	n.a.	n.a.
	65997-17-3	Fibrous glass	n.a.	n.a.	n.a.	n.a.
	90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	n.a.	n.a.	n.a.	n.a.
	67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

13. Disposal Considerations

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified

as a hazardous waste. US EPA guidelines for the classification determination are listed

in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated.

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:

Licensed to Crest Industries, Inc.

UN Number:

Hazard Class: TDG Classification:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Aviation regulated liquid, n.o.s. (Polymercaptan)

UN Number: 3334

Hazard Class: 9 - CLASS 9

15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS#	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
NA	Mercaptan Terminated Polymer	No	No	No
65997-17-3	Fibrous glass	No	No	No
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	No	No	No
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	No	No	No

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard **'Hazard Categories' defined** [X] Yes [] No Chronic (delayed) Health Hazard

for SARA Title III Sections [] Yes [X] No Fire Hazard

311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard

[] Yes [X] No Reactive Hazard

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

NA Mercaptan Terminated Polymer CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA

PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No;

GHS format



90-72-2

67762-90-7

SAFETY DATA SHEET Code Blue - Hardener

Page: 5

Revision: 05/12/2014

PA HSL: No; SC TAP: No; WI Air: No 65997-17-3 Fibrous glass CAA HAP,ODC: No; CWA NPDES: No

2,4,6-Tris(Dimethylaminomethyl)Phenol

Siloxanes and silicones, di-me, reaction products

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS:

No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA

Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No

CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Inventory, 8A, 8A PAIR; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI

Air: No

16. Other Information

Revision Date: 05/12/2014

with silica

Additional Information About

This Product:

Company Policy or

Disclaimer:

The information contained in this SDS is believed to be accurate and reliable as of the date indicated. Crest Industries, Inc. assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.



Page: 1

Revision: 05/12/2014

1. Product and Company Identification

Product Code: CE-CB (R)

Product Name: Code Blue - Resin

Company Name: Crest Industries, Inc. Phone Number: 1337 King Road (734)479-4141

Trenton, MI 48183

Web site address: crestauto.com

Emergency Contact: Chemtel (800)255-3924

International Calls (813)248-0585

Stock Number(s): CE-CB

2. Hazards Identification

Skin Corrosion/Irritation, Category 2 Serious Eye Damage/Eye Irritation, Category 2B Skin Sensitization, Category 1



GHS Signal Word: Warning

GHS Hazard Phrases: H315 - Causes skin irritation.

H320 - Causes eye irritation.

H317 - May cause an allergic skin reaction.

GHS Precaution Phrases: P280 - Wear gloves/protective clothing/eye protection.

P210 - Keep away from open flames. - No smoking. P264 - Wash hands thoroughly after

handling.

P261 - Avoid breathing dust/fume.

P362+364 - Take off contaminated clothing and wash it before reuse.

GHS Response Phrases: P302+352 - IF ON SKIN: Wash with plenty of soap and water.

P332+313 - If skin irritation occurs, get medical advice/attention.

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

 ${\tt P337+313-If\ eye\ irritation\ persists,\ get\ medical\ advice/attention.}$

P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal

P403+235 - Store in cool/well-ventilated place.

Phrases:

P501 - Dispose of contents/container to an approved treatment/storage/disposal facility

in accordance with local/regional/national and international regulations.

Potential Health Effects (Acute and Chronic):

3. Composition/Information on Ingredients

CAS#	Hazardous Components (Chemical Name)	Concentration
25068-38-6	Bisphenol-a based epoxy resin	50.00 - 70.00 %
65997-17-3	Fibrous glass	1.000 - 10.00 %
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	2.000 - 5.000 %
26142-30-3	Epichlorohydrin-polyglycol reaction product	20.00 - 30.00 %
1317-65-3	Limestone	10.00 - 20.00 %



Page: 2

Revision: 05/12/2014

4. First Aid Measures

Emergency and First Aid

Procedures:

In Case of Inhalation: If breathing is difficult, give oxygen. If inhaled, remove to fresh air. Get medical

attention/advice if you feel unwell.

In Case of Skin Contact: In case of contact, immediately wash skin with soap and copious amounts of water.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and

lower eyelids. Get medical aid immediately.

In Case of Ingestion: If swallowed, wash out mouth with water provided person is conscious. Call a physician.

Note to Physician: Treat symptomatically and supportively.

5. Fire Fighting Measures

Flash Pt: > 93.0 C (199 F) Method Used: Estimate

Explosive Limits: LEL: UEL:

Autoignition Pt: NA

Suitable Extinguishing Media: Use foam, dry chemical, or carbon dioxide. Suitable: Water spray.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear.

Flammable Properties and

Hazards:

Spilled:

6. Accidental Release Measures

Steps To Be Taken In Case

Use proper personal protective equipment as indicated in Section 8.

Material Is Released Or

Sweep up, place in a bag and hold for waste disposal. Do not let product enter drains.

Provide ventilation.

7. Handling and Storage

Precautions To Be Taken in

Handling:

Do not ingest or inhale. Avoid contact with eyes, skin, and clothing. Use with adequate

ventilation.

Precautions To Be Taken in

Keep away from sources of ignition. Store in a cool, dry place.

Storing:

8. Exposure Controls/Personal Protection

CAS#	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
25068-38-6	Bisphenol-a based epoxy resin			
65997-17-3	Fibrous glass		TLV: 1 f/cc (fibers)	
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica			
26142-30-3	Epichlorohydrin-polyglycol reaction product			
1317-65-3	Limestone	PEL: 15 (dust); 5 (resp.) ma/m3		



Page: 3

Revision: 05/12/2014

Respiratory Equipment

(Specify Type):

Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant

respirator use.

Eye Protection: Safety glasses.

Protective Gloves: Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls Use adequate ventilation to keep airborne concentrations low.

(Ventilation etc.):

Work/Hygienic/Maintenance Wash thoroughly after handling.

Practices:

9.	Physi	ical and	I Chemical	Pro	perties
----	--------------	----------	------------	-----	---------

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Gray.

sweetish odor.

Melting Point: NA

Boiling Point: 260 C (500 F)

Flash Pt: > 93.0 C (199 F) Method Used: Estimate

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1):

Specific Gravity (Water = 1): 1.062

Density: ~ 1.1 G/CM3

Solubility in Water: Percent Volatile:

Autoignition Pt: NA

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Incompatible materials, Excess heat.

Instability:

Incompatibility - Materials To Strong oxidizing agents.

Avoid:

Hazardous Decomposition or Carbon monoxide, Hazardous decomposition products formed under fire conditions.

Byproducts:

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - Hazardous Reactions:



Page: 4

Revision: 05/12/2014

11. Toxicological Information

Toxicological Information:

Carcinogenicity/Other CAS# 2238-07-5: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Information:

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
25068-38-6	Bisphenol-a based epoxy resin	n.a.	n.a.	n.a.	n.a.
65997-17-3	Fibrous glass	n.a.	n.a.	n.a.	n.a.
67762-90-7	Siloxanes and silicones, di-me, reaction products with silica	n.a.	n.a.	n.a.	n.a.
26142-30-3	Epichlorohydrin-polyglycol reaction product	n.a.	n.a.	n.a.	n.a.
1317-65-3	Limestone	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

13. Disposal Considerations

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified

as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local

hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed. RCRA U-Series: None listed.

Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated.

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name:

UN Number:

Hazard Class: TDG Classification:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Environmentally hazardous substances, liquid, n.o.s. (Bisphenol A Epoxy Resin)

UN Number: 3082 Packing Group:

Hazard Class: 9 - CLASS 9

IMDG MFAG Number:

IMDG EMS Page:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Environmentally hazardous substances, liquid, n.o.s. (Bisphenol A Epoxy Resin)

UN Number: 3082 Packing Group:

Hazard Class: 9 - CLASS 9



Page: 5

Revision: 05/12/2014

15. Regulatory Information

			<u> </u>			
EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists						
CAS#	Hazardous Components (Chemical Name)		S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)	
25068-38-6	Bisphenol-a based epo	xy resin		No	No	No
65997-17-3	Fibrous glass			No	No	No
67762-90-7	Siloxanes and silicones with silica	s, di-me, react	tion products	No	No	No
26142-30-3	Epichlorohydrin-polygly	col reaction p	product	No	No	No
1317-65-3	Limestone			No	No	No
'Hazard Categories' defined [X] Yes [] No Chronic (delator SARA Title III Sections [X] Yes [] No Fire Hazard		diate) Health Haza ayed) Health Haza ease of Pressure H zard	rd			
CAS#	Hazardous Componer	nts (Chemica	ıl Name)	Other US EPA or S	tate Lists	
25068-38-6 65997-17-3			CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -			
67762-90-7	·		Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8A, 8A PAIR; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No			
26142-30-3	26142-30-3 Epichlorohydrin-polyglycol reaction product		CAA HAP,ODC: No Inventory; CA PRO Oil/HazMat: No; M No; NY Part 597: N	No; PA HSL: No; SC	Title 8: No; MA C TAP: No; NJ EHS: TAP: No; WI Air: No	
1317-65-3 Limestone		CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 4001; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No;				

WI Air: No



Page: 6

Revision: 05/12/2014

16. Other Information

Revision Date: 05/12/2014

Additional Information About

This Product:

Company Policy or

Disclaimer:

The information contained in this SDS is believed to be accurate and reliable as of the date indicated. Crest Industries, Inc. assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.