

....

Page: 1

Revision: 01/29/2015

1. Product and Company Identification				
Product Code:	CU-P			
Product Name:	Ure-Seam Plus			
Trade Name:	de Name: Urethane Seam Sealer			
Company Name:	Crest Industries, Inc. 1337 King Road Trenton, MI 48183	Phone Number: (734)479-4141		
Web site address:	crestauto.com			
Emergency Contact:	Chemtel International Calls	(800)255-3924 (813)248-0585		
Stock Number(s):	CU-P			

2. Hazards Identification

Skin Sensitization, Category 1 Skin Corrosion/Irritation, Category 2 Serious Eye Damage/Eye Irritation, Category 2A Respiratory Sensitization, Category 1 Carcinogenicity, Category 2 Specific Target Organ Toxicity (single exposure), Category 1 Specific Target Organ Toxicity (repeated exposure), Category 1



GHS Signal Word:	Danger
GHS Hazard Phrases:	H315 - Causes skin irritation.
	H317 - May cause an allergic skin reaction.
	H319 - Causes serious eye irritation.
	H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H351 - Suspected of causing cancer.
	H370 - Causes damage to organs Sensory organs
	H372 - Causes damage to organs Nervous system through prolonged or repeated
	exposure.
GHS Precaution Phrases:	P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P260 - Do not breathe vapours.
	P264 - Wash hands thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P280 - Wear protective gloves/eye protectin/face protection.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection. P285 -
	In case of inadequate ventilation wear respiratory protection.
GHS Response Phrases:	P302+352 - IF ON SKIN: Wash with plenty of soap and water.
•	P333+313 - If skin irritation or rash occurs, get medical advice/attention.
	P362 - Take off contaminated clothing and wash before re-use.
	P304 - IF INHALED: P341 - If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.
	P342+311 - If experiencing respiratory symptoms call a POISON CENTER or
	doctor/physician.
	P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.



P337+313 - If eye irritation persists, get medical advice/attention.P308+313 - IF exposed or concerned: Get medical attention/advice.P405 - Store locked up.

GHS Storage and Disposal Phrases:

P405 - Store locked up. P501 - Dispose of contents/container to an approved treatment/storage/disposal facility in accordance with local/regional/national and international regulations.

Potential Health Effects (Acute and Chronic):

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
NA	Urethane Polymer	20.00 - 35.00 %
1333-86-4	Carbon black	<0.300 %
NA	Plasticizer Mixture	10.00 - 30.00 %
9002-86-2	Poly(vinyl chloride)	25.00 - 35.00 %
1330-20-7	Xylene (mixed isomers)	<6.000 %
101-68-8	Methylenebis(phenylisocyanate)	<0.200 %
1305-78-8	Calcium oxide	1.000 - 5.000 %
13463-67-7	Titanium dioxide	<3.000 %
100-41-4	Ethylbenzene	<2.000 %
64742-47-8	Hydrotreated light distillate (petroleum)	<2.000 %

	4. First Aid Measures		
Emergency and First Aid Procedures:			
In Case of Inhalation:	If breathed in, move person into fresh air. Consult a physician.		
In Case of Skin Contact:	Get medical aid if irritation develops or persists. Wash off with soap and plenty of water.		
In Case of Eye Contact:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.		
In Case of Ingestion:	Never give anything by mouth to an unconscious person. Get medical aid. Rinse mouth with water.		
Note to Physician:	Treat symptomatically and supportively.		
	5. Fire Fighting Measures		
Flash Pt:	>= 61.0 C (142 F) Method Used: Closed Cup		
Explosive Limits:	LEL: .6 UEL: 8		
Autoignition Pt:	NP		
Suitable Extinguishing Medi	a:Use water spray, dry chemical, carbon dioxide, or appropriate foam.		
Fire Fighting Instructions:	As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.		
Flammable Properties and			



Revision: 01/29/2015

6. Accidental Release Measures
Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of
ignition. Evacuate personnel to safe areas. Use proper personal protective equipment as
indicated in Section 8.
Do not let product enter drains.
Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container.
Avoid generating dusty conditions. Remove all sources of ignition.

7. Handling and Storage

Precautions To Be Taken in	For Industrial Use Only. Use with adequate ventilation. Avoid contact with eyes, skin,
Handling:	and clothing. Do not breathe dust, mist, or vapor. Do not eat, drink or smoke when using
-	this product. Wash thoroughly after handling. Wash clothing before reuse.
Precautions To Be Taken in	Keep container tightly closed in a dry and well-ventilated place.

Storing:

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
NA	Urethane Polymer			
1333-86-4	Carbon black	PEL: 3.5 mg/m3	TLV: 3.5 mg/m3	
NA	Plasticizer Mixture			
9002-86-2	Poly(vinyl chloride)			
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm	
101-68-8	Methylenebis(phenylisocyanate)	CEIL: 0.02 ppm	TLV: 0.005 ppm	
1305-78-8	Calcium oxide	PEL: 5 mg/m3	TLV: 2 mg/m3	
13463-67-7	Titanium dioxide	PEL: 15 (dust) mg/m3	TLV: 10 mg/m3	
100-41-4	Ethylbenzene	PEL: 100 ppm	TLV: 20 ppm STEL: 125 ppm	

TLV: 200 mg/m3

64742-47-8 Hydrotreated light distillate (petroleum)

Respiratory Equipment (Specify Type):	Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Eye Protection:	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Protective Gloves:	Wear appropriate gloves to prevent skin exposure. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.
Other Protective Clothing:	Wear appropriate protective clothing to minimize contact with skin.
Engineering Controls (Ventilation etc.):	Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.
Work/Hygienic/Maintenance Practices:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Environmental Exposure Controls:	Do not let product enter drains. Discharge into the environment must be avoided.



Page: 4

Revision: 01/29/2015

	9. Physical and Chemical Properties				
Physical States:	[]Gas []Liquid [X]Solid				
Appearance and Odor:	Black. Paste.				
	weak odor.				
Melting Point:	NA				
Boiling Point:	~ 110 C (230 F)				
Flash Pt:	>= 61.0 C (142 F) Method Used: Closed Cup				
Evaporation Rate:					
Flammability (solid, gas):					
Explosive Limits:	LEL: .6 UEL: 8				
Vapor Pressure (vs. Air or					
mm Hg):					
Vapor Density (vs. Air = 1):					
Specific Gravity (Water = 1):					
Density:	~ 1.2 G/CC				
Solubility in Water:					
Percent Volatile:					
VOC / Volume:	23.0 G/L				
Autoignition Pt:	NP				
	10. Stability and Reactivity				
Stability:	Unstable [] Stable [X]				
Conditions To Avoid - Instability:	Incompatible materials, ignition sources, Moisture, Heat.				
Incompatibility - Materials To Avoid:	oils, and moisture. Strong oxidizing agents. Water. Alcohols, Amines.				
Hazardous Decomposition of Byproducts:	r Carbon monoxide.				
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]				
Conditions To Avoid - Hazardous Reactions:					



11. Toxicological Information

Toxicologica	al Information:						
Sensitizatio	n: No data	No data available.					
Carcinogeni	city/Other CAS# 1	333-86-4: ACGIH: Not li	sted.				
Information:		California: carcinogen, initial date 2/21/03 (airborne, unbound particles of respirable size. NTP: Not listed. No data available. IARC: 3 -Group 3: Not classifiable as to its carcinogenicity to humans. NTP: No component of this product present at levels greater than or equal to 3 is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present					
		at levels greater than or equal to 0.1% is identified as a carcinogen or potential					
		gen by OSHA.					
CAS #	Hazardous Components	NTP	IARC	ACGIH	OSHA		
NA	Urethane Polymer	n.a.	n.a.	n.a.	n.a.		
1333-86-4	Carbon black		n.a.	2B	A4	n.a.	
NA	Plasticizer Mixture	Plasticizer Mixture		n.a.	n.a.	n.a.	
9002-86-2	Poly(vinyl chloride)	n.a.	3	n.a.	n.a.		
1330-20-7	Xylene (mixed isomers)		n.a.	3	A4	n.a.	
101-68-8	Methylenebis(phenylisocya	inate)	n.a.	3	n.a.	n.a.	
	Calcium oxide				n 0	n.a.	
1305-78-8	Calcium oxide		n.a.	n.a.	n.a.	n.a.	
1305-78-8 13463-67-7	Calcium oxide Titanium dioxide		n.a. n.a.	n.a. 2B	A4	n.a.	

12. Ecological Information

13. Disposal Considerations

Waste Disposal Method:Chemical waste generators must determine whether a discarded chemical is classified
as a hazardous waste. US EPA guidelines for the classification determination are listed
in 40 CFR Parts 261. Additionally, waste generators must consult state and local
hazardous waste regulations to ensure complete and accurate classification.
RCRA P-Series: None listed.
RCRA U-Series: None listed.
Contact a licensed professional waste disposal service to dispose of this material.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name DOT Hazard Class: UN/NA Number: LAND TRANSPORT (Canadian		Packing Group:	II
TDG Shipping Name: UN Number: Hazard Class:	Not Regulated.	Packing Group: TDG Classification:	II



Page: 6

	15. Regulatory Information					
EPA SARA (S	uperfund Amendn	nents and Reauth	orization Act of	of 1986) Lists		
CAS #		ponents (Chemic	al Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
NA	Urethane Polyme	er		No	No	No
1333-86-4	Carbon black			No	No	No
NA	Plasticizer Mixtur			No	No	No
9002-86-2	Poly(vinyl chlorid	,		No	No	No
1330-20-7	Xylene (mixed is	omers)		No	Yes 100 LB	Yes
101-68-8	Methylenebis(ph	enylisocyanate)		No	Yes 5000 LB	Yes-Cat. N120
1305-78-8	Calcium oxide			No	No	No
13463-67-7	Titanium dioxide			No	No	No
100-41-4	Ethylbenzene			No	Yes 1000 LB	Yes
64742-47-8	Hydrotreated ligh	nt distillate (petrole	um)	No	No	No
'Hazard Cate for SARA Tit	Hazard Categories' defined[X] Yes] NoChronic (deFor SARA Title III Sections[X] Yes] NoFire Hazard311/312 as indicated:[] Yes[X] NoSudden Rel			lease of Pressure Hazard		
		[X] Yes [] No				
CAS #		ponents (Chemic	al Name)	Other US EPA or		
NA 1333-86-4			CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -			
	1333-86-4 Carbon black			Inventory; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 0342; NY Part 597: No; PA HSL: Yes - 1; SC TAP: No; WI Air: Yes		
NA	Plasticizer Mixture		CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No			
9002-86-2 Poly(vinyl chloride)		CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: Yes - 3622; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No				
1330-20-7	Y Xylene (mixed isomers)		CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP: Yes; NJ EHS: Yes - 2014; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes		C, Title 8: TAC, Title 8; 5: CMR, Part 5; NC TAP:	
101-68-8	Methylenebis(ph	enylisocyanate)		CAA HAP,ODC: I Inventory, 8C; Ca 8; MA Oil/HazMa	HAP; CWA NPDES A PROP.65: No; CA It: No; MI CMR, Par 253; NY Part 597: Y	: No; TSCA: Yes - A TAC, Title 8: TAC, Title t 5: Part 5; NC TAP: Yes; es; PA HSL: Yes - E; SC
1305-78-8	Calcium oxide			Inventory; CA PF		No; TSCA: Yes - C, Title 8: Title 8; MA ; NC TAP: No; NJ EHS:

EREST °	SAFETY DATA SHEET		Page: 7
	L	Ure-Seam Plus Revision: 01/29/20	
13463-67-7	Titanium dioxide	Yes - 0325; NY Part 597: No; PA HSL: Yes WI Air: Yes CAA HAP,ODC: No; CWA NPDES: No; TS	
		Inventory; CA PROP.65: Yes; CA TAC, Titl Oil/HazMat: No; MI CMR, Part 5: No; NC T Yes - 1861; NY Part 597: No; PA HSL: Yes WI Air: No	le 8: No; MA AP: No; NJ EHS:
100-41-4	Ethylbenzene	CAA HAP,ODC: HAP; CWA NPDES: Yes; Inventory, 4 Test; CA PROP.65: Yes; CA T Title 8; MA Oil/HazMat: Yes; MI CMR, Part Yes; NJ EHS: Yes - 0851; NY Part 597: Ye E; SC TAP: Yes; WI Air: Yes	AC, Title 8: TAC, 5: Part 5; NC TAP:
64742-47-8	Hydrotreated light distillate (petroleum)	CAA HAP,ODC: No; CWA NPDES: No; TS Inventory; CA PROP.65: No; CA TAC, Title Oil/HazMat: No; MI CMR, Part 5: No; NC T No; NY Part 597: No; PA HSL: No; SC TA	e 8: No; MA AP: No; NJ EHS:

16. Other Information			
Revision Date:	01/29/2015		
Additional Information About This Product:			
Company Policy or Disclaimer:	The information contained in this SDS is believed to be accurate and reliable as of the date indicated. Crest Industries, Inc. assumes no legal responsibility and makes no representation, warranty or guarantee, expressed or implied, as to the completeness or accuracy of the information. It is offered solely for your consideration, investigation and verification. The user is ultimately responsible for the safe use of the material in accordance with applicable federal, state, provincial and local laws and regulations.		