

Printing date 05/20/2014 Reviewed on 04/28/2014

1 Identification

· Product identifier

· Trade name: 5010 2K RAPID CLEAR

· Article number: 5010

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

· Information department: Product safety department

· Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Irritant

Irritating to eyes.



Highly flammable

Highly flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:





Irritant Highly flammable

· Risk phrases:

Highly flammable.

Irritating to eyes.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Keep container in a well-ventilated place.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

(Contd. on page 2)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

(Contd. of page 1)

If swallowed, seek medical advice immediately and show this container or label.

· Special labeling of certain preparations:

Contains neodecansäureglycidylester, methyl methacrylate, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene); a-3-(3-(2h-benzotriazol-2-yl)-5-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene). May produce an allergic reaction.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	· Dangerous components:		
123-86-4	n-butyl acetate	10-25%	
67-64-1	acetone	10-25%	
110-43-0	heptan-2-one	10-25%	
80-62-6	methyl methacrylate	½ 2.5%	
	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	½ 2.5%	
4008-30-7	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-benzotriazol-2-yl)-5-butyl-4-hydroxyphenyl)propionyl-o-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)	½ 2.5%	
26761-45-5	neodecansäureglycidylester	½ 2.5%	

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

(Contd. of page 2)

 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · Specific end use(s) No further relevant information available.

USA ·



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

- PEL () Long-term value: 710 mg/m³, 150 ppm
- REL () Short-term value: 950 mg/m³, 200 ppm
 - Long-term value: 710 mg/m³, 150 ppm
- TLV () Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm

67-64-1 acetone

- PEL () Long-term value: 2400 mg/m³, 1000 ppm
- REL () Long-term value: 590 mg/m³, 250 ppm
- TLV () Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm BEI

110-43-0 heptan-2-one

- PEL () Long-term value: 465 mg/m³, 100 ppm
- REL () Long-term value: 465 mg/m³, 100 ppm
- TLV () Long-term value: 233 mg/m³, 50 ppm
- · Ingredients with biological limit values:

67-64-1 acetone

BEI () 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Use suitable respiratory protective device in case of insufficient ventilation.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical prope	erties	
· Information on basic physical and chemical properties		
· General Information		
· Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	55 °C (131 °F)	
· Flash point:	-5 °C (23 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	370 °C (698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
· Explosion limits:		
Lower:	1.0 Vol %	
Upper:	13.0 Vol %	
· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)	
· Density at 20 °C (68 °F):	0.93903 g/cm³ (7.836 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
Evaporation rate	Not determined.	

(Contd. on page 6)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

		(Contd. of page s
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	62.2 %	
VOC content:	39.0 %	
	505.8 g/l / 4.22 lb/gl	
Solids content:	36.7 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
110-43-	0 hept	an-2-one
Oral	LD50	1670 mg/kg (rat)
Dermal	LD50	12600 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
80-62-6	methyl methacrylate	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 7)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

· **DOT** Paint
· **ADR** 1263 Paint
· **IMDG, IATA** PAINT

(Contd. on page 8)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

(Contd. of page 7)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids.

· Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA //

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler): 33EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 methyl methacrylate

100-41-4 ethylbenzene

1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

123-86-4 n-butyl acetate

67-64-1 acetone

110-43-0 heptan-2-one

80-62-6 methyl methacrylate

41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

65-85-0 Benzoic acid

26761-45-5 neodecansäureglycidylester

64742-95-6 Solvent naphtha (petroleum), light arom.

(Contd. on page 9)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

	(Contd. of page 8)
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate
	n-butyl methacrylate
	2-hydroxyethyl methacrylate
79-41-4	methacrylic acid
78-83-1	butanol
	dibutyltin dilaurate
556-67-2	octamethylcyclotetrasiloxane

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)			
	67-64-1	acetone	I
		methyl methacrylate	E, NL
	65-85-0	Benzoic acid	D
	1330-20-7		1
	100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)			
67-64-1	acetone	A4	
	methyl methacrylate	A4	
	dibutyltin dilaurate	A4	
1330-20-7	xylene	A4	
100-41-4	ethylbenzene	A3	

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:





Irritant Highly flammable

· Risk phrases:

Highly flammable. Irritating to eyes.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 10)



Printing date 05/20/2014 Reviewed on 04/28/2014

Trade name: 5010 2K RAPID CLEAR

(Contd. of page 9)

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Keep container in a well-ventilated place.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

If swallowed, seek medical advice immediately and show this container or label.

· Special labeling of certain preparations:

Contains neodecansäureglycidylester, methyl methacrylate, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene); a-3-(3-(2h-benzotriazol-2-yl)-5-butyl-4-hydroxyphenyl)propionyl-o-3-(3-(2h-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene). May produce an allergic reaction.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- · Contact: Ms. Topaljikian

USA