

Printing date 03/12/2015

Safety Data Sheet acc. to OSHA HCS

Page 1/11

Reviewed on 03/12/2015

| 1 Identification | |
|---|--------------------|
| · Product identifier | |
| · Trade name: <u>AD263 FISHEYE ELIMINATOR</u> | |
| Details of the supplier of the safety data sheet Manufacturer/Supplier: Lusid Technologies 5195 West 4700 South KEARNS, UT 84118 USA | |
| • Information department: Product safety department • Emergency telephone number: 1-800-535-5053 | |
| 2 Hazard(s) identification | |
| · Classification of the substance or mixture | |
| GHS02 Flame | |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor. | |
| GHS08 Health hazard | |
| Carc. 2 H351 Suspected of causing cancer. | |
| GHS07 | |
| Skin Irrit. 2 H315 Causes skin irritation. | |
| · Classification according to Directive 67/548/EEC or Directive 1999/45/EC | |
| Harmful | |
| Harmful by inhalation and in contact with skin. | |
| Irritant | |
| Irritating to skin. | |
| Highly flammable | |
| Highly flammable. Information concerning particular hazards for human and environment: The product has to be labeled due to the calculation procedure of international guidelines. Classification system: | |
| The classification was made according to the latest editions of international substances lists, | and expanded upon |
| from company and literature data. | (Contd. on page 2) |



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

· Label elements

• *Labelling according to EU guidelines: The product has been classified and marked in accordance with directives on hazardous materials.*

· Code letter and hazard designation of product:



Harmful Highly flammable

- Hazard-determining components of labeling: xylene
- **Risk phrases:** Highly flammable. Harmful by inhalation and in contact with skin. Irritating to skin.
- · Safety phrases:

Keep out of the reach of children. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE3Fire = 3REACTIVITY0Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

540-88-5 tert-butyl acetate

25-50% (Contd. on page 3)

USA



(Contd. of page 1)



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

| | (Con | td. of page 2) |
|-----------|------------------|----------------|
| 1330-20-7 | xylene | 25-50% |
| 122-99-6 | 2-Phenoxyethanol | 2.5-10% |
| 100-41-4 | ethylbenzene | 2.5-10% |

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

| · Personal precautions, protective equipment and emergency procedures |
|--|
| Wear protective equipment. Keep unprotected persons away. |
| · Environmental precautions: |
| Do not allow product to reach sewage system or any water course. |
| Inform respective authorities in case of seepage into water course or sewage system. |
| Do not allow to enter sewers/ surface or ground water. |
| • Methods and material for containment and cleaning up: |
| Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). |
| Dispose contaminated material as waste according to item 13. |
| Ensure adequate ventilation. |
| Do not flush with water or aqueous cleansing agents |
| |

(Contd. on page 4)

USA

Page 3/11

Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

| 540-8 | 28-5 tert-butyl acetate | |
|-------|--|-------------------|
| PEL | Long-term value: 950 mg/m³, 200 ppm | |
| REL | Long-term value: 950 mg/m³, 200 ppm | |
| TLV | Long-term value: 950 mg/m³, 200 ppm | |
| 1330- | 20-7 xylene | |
| PEL | Long-term value: 435 mg/m³, 100 ppm | |
| | Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm | |
| | Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI | |
| | | (Contd. on page 3 |



Page 4/11

(Contd. of page 3)



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

| | (Contd. of page 4 |
|-------|---|
| 100-4 | 11-4 ethylbenzene |
| PEL | Long-term value: 435 mg/m ³ , 100 ppm |
| | Short-term value: 545 mg/m³, 125 ppm |
| | Long-term value: 435 mg/m ³ , 100 ppm |
| TLV | Long-term value: 87 mg/m³, 20 ppm |
| | BEI |
| | dients with biological limit values: |
| | -20-7 xylene |
| BEI | 1.5 g/g creatinine |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: Methylhippuric acids |
| | 11-4 ethylbenzene |
| | 0.7 g/g creatinine |
| | Medium: urine |
| | Time: end of shift at end of workweek |
| | Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
| | Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative) |
| Addit | tional information: The lists that were valid during the creation were used as basis. |
| Exdo | sure controls |
| | onal protective equipment: |
| | ral protective and hygienic measures: |
| | away from foodstuffs, beverages and feed. |
| | diately remove all soiled and contaminated clothing. |
| Wash | hands before breaks and at the end of work. |
| Avoia | l contact with the skin. |
| Avoia | l contact with the eyes and skin. |
| | thing equipment: |
| | se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure us |
| | ratory protective device that is independent of circulating air. |
| Prote | ction of hands: |
| ſſ | |
| 1112 | |
| | Protective gloves |
| | Protective gloves |
| The | |
| | love material has to be impermeable and resistant to the product/ the substance/ the preparation. |
| Due t | |

Page 5/11



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

| · Appearance: | |
|-------------------------------------|---|
| Form: | Liquid |
| Color: | Clear |
| · Odor: | Characteristic |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 97 °C (207 °F) |
| · Flash point: | 15 °C (59 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 430 °C (806 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapo mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 7.0 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 41 hPa (31 mm Hg) |
| • Density at 20 °C (68 °F): | 0.89 g/cm ³ (7.427 lbs/gal) |
| · Relative density | Not determined. |

Page 6/11

(Contd. of page 5)



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

| | | (Contd. of page |
|------------------------------------|--|-----------------|
| · Vapour density | Not determined. | |
| · Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| Water: | Not miscible or difficult to mix. | |
| · Partition coefficient (n-octan | ol/water): Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| · Solvent content: | | |
| Organic solvents: | 92.8 % | |
| VOC content: | 44.7 % | |
| | Coating VOC 817.4 g/l / 6.82 lb/gl | |
| | Material VOC 409.6 g/l 3.41 lb/gl | |
| Solids content: | 7.2 % | |
| • Other information | No further relevant information available. | |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

(Contd. on page 8)

Page 7/11



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

| Transport information | | |
|----------------------------------|--------|-------------------|
| · UN-Number · DOT, IMDG, IATA | UN1263 | |
| • <i>D01, IMD</i> 0, IATA | 011205 | (Contd. on page 9 |

(Contd. of page 7)

3

2B

Page 8/11



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

| TTAT | (Contd. of pa |
|--|---|
| · UN proper shipping name · DOT · IMDG, IATA | Paint PAINT |
| · Transport hazard class(es) | |
| DOT | |
| RAMABLE LOUD | |
| · Class · Label | 3 Flammable liquids 3 |
| · IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group · DOT, IMDG, IATA | Ш |
| · Environmental hazards: · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| Danger code (Kemler): | 33 |
| · EMS Number: | <i>F-E,<u>S-E</u></i> |
| • Transport in bulk according to Annex MARPOL73/78 and the IBC Code | II of Not applicable. |
| | |
| Transport/Additional information: | |
| • DOT • Quantity limitations | On passenger aircraft/rail: 5 L |
| Quantity tillitations | On cargo aircraft only: 60 L |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| \cdot Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| UN "Model Regulation": | UN1263, Paint, 3, II |

(Contd. on page 10)

Page 9/11



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

(Contd. of page 9)

Page 10/11

| · Safety, health and environmental regulations/legislation specific for the substance of · Sara | or mixture |
|---|--|
| Sura Section 355 (extremely hazardous substances): | |
| None of the ingredients is listed. | |
| Section 313 (Specific toxic chemical listings): | |
| 1330-20-7 xylene | |
| 100-41-4 ethylbenzene | |
| · TSCA (Toxic Substances Control Act): | |
| All ingredients are listed. | |
| Proposition 65 | |
| Chemicals known to cause cancer: | |
| 100-41-4 ethylbenzene | |
| Chemicals known to cause reproductive toxicity for females: | |
| None of the ingredients is listed. | |
| Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| Chemicals known to cause developmental toxicity: | |
| None of the ingredients is listed. | |
| Carcinogenic categories | |
| EPA (Environmental Protection Agency) | |
| 1330-20-7 xylene | |
| 100-41-4 ethylbenzene | |
| TLV (Threshold Limit Value established by ACGIH) | ······································ |
| 1330-20-7 xylene | A |
| 100-41-4 ethylbenzene | ŀ |
| NIOSH-Ca (National Institute for Occupational Safety and Health) | |

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:



Harmful Highly flammable

(Contd. on page 11)



Printing date 03/12/2015

Reviewed on 03/12/2015

Trade name: AD263 FISHEYE ELIMINATOR

(Contd. of page 10)

• *Hazard-determining components of labeling: xylene*

• **Risk phrases:** Highly flammable. Harmful by inhalation and in contact with skin. Irritating to skin.

• Safety phrases:

Keep out of the reach of children.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Wear suitable protective clothing and gloves.
If swallowed, seek medical advice immediately and show this container or label.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Roberts
- · Date of preparation / last revision 03/12/2015 / -
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Carc. 2: Carcinogenicity, Hazard Category 2