

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

1 Identification

- **Product identifier**
- **Trade name: EP210 DARK GRAY EPOXY PRIMER**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
5195 West 4700 South
KEARNS, UT 84118
USA
- **Information department: Product safety department**
- **Emergency telephone number: 1-800-535-5053**

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Warning
- **Hazard-determining components of labeling:**
Talc (Mg₃H₂(SiO₃)₄)
titanium dioxide
Carbon black

(Contd. on page 2)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 1)

· **Hazard statements**

Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Keep container tightly closed.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO₂, powder or water spray.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

14807-96-6	Talc (Mg3H2(SiO3)4)	25-50%
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%
68410-23-1	Liquid Polyamide Resin	10-25%
13463-67-7	titanium dioxide	10-25%
110-43-0	heptan-2-one	2.5-10%
7779-90-0	trizinc bis(orthophosphate)	≤ 2.5%
67-64-1	acetone	≤ 2.5%
1333-86-4	Carbon black	≤ 2.5%
100-41-4	ethylbenzene	≤ 2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm
BEI

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

REL Long-term value: 3.5* mg/m³
*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³
*inhalable fraction

· **Ingredients with biological limit values:**

67-64-1 acetone

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Dark grey
· Odor:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	139 °C (282 °F)

· **Flash point:** 41 °C (106 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 533 °C (991 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 6)

· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.45 g/cm ³ (12.1 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	9.9 %
VOC content:	9.9 %
	Coating VOC 225.0 g/l / 1.87 lb/gl
	Material VOC 154.0 g/l 1.28 lb/gl
· Solids content:	62.7 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
68410-23-1 Liquid Polyamide Resin		
Oral	LD50	2000 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
7779-90-0 trizinc bis(orthophosphate)		
Oral	LD50	>5000 mg/kg (rat)

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 7)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
14807-96-6	Talc (Mg3H2(SiO3)4)	2B
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
108-38-3	m-xylene	3
100-41-4	ethylbenzene	2B
106-42-3	p-xylene	3
95-47-6	o-xylene	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER



(Contd. of page 8)

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, IMDG, IATA** III
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Flammable liquids
- **Danger code (Kemler):** 30

(Contd. on page 10)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 9)

· EMS Number:	<i>F-E,S-E</i>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	<i>Not applicable.</i>
· Transport/Additional information:	
· DOT	
· Quantity limitations	<i>On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L</i>
· IMDG	
· Limited quantities (LQ)	<i>5L</i>
· Excepted quantities (EQ)	<i>Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</i>
· UN "Model Regulation":	<i>UN1263, Paint, 3, III</i>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

7779-90-0	<i>trizinc bis(orthophosphate)</i>
108-38-3	<i>m-xylene</i>
100-41-4	<i>ethylbenzene</i>
106-42-3	<i>p-xylene</i>
95-47-6	<i>o-xylene</i>

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7	<i>titanium dioxide</i>
1333-86-4	<i>Carbon black</i>
100-41-4	<i>ethylbenzene</i>

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 10)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

7779-90-0	trizinc bis(orthophosphate)	D, I, II
67-64-1	acetone	I
108-38-3	m-xylene	I
100-41-4	ethylbenzene	D
106-42-3	p-xylene	I
95-47-6	o-xylene	I

· TLV (Threshold Limit Value established by ACGIH)

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
13463-67-7	titanium dioxide	A4
67-64-1	acetone	A4
1333-86-4	Carbon black	A4
108-38-3	m-xylene	A4
100-41-4	ethylbenzene	A3
106-42-3	p-xylene	A4
95-47-6	o-xylene	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
1333-86-4	Carbon black

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

Talc (Mg₃H₂(SiO₃)₄)

titanium dioxide

Carbon black

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

(Contd. on page 12)



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

(Contd. of page 11)

· Precautionary statements

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - Wear protective gloves / eye protection / face protection.
 - Wear protective gloves.
 - Wear eye protection / face protection.
 - Ground/bond container and receiving equipment.
 - Keep container tightly closed.
 - Use only non-sparking tools.
 - Take precautionary measures against static discharge.
 - Wash thoroughly after handling.
 - Obtain special instructions before use.
 - Do not handle until all safety precautions have been read and understood.
 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - Specific treatment (see on this label).
 - IF exposed or concerned: Get medical advice/attention.
 - If skin irritation occurs: Get medical advice/attention.
 - If eye irritation persists: Get medical advice/attention.
 - In case of fire: Use for extinction: CO₂, powder or water spray.
 - Take off contaminated clothing and wash it before reuse.
 - Store locked up.
 - Store in a well-ventilated place. Keep cool.
 - Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** Mr. Roberts
- **Date of preparation / last revision** 06/11/2015 / -
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - Flam. Liq. 3: Flammable liquids, Hazard Category 3
 - Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

(Contd. on page 13)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2015

Reviewed on 03/17/2015

Trade name: EP210 DARK GRAY EPOXY PRIMER

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Carc. 2: Carcinogenicity, Hazard Category 2

(Contd. of page 12)