



Printing date 03/02/2015 Reviewed on 03/02/2015

1 Identification

- · Product identifier
- · Trade name: GH1 FAST ACTIVATOR
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Lusid Technologies 5195 West 4700 South KEARNS, UT 84118 USA
- · Information department: Product safety department
- · Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



X Harmful

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Irritan

Irritating to eyes and skin. May cause sensitisation by inhalation and skin contact.



Highly flammable

(Contd. on page 2)





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 1)

Highly flammable.

Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:





Harmful Highly flammable

· Hazard-determining components of labeling:

poly(hexamethylene diisocyanate) toluene

· Risk phrases:

Highly flammable.

Irritating to eyes and skin.

May cause sensitisation by inhalation and skin contact.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

Avoid contact with skin and eyes.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

In case of accident by inhalation: remove casualty to fresh air and keep at rest.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

(Contd. on page 3)





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

ſ	· Dangerous o	onents:	
	28182-81-2	poly(hexamethylene diisocyanate)	50-100%
	108-88-3	toluene	25-50%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



Page 4/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

REI

· Ingredients with biological limit values:

108-88-3 toluene

BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



(Contd. on page 6)





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physic	cal and chemical properties
General Information	
· Appearance:	
Form:	Liquid
Color:	Clear

Odor: Characteristic
 Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition Melting point/Melting range:

Melting point/Melting range:Undetermined.Boiling point/Boiling range:110 °C (230 °F)

• Flash point: 4 °C (39 °F)

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 535 °C (995 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 7.0 Vol %

(Contd. on page 7)





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

		(Contd. of page
· Vapor pressure at 20 °C (68 °F):	29 hPa (22 mm Hg)	
· Density at 20 °C (68 °F):	1.006 g/cm³ (8.395 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	46.6 %	
VOC content:	46.6 %	
	Coating VOC 468.9 g/l / 3.91 lb/gl	
	Material VOC 468.9 g/l / 3.91 lb/gl	
Solids content:	53.4 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 1	· LD/LC50 values that are relevant for classification: 108-88-3 toluene				
108-88-3 to					
Oral	LD50	5000 mg/kg (rat)			
Dermal	LD50	12124 mg/kg (rabbit)			
Inhalative	LC50/4 h	5320 mg/l (mouse)			

(Contd. on page 8)





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 7)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

108-88-3 toluene

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

 $(Contd.\ on\ page\ 9)$





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 8)

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number	******
DOT, IMDG, IATA	UN1263
UN proper shipping name	
DOT	Paint mixture
IMDG, IATA	PAINT mixture
Transport hazard class(es)	
DOT	
ELAMABLE IVID	
3	
Class	2 Fl
Class Label	3 Flammable liquids 3
	J
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
	II .
Environmental hazards:	N.
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u>
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
Zuaning minumons	On cargo aircraft only: 60 L

(Contd. on page 10)





Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 9)

 \cdot IMDG

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN1263, Paint mixture, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

1L

- . Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

108-88-3 toluene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

108-88-3 toluene

II

· TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 11)



Page 11/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 10)

· Hazard symbols:





Harmful Highly flammable

· Hazard-determining components of labeling:

poly(hexamethylene diisocyanate) toluene

· Risk phrases:

Highly flammable.

Irritating to eyes and skin.

May cause sensitisation by inhalation and skin contact.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

Avoid contact with skin and eyes.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable gloves.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

In case of accident by inhalation: remove casualty to fresh air and keep at rest.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Roberts
- · Date of preparation / last revision 03/02/2015 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 12)



Page 12/12

Safety Data Sheet acc. to OSHA HCS

Printing date 03/02/2015 Reviewed on 03/02/2015

Trade name: GH1 FAST ACTIVATOR

(Contd. of page 11)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1