



Printing date 08/24/2015 Reviewed on 08/24/2015

## 1 Identification

- · Product identifier
- · Trade name: GT211 2.1 VOC CLEAR
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Lusid Technologies 5195 West 4700 South KEARNS, UT 84118 USA
- · Information department: Product safety department
- · Emergency telephone number: 1-800-535-5053

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- . Lahel elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

· Signal word Danger

2.3....

· Hazard-determining components of labeling:

*n-butyl acetate acetone* 

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

(Contd. on page 2)





Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 1)

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)



Page 3/12

acc. to OSHA HCS

Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 2)

· vPvB: Not applicable.

LUSID TECHNOLOG

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:					
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%			
123-86-4	n-butyl acetate	10-25%			
67-64-1	acetone	10-25%			
110-43-0	heptan-2-one	≤ 2.5%			
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≤ 2.5%			

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)





Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 3)

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components	with lim	it values	that re	equire	monitoring	at the	workplace:

### 123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 950 mg/m³, 200 ppm

Long-term value: 713 mg/m³, 150 ppm

#### 67-64-1 acetone

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

(Contd. on page 5)





Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 4)

REL | Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

BEI

### 110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 465 mg/m³, 100 ppm TLV Long-term value: 233 mg/m³, 50 ppm

### · Ingredients with biological limit values:

#### 67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)





Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 5)

· Eye protection:

· Vapour density

Water:

· Evaporation rate

· Solubility in / Miscibility with

· Partition coefficient (n-octanol/water): Not determined.



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and o · General Information	chemical properties
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	55 °C (131 °F)
· Flash point:	-17 °C (1 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (175 mm Hg)
· Density at 20 °C (68 °F):	1.05745 g/cm³ (8.824 lbs/gal)
· Relative density	Not determined.

Not determined.

Not determined.

Not miscible or difficult to mix.

(Contd. on page 7)





Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

		(Contd. of page 0
· Viscosity:	N. J I	
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	30.0 %	
VOC content:	19.7 %	
	Coating VOC 297.1 g/l / 2.48 lb/gl	
	Material VOC 211.0 g/l / 1.76 lb/gl	
Solids content:	49.8 %	
· Other information	No further relevant information available.	

# 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- $\cdot \textit{Sensitization:} \ \textit{No sensitizing effects known.}$
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

None of the ingredients is listed.

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
· NTP (Natio	onal Toxicology Program)	

(Contd. on page 8)



Page 8/12

acc. to OSHA HCS

Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

# 12 Ecological information

· Toxicity

LUSID TECHNOLOG

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

				- 4		<i>.</i>			
_ / / /	$\boldsymbol{v}\boldsymbol{\alpha}$	$\alpha \circ \alpha$	$n \alpha$	r	T T T	tai	*****/	7	$\alpha m$
		/ A Y	,,,,			.,,,,	mc	# # A	,,,,

· UN-Number

· **DOT**, **IMDG**, **IATA** UN1263

· UN proper shipping name

· DOT Paint · IMDG, IATA PAINT

(Contd. on page 9)





Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 8) · Transport hazard class(es)  $\cdot DOT$ · Class 3 Flammable liquids · Label · IMDG, IATA · Class 3 Flammable liquids · Label · Packing group II· DOT, IMDG, IATA · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 33 · EMS Number: F-E,S-E· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information:  $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L  $\cdot$  IMDG · Limited quantities (LQ) 5LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN1263, Paint, 3, II

US





Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 9)

Safety, health and environmental regulations/legislation specific for the Sara	substance or mixture
Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
1330-20-7 xylene	
100-41-4 ethylbenzene	
108-88-3 toluene	
TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
Proposition 65	
Chemicals known to cause cancer:	
100-41-4 ethylbenzene	
Chemicals known to cause reproductive toxicity for females:	
108-88-3 toluene	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
108-88-3 toluene	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
67-64-1 acetone	
1330-20-7 xylene	
100-41-4 ethylbenzene	
108-88-3 toluene	
TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	A
1330-20-7 xylene	A
100-41-4 ethylbenzene	A
77-58-7 dibutyltin dilaurate	A
108-88-3 toluene	A
NIOSH-Ca (National Institute for Occupational Safety and Health)	·

(Contd. on page 11)



Page 11/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 10)

#### · Hazard pictograms





GHS02 G

#### · Signal word Danger

#### · Hazard-determining components of labeling:

n-butyl acetate

acetone

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

#### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

#### · Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Wear protective gloves.

Wear eye protection / face protection.

Ground/bond container and receiving equipment.

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 12)



Page 12/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/24/2015 Reviewed on 08/24/2015

Trade name: GT211 2.1 VOC CLEAR

(Contd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Roberts
- · Date of preparation / last revision 08/24/2015 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

US