

Printing date 05/11/2015

Reviewed on 05/11/2015

1 Identification

· Product identifier

· Trade name: HLX ACTIVATOR

Details of the supplier of the safety data sheet
Manufacturer/Supplier: Lusid Technologies
5195 West 4700 South KEARNS, UT 84118 USA

• Information department: Product safety department • Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS08 Health hazard Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Classification according to Directive 67/548/EEC or Directive 1999/45/EC Harmful Harmful by inhalation and in contact with skin. X Irritant Irritating to eyes and skin. May cause sensitisation by inhalation and skin contact. Flammable. · Information concerning particular hazards for human and environment: The product has to be labeled due to the calculation procedure of international guidelines. · Classification system: The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data. (Contd. on page 2) USA

Page 1/11



Printing date 05/11/2015

Reviewed on 05/11/2015

Trade name: HLX ACTIVATOR

· Label elements

- *Labelling according to EU guidelines:* The product has been classified and marked in accordance with directives on hazardous materials.
- · Code letter and hazard designation of product:



Harmful

• *Hazard-determining components of labeling:* poly(hexamethylene diisocyanate) xylene

· Risk phrases:

Flammable. Harmful by inhalation and in contact with skin. Irritating to eyes and skin. May cause sensitisation by inhalation and skin contact.

· Safety phrases:

Keep out of the reach of children. Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer). Wear suitable protective clothing and gloves. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Dispose of this material and its container to hazardous or special waste collection point.

In case of accident by inhalation: remove casualty to fresh air and keep at rest.

- · Classification system:
- · NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 3)

(Contd. of page 1)



Printing date 05/11/2015

Reviewed on 05/11/2015

Trade name: HLX ACTIVATOR

(Contd. of page 2)

50-100% 25-50%

Page 3/11

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

1330-20-7 xylene

28182-81-2 poly(hexamethylene diisocyanate)

4 First-aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures* Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

USA

LUSID TECHNOLOGIES

Safety Data Sheet acc. to OSHA HCS

Printing date 05/11/2015

Trade name: HLX ACTIVATOR

Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
 Information about protection against explosions and file
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with	limit values that	require monitoring	at the workplace:

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

- REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
- TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

Reviewed on 05/11/2015

Page 4/11

(Contd. of page 3)



Printing date 05/11/2015

Trade name: HLX ACTIVATOR

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- \cdot Information on basic physical and chemical properties
- · General Information

• Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.

(Contd. on page 6)

Reviewed on 05/11/2015

(Contd. of page 4)

- USA

Page 5/11



Printing date 05/11/2015

Reviewed on 05/11/2015

Trade name: HLX ACTIVATOR

	(Contd. of page	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 137 °C (279 °F)	
Flash point:	30 °C (86 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	500 °C (932 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.	
Explosion limits:		
Lower:	1.1 Vol %	
Upper:	7.0 Vol %	
Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)	
Density at 20 °C (68 °F):	0.99 g/cm ³ (8.262 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	52.3 %	
VOC content:	52.3 %	
	Coating VOC 517.0 g/l / 4.31 lb/gl	
	Material VOC 517.0 g/l / 4.31 lb/gl	
Solids content:	47.7 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 7)

USA

Printing date 05/11/2015

Trade name: HLX ACTIVATOR

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization:
- Sensitization possible through inhalation.
- Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 8)



Reviewed on 05/11/2015

(Contd. of page 6)

. .

3

Printing date 05/11/2015

Trade name: HLX ACTIVATOR

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- \cdot Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint mixture	
IMDG, IATA	PAINT mixture	
Transport hazard class(es)		
DOT		
TRANSFEE LOUD 3 Class	3 Flammable liquids	
Label	3	
IMDG, IATA		
Class	3 Flammable liquids	
Label	3	



(Contd. of page 7)

Reviewed on 05/11/2015





Printing date 05/11/2015

Reviewed on 05/11/2015

Trade name: HLX ACTIVATOR

	(Contd. of page
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	30
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
• Transport in bulk according to Annex I	I of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
~ .	On cargo aircraft only: 220 L
· IMDG	
mited quantities (LQ) 5L	
Excepted quantities $(\widetilde{E}Q)$	Code: El
· · · · · · · · · · · · · · · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN1263, Paint mixture, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

 \cdot Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

 \cdot Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

Page 9/11

USA



Printing date 05/11/2015

Reviewed on 05/11/2015

Trade name: HLX ACTIVATOR

(Contd. of page 9)

Ι

A4

Page 10/11

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

• TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:



Harmful

• *Hazard-determining components of labeling:* poly(hexamethylene diisocyanate) xylene

· Risk phrases:

Flammable. Harmful by inhalation and in contact with skin. Irritating to eyes and skin. May cause sensitisation by inhalation and skin contact.

· Safety phrases:

Keep out of the reach of children.
Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
Wear suitable protective clothing and gloves.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Dispose of this material and its container to hazardous or special waste collection point.
In case of accident by inhalation: remove casualty to fresh air and keep at rest.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Mr. Roberts

- · Date of preparation / last revision 05/11/2015 / -
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

(Contd. on page 11)

⁻ USA



Printing date 05/11/2015

Trade name: HLX ACTIVATOR

Reviewed on 05/11/2015

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 3: Flammable liquids, Hazard Category 3 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 1 Skin Sens. 1: Sensitisation - Respirat., Hazard Category 1 (Contd. of page 10)

USA

Page 11/11