

Safety Data Sheet acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

1 Identification

- **Product identifier**
- **Trade name:** LXK LIXX FLEET BLACK
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Lusid Technologies
5195 West 4700 South
KEARNS, UT 84118
USA
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Toxic

May cause cancer. May cause heritable genetic damage.



Harmful

Harmful by inhalation. Possible risk of harm to the unborn child.



Highly flammable

Highly flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labeled due to the calculation procedure of international guidelines.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 1)

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Code letter and hazard designation of product:**



Toxic
Highly flammable

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.
toluene

· **Risk phrases:**

May cause cancer.
May cause heritable genetic damage.
Highly flammable.
Also harmful by inhalation.
Possible risk of harm to the unborn child.

· **Safety phrases:**

Avoid exposure - obtain special instructions before use.
Keep locked up and out of the reach of children.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Wear suitable protective clothing, gloves and eye/face protection.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **Special labeling of certain preparations:**

Restricted to professional users.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 3
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *0
Fire = 3
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

108-65-6	2-methoxy-1-methylethyl acetate	10-25%
1330-20-7	xylene	10-25%
108-88-3	toluene	2.5-10%
110-43-0	heptan-2-one	2.5-10%
123-86-4	n-butyl acetate	2.5-10%
1333-86-4	Carbon black	≤ 2.5%
100-41-4	ethylbenzene	≤ 2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤ 2.5%
64-17-5	ethanol	≤ 2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

USA

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 4)

8 Exposure controls/personal protection

· *Additional information about design of technical systems: No further data; see item 7.*

· *Control parameters*

· *Components with limit values that require monitoring at the workplace:*

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm

Long-term value: 434 mg/m³, 100 ppm

BEI

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

110-43-0 heptan-2-one

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 950 mg/m³, 200 ppm

Long-term value: 713 mg/m³, 150 ppm

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

REL Long-term value: 3.5* mg/m³

*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³

*inhalable fraction

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 5)

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 6)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Black

· **Odor:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 110 °C (230 °F)

· **Flash point:** 4 °C (39 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 315 °C (599 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.1 Vol %

Upper: 10.8 Vol %

· **Vapor pressure at 20 °C (68 °F):** 6.7 hPa (5 mm Hg)

· **Density at 20 °C (68 °F):** 1.01384 g/cm³ (8.46 lbs/gal)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 7)

- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 52.22 %
 - VOC content:** 52.22 %
 - Coating VOC 529.4 g/l / 4.42 lb/gl
 - Material VOC 529.4 g/l / 4.42 lb/gl
- **Solids content:** 47.7 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 8)

Inhalative LC50/4 h >10.2 mg/l (rat)

· Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7	xylene	3
108-88-3	toluene	3
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B
64-17-5	ethanol	1
67-63-0	propan-2-ol	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015



Trade name: LXX LIXX FLEET BLACK

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
-
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, IMDG, IATA** II
- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Flammable liquids
- **Danger code (Kemler):** 33
- **EMS Number:** F-E,S-E
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 10)

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN1263, Paint, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

108-88-3 toluene

100-41-4 ethylbenzene

67-56-1 methanol

7664-38-2 phosphoric acid

67-63-0 propan-2-ol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

64-17-5 ethanol

(Contd. on page 12)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 11)

67-56-1 methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7	xylene	I
108-88-3	toluene	II
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7	xylene	A4
108-88-3	toluene	A4
1333-86-4	Carbon black	A4
100-41-4	ethylbenzene	A3
64-17-5	ethanol	A3
77-58-7	dibutyltin dilaurate	A4
67-63-0	propan-2-ol	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4	Carbon black
-----------	--------------

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:



Toxic
Highly flammable

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.
toluene

· Risk phrases:

May cause cancer.
May cause heritable genetic damage.
Highly flammable.
Also harmful by inhalation.
Possible risk of harm to the unborn child.

· Safety phrases:

Avoid exposure - obtain special instructions before use.
Keep locked up and out of the reach of children.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Wear suitable protective clothing, gloves and eye/face protection.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

(Contd. on page 13)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/02/2015

Reviewed on 06/02/2015

Trade name: LXX LIXX FLEET BLACK

(Contd. of page 12)

- **Special labeling of certain preparations:**
Restricted to professional users.
- **National regulations:**
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** *Environment protection department.*
- **Contact:** *Mr. Roberts*
- **Date of preparation / last revision** 06/02/2015 / -
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Muta. 1B: Germ cell mutagenicity, Hazard Category 1B
Carc. 1A: Carcinogenicity, Hazard Category 1A
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2