

Printing date 05/20/2014 Reviewed on 02/22/2014

1 Identification

· Product identifier

· Trade name: S1522 REDUCER FAST

· Article number: S1522

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Information department: Product safety department
- · Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



X Harmful

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.



Irritant

Irritating to skin.



Highly flammable

Highly flammable.

Vapours may cause drowsiness and dizziness.

- Information concerning particular hazards for human and environment:
- The product has to be labeled due to the calculation procedure of international guidelines.
- · Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:





Harmful Highly flammable

· Hazard-determining components of labeling:

toluene

· Risk phrases:

Highly flammable.

Irritating to skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

(Contd. on page 2)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

(Contd. of page 1)

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 3 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangero	us components:	
123-86-4	n-butyl acetate	25-50%
108-88-3	toluene	25-50%
108-65-6	2-methoxy-1-methylethyl acetate	10-25%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

 Indication of any immediate medical attention and special treatment needed No further relevant information available.

1167



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

(Contd. of page 3)

· Control parameters

00//10/	parameters
· Compor	nents with limit values that require monitoring at the workplace:
123-86-4	I n-butyl acetate
PEL ()	Long-term value: 710 mg/m³, 150 ppm
REL ()	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV ()	Short-term value: 950 mg/m³, 200 ppm Long-term value: 713 mg/m³, 150 ppm
108-88-3	toluene
PEL ()	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL ()	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
TLV ()	Long-term value: 75 mg/m³, 20 ppm BEI
108-65-6	2-methoxy-1-methylethyl acetate
WEEL ()	Long-term value: 50 ppm
· Ingredie	ents with biological limit values:
108-88-3	3 toluene
M. T.	.02 mg/L fledium: blood ime: prior to last shift of workweek arameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

(Contd. of page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

· Danger of explosion:

· Explosion limits: Lower:



Tightly sealed goggles

Physical and chemical properties

Information on basic physical and General Information	l chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	110 °C (230 °F)
Flash point:	14 °C (57 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	315 °C (599 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.

vapor mixtures are possible.

1.2 Vol %

(Contd. on page 6)

Product is not explosive. However, formation of explosive air/



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

		(Contd. of page 5)
Upper:	10.8 Vol %	
· Vapor pressure at 20 °C (68 °F):	29 hPa (22 mm Hg)	
· Density at 20 °C (68 °F):	0.89049 g/cm³ (7.431 lbs/gal)	
Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.0 %	
	890.5 g/l / 7.43 lb/gl	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	values tha	at are relevant for classification:
Oral	LD50	5800 mg/kg (mouse)
108-88-3	toluene	
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

(Contd. of page 6)

Irritant

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-88-3 toluene

3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name		
· DOT	Paint	
· ADR	1263 Paint	
· IMDG, IATA	PAINT	

(Contd. on page 8)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

(Contd. of page 7)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids.

· Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA //

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler): 33
EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S1522 REDUCER FAST

(Contd. of page 8)

· Chemicals known to cause developmental toxicity:

108-88-3 toluene

· Carcinogenic categories

· EPA (Environmental Protection Agency)

108-88-3 toluene

| | | |

· TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:





Harmful Highly flammable

· Hazard-determining components of labeling:

toluene

· Risk phrases:

Highly flammable.

Irritating to skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- · Contact: Ms. Topaljikian