






1 Identification of the substance/mixture and of the company/undertaking

- . **Product identifier**
- . **Trade name:** S1918 TOUCH UP BICOAT
- . **Article number:** S1918
- . **Details of the supplier of the safety data sheet**
- . **Manufacturer/Supplier:**
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- . **Information department:** Product safety department
- . **Emergency telephone number:** 1-800-535-5053

2 Hazards identification

- . **Classification of the substance or mixture**
- . **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
-  Harmful
Harmful by inhalation and in contact with skin.
-  Irritant
Irritating to skin.
- Flammable.
- . **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of international guidelines.
- . **Classification system:**
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- . **Label elements**
- . **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with directives on hazardous materials.
- . **Code letter and hazard designation of product:**
-  Harmful
- . **Hazard-determining components of labelling:**
xylene
- . **Risk phrases:**
Flammable.
Harmful by inhalation and in contact with skin.
Irritating to skin.
- . **Safety phrases:**
Keep out of the reach of children.
Wear suitable protective clothing and gloves.
If swallowed, seek medical advice immediately and show this container or label.
Dispose of this material and its container to hazardous or special waste collection point.



Trade name: S1918 TOUCH UP BICOAT

(Contd. of page 1)

- . **Classification system:**
- . **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- . **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 3
Reactivity = 0

- . **Other hazards**
- . **Results of PBT and vPvB assessment**
- . **PBT:** Not applicable.
- . **vPvB:** Not applicable.

3 Composition/information on ingredients

- . **Chemical characterization: Mixtures**
- . **Description:** Mixture of the substances listed below with nonhazardous additions.

. **Dangerous components:**

123-86-4	n-butyl acetate	25-50%
1330-20-7	xylene	10-25%
108-65-6	2-methoxy-1-methylethyl acetate	10-25%

4 First aid measures

- . **Description of first aid measures**
- . **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- . **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- . **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- . **After eye contact:** Rinse opened eye for several minutes under running water.
- . **After swallowing:** If symptoms persist consult doctor.
- . **Information for doctor:**
- . **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- . **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- . **Extinguishing media**
- . **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- . **For safety reasons unsuitable extinguishing agents:** Water with full jet
- . **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 3)



Trade name: S1918 TOUCH UP BICOAT

(Contd. of page 2)

- . **Advice for firefighters**
- . **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- . **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- . **Environmental precautions:** No special measures required.
- . **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- . **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- . **Handling:**
- . **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- . **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- . **Conditions for safe storage, including any incompatibilities**
- . **Storage:**
- . **Requirements to be met by storerooms and receptacles:** No special requirements.
- . **Information about storage in one common storage facility:** Not required.
- . **Further information about storage conditions:** Keep receptacle tightly sealed.
- . **Storage class:** 3
- . **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- . **Additional information about design of technical systems:** No further data; see item 7.
- . **Control parameters**

. **Components with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

(Contd. on page 4)



Trade name: S1918 TOUCH UP BICOAT

(Contd. of page 3)

108-65-6 2-methoxy-1-methylethyl acetate

WEEL 50 ppm

. **Additional information:** *The lists that were valid during the creation were used as basis.*

. **Exposure controls**

. **Personal protective equipment:**

. **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

. **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

. **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

. **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

. **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

. **Information on basic physical and chemical properties**

. **General Information**

. **Appearance:**

Form:

Liquid

Color:

Colorless

. **Odor:**

Characteristic

. **Odour threshold:**

Not determined.

. **pH-value:**

Not determined.

. **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

124°C (255 °F)

. **Flash point:**

27°C (81 °F)

(Contd. on page 5)



Trade name: S1918 TOUCH UP BICOAT

(Contd. of page 4)

. Flammability (solid, gaseous):	Not applicable.
. Ignition temperature:	315°C (599 °F)
. Decomposition temperature:	Not determined.
. Auto igniting:	Product is not selfigniting.
. Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
. Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
. Vapor pressure at 20°C (68 °F):	10.7 hPa (8 mm Hg)
. Density at 20°C (68 °F):	0.925 g/cm ³ (7.719 lbs/gal)
. Relative density	Not determined.
. Vapour density	Not determined.
. Evaporation rate	Not determined.
. Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
. Partition coefficient (n-octanol/water):	Not determined.
. Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
. Solvent content:	
Organic solvents:	85.2 %
VOC content:	85.2 %
	788.5 g/l / 6.58 lb/gl
Solids content:	14.8 %
. Other information	No further relevant information available.

10 Stability and reactivity

- . **Reactivity**
- . **Chemical stability**
- . **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- . **Possibility of hazardous reactions** No dangerous reactions known.
- . **Conditions to avoid** No further relevant information available.
- . **Incompatible materials:** No further relevant information available.
- . **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- . **Information on toxicological effects**
- . **Acute toxicity:**
- . **LD/LC50 values that are relevant for classification:**
- 1330-20-7 xylene**

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- . **Primary irritant effect:**
- . **on the skin:** Irritant to skin and mucous membranes.

(Contd. on page 6)



Trade name: S1918 TOUCH UP BICOAT

(Contd. of page 5)

- . **on the eye:** No irritating effect.
- . **Sensitization:** No sensitizing effects known.
- . **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
- . **Carcinogenic categories**

. **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

. **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

- . **Toxicity**
- . **Aquatic toxicity:** No further relevant information available.
- . **Persistence and degradability** No further relevant information available.
- . **Behavior in environmental systems:**
- . **Bioaccumulative potential** No further relevant information available.
- . **Mobility in soil** No further relevant information available.
- . **Results of PBT and vPvB assessment**
- . **PBT:** Not applicable.
- . **vPvB:** Not applicable.
- . **Other adverse effects** No further relevant information available.

13 Disposal considerations

- . **Waste treatment methods**
- . **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- . **Uncleaned packagings:**
- . **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- . **UN-Number**
- . **DOT, ADR, IMDG, IATA** UN1263
- . **UN proper shipping name**
- . **DOT, IMDG, IATA** PAINT RELATED MATERIAL
- . **ADR** 1263 PAINT RELATED MATERIAL

(Contd. on page 7)



Trade name: S1918 TOUCH UP BICOAT

(Contd. of page 6)

. **Transport hazard class(es)**

. **DOT**



. **Label**

3

. **ADR, IMDG**



. **Class**

3 Flammable liquids

. **Label**

3

. **IATA**



. **Label**

3

. **Packing group**

. **DOT, ADR, IMDG, IATA**

III

. **Environmental hazards:**

. **Marine pollutant:**

No

. **Special precautions for user**

Warning: Flammable liquids

. **EMS Number:**

F-E, S-E

. **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

15 Regulatory information

. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

. **Sara**

. **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

. **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

. **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

. **Proposition 65**

. **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

. **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 8)



Trade name: S1918 TOUCH UP BICOAT

(Contd. of page 7)

. Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

. Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

. Carcinogenic categories

. EPA (Environmental Protection Agency)

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

. TLV (Threshold Limit Value established by ACGIH)

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

. NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

. OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

. Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

. Hazard symbols:



Harmful

. Hazard-determining components of labelling:

xylene

. Risk phrases:

Flammable.
Harmful by inhalation and in contact with skin.
Irritating to skin.

. Safety phrases:

Keep out of the reach of children.
Wear suitable protective clothing and gloves.
If swallowed, seek medical advice immediately and show this container or label.
Dispose of this material and its container to hazardous or special waste collection point.

. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- . Department issuing MSDS:** Product safety department
- . Contact:** Ms. Topaljikian