Printing date 08/07/2012 Reviewed on 05/03/2012

1 Identification of the substance/mixture and of the company/undertaking

. Product identifier

. Trade name: S2012 TOUCH UP MONOCOAT

. Article number: S2012

- . Details of the supplier of the safety data sheet
- . Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623 Beirut

LEBANON

info@generalpaint.biz

. Information department: Product safety department . Emergency telephone number: 1-800-535-5053

2 Hazards identification

- . Classification of the substance or mixture
- . Classification according to Directive 67/548/EEC or Directive 1999/45/EC




Harmful

Harmful by inhalation and in contact with skin.



Irritant

Irritating to eyes, respiratory system and skin.



Highly flammable

Harmful to aquatic organisms.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- . Label elements
- . Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

. Code letter and hazard designation of product:





Harmful Highly flammable

. Hazard-determining components of labelling:

methyl isobutyl ketone

. Risk phrases:

Highly flammable.

Harmful by inhalation and in contact with skin. Irritating to eyes, respiratory system and skin.

Harmful to aquatic organisms.

. Safety phrases:

Keep locked up and out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing, gloves and eye/face protection.

(Contd. on page 2)



Printing date 08/07/2012 Reviewed on 05/03/2012

Trade name: S2012 TOUCH UP MONOCOAT

(Contd. of page 1)

If swallowed, seek medical advice immediately and show this container or label.

Classification system:

. NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

. HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

- . Other hazards
- . Results of PBT and vPvB assessment
- . **PBT**: Not applicable. . **vPvB**: Not applicable.

3 Composition/information on ingredients

- . Chemical characterization: Mixtures
- . Description: Mixture of the substances listed below with nonhazardous additions.

. Dangerous components:		
	methyl isobutyl ketone	25-50%
108-65-6	2-methoxy-1-methylethyl acetate	25-50%
1330-20-7	xylene	25-50%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%

4 First aid measures

- . Description of first aid measures
- . General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

. After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- . After skin contact: Immediately wash with water and soap and rinse thoroughly.
- . After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- . After swallowing: If symptoms persist consult doctor.
- . Information for doctor:
- . Most important symptoms and effects, both acute and delayed

No further relevant information available.

. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- . Extinguishing media
- . Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- . For safety reasons unsuitable extinguishing agents: Water with full jet
- . Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



Printing date 08/07/2012 Reviewed on 05/03/2012

Trade name: S2012 TOUCH UP MONOCOAT

(Contd. of page 2)

. Advice for firefighters

. Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

. Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

. Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

. Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- . Handling:
- . Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

. Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- . Conditions for safe storage, including any incompatibilities
- . Storage:
- . Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- . Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- . Storage class: З
- . Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Long-term value: 82 mg/m³, 20 ppm

- . Additional information about design of technical systems: No further data; see item 7.
- Control parameters

BEI

. Control parameters				
. Components with limit values that require monitoring at the workplace:				
methyl isobutyl ketone				
PEL	410 mg/m³, 100 ppm			
REL	Short-term value: 300 mg/m³, 75 ppm			
	Long-term value: 205 mg/m³, 50 ppm			
TLV	Short-term value: 307 mg/m³, 75 ppm			

(Contd. on page 4)



Printing date 08/07/2012 Reviewed on 05/03/2012

Trade name: S2012 TOUCH UP MONOCOAT

108-65	Contd. of page 3) 5-6 2-methoxy-1-methylethyl acetate
WEEL	50 ppm
1330-2	20-7 xylene
PEL REL	435 mg/m³, 100 ppm Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI

- . Additional information: The lists that were valid during the creation were used as basis.
- . Exposure controls
- Personal protective equipment:
- . General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

. Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

. Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

. Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- . Information on basic physical and chemical properties
- . General Information
- . Appearance:

Form: Fluid

Color: According to product specification

. **Odor:** Characteristic . **Odour threshold:** Not determined.

(Contd. on page 5)



Printing date 08/07/2012 Reviewed on 05/03/2012

Trade name: S2012 TOUCH UP MONOCOAT

	(Contd. of page
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	115°C (239 °F)
Flash point:	14°C (57 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	315°C (599 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosiv
	air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
Vapor pressure at 20°C (68 °F):	8 hPa (6 mm Hg)
Density at 20°C (68 °F):	0.88778 g/cm³ (7.409 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	t er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	95.9 %
VOC content:	95.9 %
	851.6 g/l / 7.11 lb/gl
Solids content:	4.1 %
Other information	No further relevant information available.

10 Stability and reactivity

- . Reactivity
- . Chemical stability
- . Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.

 Possibility of hazardous reactions No dangerous reactions known.
- . Conditions to avoid No further relevant information available.
- . Incompatible materials: No further relevant information available.
 . Hazardous decomposition products: No dangerous decomposition products known.



Reviewed on 05/03/2012 Printing date 08/07/2012

Trade name: S2012 TOUCH UP MONOCOAT

(Contd. of page 5)

1 Toxicological information

- . Information on toxicological effects
- . Acute toxicity:

. LD/LC50 values that are relevant for classification:				
methyl is	methyl isobutyl ketone			
Oral	LD50	2080 mg/kg (rat)		
Dermal	LD50	16000 mg/kg (rab)		
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)		
1330-20-7	1330-20-7 xylene			
Oral	LD50	4300 mg/kg (rat)		
Dermal	LD50	2000 mg/kg (rabbit)		
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6800 mg/kg (rat)		
Dermal	LD50	>3400 mg/kg (rab)		
Inhalative	LC50/4 h	>10.2 mg/l (rat)		

- Primary irritant effect:
- . on the skin: Irritant to skin and mucous membranes.
- . on the eye: Irritating effect.
- . **Sensitization:** No sensitizing effects known. **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

. Carcinogenic categories

. IARC (International Agency for Research on Cancer)			
1330-20-7		3	
100-41-4	ethylbenzene	2B	
. NTP (Natio	. NTP (National Toxicology Program)		
None of the ingredients is listed.			

12 Ecological information

- . Toxicity
- . Aquatic toxicity: No further relevant information available.
- . Persistence and degradability No further relevant information available.
- . Behavior in environmental systems:
- . Bioaccumulative potential No further relevant information available.
- . Mobility in soil No further relevant information available.
- . Ecotoxical effects:
- . Remark: Harmful to fish
- . Additional ecological information:
- . General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- . Results of PBT and vPvB assessment
- . **PBT:** Not applicable.
- . vPvB: Not applicable.

(Contd. on page 7)

CEUEBHL

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/07/2012 Reviewed on 05/03/2012

Trade name: S2012 TOUCH UP MONOCOAT

(Contd. of page 6)

. Other adverse effects No further relevant information available.

13 Disposal considerations

- . Waste treatment methods
- . Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packagings:
- . Recommendation: Disposal must be made according to official regulations.

Transport information		
UN-Number DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name DOT, IMDG, IATA ADR	PAINT 1263 PAINT	
Transport hazard class(es)		
DOT		
PLANMAGE F. JELLO		
Class	3 Flammable liquids.	
Label	3	
Class	3 Flammable liquids	
Label	3	
Packing group DOT, ADR, IMDG, IATA	II	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	
Danger code (Kemler): EMS Number:	33 E E S E	
LING HUMBEL.	F-E, <u>S-E</u>	

USA

(Contd. on page 8)

Printing date 08/07/2012 Reviewed on 05/03/2012

Trade name: S2012 TOUCH UP MONOCOAT

(Contd. of page 7)

15 Regulatory information

- . Safety, health and environmental regulations/legislation specific for the substance or mixture
- . Sara

CENERAL

. Section 355 (extremely hazardous substances	;):
---	-----

None of the ingredients is listed.

. Section 313 (Specific toxic chemical listings):

methyl isobutyl ketone

1330-20-7 xylene

100-41-4 ethylbenzene

. TSCA (Toxic Substances Control Act):

All ingredients are listed.

. Proposition 65

. Chemicals known to cause cancer:

methyl isobutyl ketone

100-41-4 ethylbenzene

. Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

. Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

. Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

. Carcinogenic categories

. EPA (Environmental Protection Agency)		
	methyl isobutyl ketone	1
1330-20-7	xylene	1
100-41-4	ethylbenzene	D

. TLV (Threshold Limit Value established by ACGIH)

-	·	
1330-20-7	xylene	A4
100-41-4	ethylbenzene	<i>A</i> 3

. NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

. OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

. Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

. Hazard symbols:





Harmful Highly flammable

. Hazard-determining components of labelling:

xylene methyl isobutyl ketone

. Risk phrases:

Highly flammable.

Harmful by inhalation and in contact with skin.



Printing date 08/07/2012 Reviewed on 05/03/2012

Trade name: S2012 TOUCH UP MONOCOAT

(Contd. of page 8)

Irritating to eyes, respiratory system and skin. Harmful to aquatic organisms.

. Safety phrases:

Keep locked up and out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing, gloves and eye/face protection.

If swallowed, seek medical advice immediately and show this container or label.

. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- . Department issuing MSDS: Product safety department
- . Contact: Ms. Topaljikian

USA