

Printing date 05/20/2014 Reviewed on 02/22/2014

# 1 Identification

· Product identifier

· Trade name: S2232 REDUCER NORMAL

· Article number: S2232

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:

General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Information department: Product safety department
- · Emergency telephone number: 1-800-535-5053

### 2 Hazard(s) identification

- · Classification of the substance or mixture
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Harmful

Harmful by inhalation and in contact with skin. Harmful: may cause lung damage if swallowed.



Irritant

Irritating to respiratory system and skin.



Highly flammable

Highly flammable.

Harmful to aquatic organisms.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:





Harmful Highly flammable

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom. xylene

· Risk phrases:

Highly flammable.

Harmful by inhalation and in contact with skin.

Irritating to respiratory system and skin.

Harmful to aquatic organisms.

(Contd. on page 2)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 1)

Harmful: may cause lung damage if swallowed.

#### · Safety phrases:

Keep locked up and out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing, gloves and eye/face protection.

If swallowed, seek medical advice immediately and show this container or label.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 3

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous components: |  |         |  |
|-------------------------|--|---------|--|
| 123-86-4                | n-butyl acetate                          | 25-50%  |  |
| 1330-20-7               | xylene                                   | 10-25%  |  |
| 64742-95-6              | Solvent naphtha (petroleum), light arom. | 10-25%  |  |
| 108-65-6                | 2-methoxy-1-methylethyl acetate          | 10-25%  |  |
| 763-69-9                | ethyl 3-ethoxypropionate                 | 2.5-10% |  |

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact: Rinse opened eve for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Storage class: 3

(Contd. on page 4)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

| · Components with limit values that require monitoring at the workplace: |  |  |  |  |
|--|--|--|--|--|
| 123-86-4 n-butyl acetate   |  |  |  |  |
| PEL ()   | Long-term value: 710 mg/m³, 150 ppm  |  |  |  |
| REL ()   | Short-term value: 950 mg/m³, 200 ppm<br>Long-term value: 710 mg/m³, 150 ppm        |  |  |  |
| TLV ()   | Short-term value: 950 mg/m³, 200 ppm<br>Long-term value: 713 mg/m³, 150 ppm        |  |  |  |
| 1330-20-7 xylene   |  |  |  |  |
| PEL ()   | Long-term value: 435 mg/m³, 100 ppm  |  |  |  |
| REL ()   | Short-term value: 655 mg/m³, 150 ppm<br>Long-term value: 435 mg/m³, 100 ppm        |  |  |  |
| TLV ()   | Short-term value: 651 mg/m³, 150 ppm<br>Long-term value: 434 mg/m³, 100 ppm<br>BEI |  |  |  |

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL () Long-term value: 50 ppm

Ingredients with biological limit values:

### 1330-20-7 xylene

BEI () 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

| 9 Physical and chemical properties  |  |  |  |
|-------------------------------------|--|--|--|
| · Information on basic physical and | chemical properties  |  |  |
| General Information                 |  |  |  |
| · Appearance:                       |  |  |  |
| Form:<br>Color:                     | Liquid<br>Clear  |  |  |
| · Odor:                             | Characteristic   |  |  |
| · Odour threshold:                  | Not determined.  |  |  |
| · pH-value:                         | Not determined.  |  |  |
| · Change in condition               |  |  |  |
| Melting point/Melting range:        | Undetermined.  |  |  |
| Boiling point/Boiling range:        | 124 °C (255 °F)  |  |  |
| · Flash point:                      | 14 °C (57 °F)  |  |  |
| · Flammability (solid, gaseous):    | Not applicable.  |  |  |
| · Ignition temperature:             | 315 °C (599 °F)  |  |  |
| · Decomposition temperature:        | Not determined.  |  |  |
| · Auto igniting:                    | Product is not selfigniting.   |  |  |
| · Danger of explosion:              | Product is not explosive. However, formation of explosive air vapor mixtures are possible. |  |  |
| · Explosion limits:                 |  |  |  |
| Lower:                              | 0.7 Vol %  |  |  |
| Upper:                              | 10.8 Vol %   |  |  |
| · Vapor pressure at 20 °C (68 °F):  | 10.7 hPa (8 mm Hg)   |  |  |
| · Density at 20 °C (68 °F):         | 0.8917 g/cm³ (7.441 lbs/gal)   |  |  |
| · Relative density                  | Not determined.  |  |  |
| Vapour density                      | Not determined.  |  |  |
| · Evaporation rate                  | Not determined.  |  |  |

(Contd. on page 6)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 5)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

Organic solvents: 100.0 % VOC content: 100.0 %

891.7 g/l / 7.44 lb/gl

· Other information No further relevant information available.

# 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| LD/LC50 values that are relevant for classification: |   |                     |  |  |  |  |
|--|---|---------------------|--|--|--|--|
| Oral   | LD50  | 5800 mg/kg (mouse)  |  |  |  |  |
| 1330-20-7 xylene                                     |   |                     |  |  |  |  |
| Oral   | LD50  | 4300 mg/kg (rat)    |  |  |  |  |
| Dermal   | LD50  | 2000 mg/kg (rabbit) |  |  |  |  |
| 64742-95-  | 64742-95-6 Solvent naphtha (petroleum), light arom. |                     |  |  |  |  |
| Oral   | LD50  | >6800 mg/kg (rat)   |  |  |  |  |
| Dermal   | LD50  | >3400 mg/kg (rab)   |  |  |  |  |
| Inhalative   | LC50/4 h  | >10.2 mg/l (rat)    |  |  |  |  |
| Primary irritant effect:                             |   |                     |  |  |  |  |

- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

(Contd. on page 7)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 6)

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

| 14 Transport information              |            |
|---------------------------------------|------------|
| · UN-Number<br>· DOT, ADR, IMDG, IATA | UN1263     |
| · UN proper shipping name             |            |
| DOT                                   | Paint      |
| · ADR                                 | 1263 Paint |
| · IMDG, IATA                          | PAINT      |

(Contd. on page 8)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 7)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids.

· Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA //

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

Danger code (Kemler): 33EMS Number: F-E,S-E

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)



Printing date 05/20/2014 Reviewed on 02/22/2014

Trade name: S2232 REDUCER NORMAL

(Contd. of page 8)

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

1

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:





Harmful Highly flammable

#### · Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom. xylene

#### · Risk phrases:

Highly flammable.

Harmful by inhalation and in contact with skin.

Irritating to respiratory system and skin.

Harmful to aquatic organisms.

Harmful: may cause lung damage if swallowed.

### · Safety phrases:

Keep locked up and out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing, gloves and eye/face protection.

If swallowed, seek medical advice immediately and show this container or label.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- · Contact: Ms. Topaljikian