



### 1 Identification

- **Product identifier**
- **Trade name:** S8595 SLOW REDUCER
- **Article number:** S8595
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
xylene  
methyl isobutyl ketone  
n-butyl acetate
- **Hazard statements**  
Highly flammable liquid and vapor.



Trade name: **S8595 SLOW REDUCER**

(Contd. of page 1)

*Harmful if inhaled.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of causing cancer.  
May cause respiratory irritation. May cause drowsiness or dizziness.*

**Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wear protective gloves / eye protection / face protection.  
Ground/bond container and receiving equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Specific treatment (see on this label).  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Call a poison center/doctor if you feel unwell.  
IF exposed or concerned: Get medical advice/attention.  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
In case of fire: Use for extinction: CO2, powder or water spray.  
Take off contaminated clothing and wash it before reuse.  
Store locked up.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Dispose of contents/container in accordance with local/regional/national/international regulations.*

**Classification system:**

**NFPA ratings (scale 0 - 4)**



**HMIS-ratings (scale 0 - 4)**



**Other hazards**

**Results of PBT and vPvB assessment**

- PBT:** *Not applicable.*
- vPvB:** *Not applicable.*



**Trade name: S8595 SLOW REDUCER**

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** *Mixture of the substances listed below with nonhazardous additions.*

- **Dangerous components:**

108-65-6	2-methoxy-1-methylethyl acetate	25-50%
1330-20-7	xylene	25-50%
123-86-4	n-butyl acetate	10-25%
	methyl isobutyl ketone	10-25%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
*Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.*
- **After inhalation:**  
*Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.*  
*In case of unconsciousness place patient stably in side position for transportation.*
- **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*
- **After eye contact:**  
*Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.*
- **After swallowing:** *If symptoms persist consult doctor.*
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
*No further relevant information available.*
- **Indication of any immediate medical attention and special treatment needed**  
*No further relevant information available.*

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** *CO2, sand, extinguishing powder. Do not use water.*
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **Special hazards arising from the substance or mixture** *No further relevant information available.*
- **Advice for firefighters**
- **Protective equipment:** *Mouth respiratory protective device.*

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
*Wear protective equipment. Keep unprotected persons away.*
- **Environmental precautions:**  
*Do not allow product to reach sewage system or any water course.*  
*Inform respective authorities in case of seepage into water course or sewage system.*  
*Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*  
*Dispose contaminated material as waste according to item 13.*

(Contd. on page 4)



**Trade name: S8595 SLOW REDUCER**

(Contd. of page 3)

- Ensure adequate ventilation.*
- Do not flush with water or aqueous cleansing agents*
- **Reference to other sections**
- See Section 7 for information on safe handling.*
- See Section 8 for information on personal protection equipment.*
- See Section 13 for disposal information.*

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
- Ensure good ventilation/exhaustion at the workplace.*
- Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**
- Keep ignition sources away - Do not smoke.*
- Protect against electrostatic charges.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store in a cool location.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:**
- Keep receptacle tightly sealed.*
- Store in cool, dry conditions in well sealed receptacles.*
- **Storage class:** 3
- **Specific end use(s)** *No further relevant information available.*

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL Long-term value: 50 ppm

**1330-20-7 xylene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm

Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm

Long-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm

Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

TLV Short-term value: (950) NIC-712 mg/m<sup>3</sup>, (200) NIC-150 ppm

Long-term value: (713) NIC-238 mg/m<sup>3</sup>, (150) NIC-50 ppm

(Contd. on page 5)



**Trade name: S8595 SLOW REDUCER**

(Contd. of page 4)

**methyl isobutyl ketone**

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI

**· Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**methyl isobutyl ketone**

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

**· Additional information:** *The lists that were valid during the creation were used as basis.*

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.*
- Immediately remove all soiled and contaminated clothing.*
- Wash hands before breaks and at the end of work.*
- Avoid contact with the eyes and skin.*

**· Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

**· Protection of hands:**



*Protective gloves*

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

**· Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

**· Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

(Contd. on page 6)



Trade name: S8595 SLOW REDUCER

(Contd. of page 5)

· Eye protection:



*Tightly sealed goggles*

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	<i>Fluid</i>
Color:	<i>Clear</i>
· Odor:	<i>Characteristic</i>
· Odour threshold:	<i>Not determined.</i>

· pH-value: *Not determined.*

· Change in condition

Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>115 °C (239 °F)</i>

· Flash point: *14 °C (57 °F)*

· Flammability (solid, gaseous): *Not applicable.*

· Ignition temperature: *315 °C (599 °F)*

· Decomposition temperature: *Not determined.*

· Auto igniting: *Product is not selfigniting.*

· Danger of explosion: *Product is not explosive. However, formation of explosive air/vapor mixtures are possible.*

· Explosion limits:

Lower:	<i>1.1 Vol %</i>
Upper:	<i>10.8 Vol %</i>

· Vapor pressure at 20 °C (68 °F): *10.7 hPa (8 mm Hg)*

· Density at 20 °C (68 °F): *0.878 g/cm<sup>3</sup> (7.327 lbs/gal)*

· Relative density: *Not determined.*

· Vapour density: *Not determined.*

· Evaporation rate: *Not determined.*

· Solubility in / Miscibility with

Water: *Not miscible or difficult to mix.*

· Partition coefficient (n-octanol/water): *Not determined.*

· Viscosity:

Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>

· Solvent content:

Organic solvents:	<i>100.0 %</i>
Coating VOC content:	<i>100.0 %</i>
	<i>878.0 g/l / 7.33 lb/gl</i>

(Contd. on page 7)



**Trade name: S8595 SLOW REDUCER**

(Contd. of page 6)

<b>Material VOC content:</b>	878.0 g/l / 7.33 lb/gl
<b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

**methyl isobutyl ketone**

Oral	LD50	2080 mg/kg (rat)
Dermal	LD50	16000 mg/kg (rab)
Inhalative	LC50/4 h	8.3-16.6 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
	methyl isobutyl ketone	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.





Trade name: **S8595 SLOW REDUCER**

(Contd. of page 7)


### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **Persistence and degradability** *No further relevant information available.*
- **Behavior in environmental systems:**
- **Bioaccumulative potential** *No further relevant information available.*
- **Mobility in soil** *No further relevant information available.*
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water*  
*Do not allow product to reach ground water, water course or sewage system.*  
*Danger to drinking water if even small quantities leak into the ground.*
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **Other adverse effects** *No further relevant information available.*

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

### 14 Transport information

- |   |                     |
|---|---------------------|
| · <b>UN-Number</b>  |                     |
| · <b>DOT, ADR, IMDG, IATA</b>   | UN1263              |
| · <b>UN proper shipping name</b>  |                     |
| · <b>DOT</b>  | Paint               |
| · <b>ADR</b>  | 1263 Paint          |
| · <b>IMDG, IATA</b>   | PAINT               |
| · <b>Transport hazard class(es)</b>   |                     |
| · <b>DOT</b>  |                     |
|  |                     |
| · <b>Class</b>  | 3 Flammable liquids |
| · <b>Label</b>  | 3                   |

(Contd. on page 9)





# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 05/03/2012

Trade name: S8595 SLOW REDUCER

(Contd. of page 8)

## · ADR, IMDG, IATA



· Class 3 Flammable liquids  
· Label 3

· Packing group II  
· DOT, ADR, IMDG, IATA

· Environmental hazards:  
· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids  
· Danger code (Kemler): 33  
· EMS Number: F-E, S-E

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

## · Transport/Additional information:

· DOT  
· Quantity limitations On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

· ADR  
· Excepted quantities (EQ) Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· IMDG  
· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN1263, Paint, 3, II

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture  
· Sara

## · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

## · Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

methyl isobutyl ketone

## · TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 10)

US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/21/2015

Reviewed on 05/03/2012

Trade name: S8595 SLOW REDUCER

(Contd. of page 9)

· **Proposition 65**

· **Chemicals known to cause cancer:**

*methyl isobutyl ketone*

· **Chemicals known to cause reproductive toxicity for females:**

*None of the ingredients is listed.*

· **Chemicals known to cause reproductive toxicity for males:**

*None of the ingredients is listed.*

· **Chemicals known to cause developmental toxicity:**

*methyl isobutyl ketone*

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	<i>xylene</i>	/
	<i>methyl isobutyl ketone</i>	/

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	<i>xylene</i>	A4
-----------	---------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

*None of the ingredients is listed.*

· **GHS label elements**

*The product is classified and labeled according to the Globally Harmonized System (GHS).*

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*xylene*  
*methyl isobutyl ketone*  
*n-butyl acetate*

· **Hazard statements**

*Highly flammable liquid and vapor.*  
*Harmful if inhaled.*  
*Causes skin irritation.*  
*Causes serious eye irritation.*  
*Suspected of causing cancer.*  
*May cause respiratory irritation. May cause drowsiness or dizziness.*

· **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*  
*Use explosion-proof electrical/ventilating/lighting/equipment.*  
*Avoid breathing dust/fume/gas/mist/vapors/spray*  
*Wear protective gloves / eye protection / face protection.*  
*Ground/bond container and receiving equipment.*  
*Use only non-sparking tools.*  
*Take precautionary measures against static discharge.*  
*Wash thoroughly after handling.*  
*Use only outdoors or in a well-ventilated area.*  
*Obtain special instructions before use.*

(Contd. on page 11)



Trade name: **S8595 SLOW REDUCER**

(Contd. of page 10)

*Do not handle until all safety precautions have been read and understood.*

*IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*Specific treatment (see on this label).*

*IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*

*Call a poison center/doctor if you feel unwell.*

*IF exposed or concerned: Get medical advice/attention.*

*If skin irritation occurs: Get medical advice/attention.*

*If eye irritation persists: Get medical advice/attention.*

*In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.*

*Take off contaminated clothing and wash it before reuse.*

*Store locked up.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

*• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.*

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

• **Department issuing SDS:** Product safety department

• **Contact:** Ms. Topaljikian

• **Date of preparation / last revision** 10/21/2015 / -

• **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 2: Flammable liquids, Hazard Category 2*

*Acute Tox. 4: Acute toxicity, Hazard Category 4*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*

*Carc. 2: Carcinogenicity, Hazard Category 2*

*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*