

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

### 1 Identification

- **Product identifier**
- **Trade name:** SX01 ADHESION PROMOTER
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Lusid Technologies  
5195 West 4700 South  
KEARNS, UT 84118  
USA
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Harmful

Harmful by inhalation and in contact with skin.



Irritant

Irritating to eyes and skin.



Highly flammable

Highly flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labeled due to the calculation procedure of international guidelines.

(Contd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 1)

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Code letter and hazard designation of product:**



Harmful  
Highly flammable

· **Hazard-determining components of labeling:**

xylene  
ethylbenzene

· **Risk phrases:**

Highly flammable.  
Harmful by inhalation and in contact with skin.  
Irritating to eyes and skin.

· **Safety phrases:**

Keep out of the reach of children.  
Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Wear suitable protective clothing and gloves.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

USA

(Contd. on page 3)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 2)

**3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1330-20-7	xylene	10-25%
100-41-4	ethylbenzene	10-25%
540-88-5	tert-butyl acetate	10-25%
67-64-1	acetone	10-25%
141-78-6	ethyl acetate	10-25%

**4 First-aid measures**

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 3)

- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**1330-20-7 xylene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm

Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

(Contd. on page 5)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 4)

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
BEI

**100-41-4 ethylbenzene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm  
Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm  
BEI

**540-88-5 tert-butyl acetate**

PEL Long-term value: 950 mg/m<sup>3</sup>, 200 ppm  
REL Long-term value: 950 mg/m<sup>3</sup>, 200 ppm  
TLV Long-term value: 950 mg/m<sup>3</sup>, 200 ppm

**67-64-1 acetone**

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm  
REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
TLV Short-term value: (1782) NIC-1187 mg/m<sup>3</sup>, (750) NIC-500 ppm  
Long-term value: (1188) NIC-594 mg/m<sup>3</sup>, (500) NIC-250 ppm  
BEI

**141-78-6 ethyl acetate**

PEL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm  
REL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm  
TLV Long-term value: 1440 mg/m<sup>3</sup>, 400 ppm

**· Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI 1.5 g/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Methylhippuric acids

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
Medium: end-exhaled air  
Time: not critical  
Parameter: Ethyl benzene (semi-quantitative)

(Contd. on page 6)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 5)

**67-64-1 acetone**

BEI 50 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Acetone (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

Trade name: SX01 ADHESION PROMOTER

(Contd. of page 6)

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid  
Color: Clear  
Odor: Characteristic  
Odour threshold: Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.  
Boiling point/Boiling range: 55 °C (131 °F)

· **Flash point:** -17 °C (1 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 430 °C (806 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.0 Vol %  
Upper: 13.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 233 hPa (175 mm Hg)

· **Density at 20 °C (68 °F):** 0.86 g/cm<sup>3</sup> (7.177 lbs/gal)

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.  
Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 95.0 %  
VOC content: 65.0 %  
Coating VOC 817.0 g/l / 6.81 lb/gl  
Material VOC 540.0 g/l / 4.51 lb/gl

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 7)

**Solids content:** 5.0 %  
**Other information** No further relevant information available.

**10 Stability and reactivity**

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

**100-41-4 ethylbenzene**

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
 Harmful  
 Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 9)





## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 8)

**· OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- |                                  |        |
|----------------------------------|--------|
| · <b>UN-Number</b>               |        |
| · <b>DOT, IMDG, IATA</b>         | UN1263 |
| · <b>UN proper shipping name</b> |        |
| · <b>DOT</b>                     | Paint  |
| · <b>IMDG, IATA</b>              | PAINT  |

(Contd. on page 10)

-USA-

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 9)

· **Transport hazard class(es)**

· **DOT**



· **Class** 3 Flammable liquids  
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**  
· **DOT, IMDG, IATA** II

· **Environmental hazards:**  
· **Marine pollutant:** No

· **Special precautions for user** Warning: Flammable liquids  
· **Danger code (Kemler):** 33  
· **EMS Number:** F-E,S-E

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

· **IMDG**  
· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN1263, Paint, 3, II

USA

(Contd. on page 11)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 10)

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

67-64-1 acetone

I

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

67-64-1 acetone

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 12)

## Safety Data Sheet acc. to OSHA HCS

Printing date 05/05/2015

Reviewed on 05/05/2015

**Trade name: SX01 ADHESION PROMOTER**

(Contd. of page 11)

· **Hazard symbols:**



*Harmful  
Highly flammable*

· **Hazard-determining components of labeling:**

*xylene  
ethylbenzene*

· **Risk phrases:**

*Highly flammable.  
Harmful by inhalation and in contact with skin.  
Irritating to eyes and skin.*

· **Safety phrases:**

*Keep out of the reach of children.  
Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Wear suitable protective clothing and gloves.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** *Environment protection department.*

· **Contact:** *Mr. Roberts*

· **Date of preparation / last revision** *05/05/2015 / -*

· **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*Flam. Liq. 2: Flammable liquids, Hazard Category 2*

*Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2*

*Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A*

*Carc. 2: Carcinogenicity, Hazard Category 2*

*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*