





1 Identification of the substance/mixture and of the company/undertaking

- . **Product identifier**
- . **Trade name:** 613 DEEP BLUE
- . **Article number:** 613
- . **Details of the supplier of the safety data sheet**
- . **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- . **Information department:** Product safety department
- . **Emergency telephone number:** 1-800-535-5053

2 Hazards identification

- . **Classification of the substance or mixture**
- . **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**  
Flammable. Harmful to aquatic organisms. Vapours may cause drowsiness and dizziness.
- . **Information concerning particular hazards for human and environment:**  
The product has to be labelled due to the calculation procedure of international guidelines.
- . **Classification system:**  
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.
- . **Label elements**
- . **Labelling according to EU guidelines:**  
The product has been classified and marked in accordance with directives on hazardous materials.
- . **Risk phrases:**  
Flammable.  
Harmful to aquatic organisms.  
Vapours may cause drowsiness and dizziness.
- . **Safety phrases:**  
Keep out of the reach of children.  
Avoid contact with eyes.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
If swallowed, seek medical advice immediately and show this container or label.
- . **Special labelling of certain preparations:**  
Contains neodecansäureglycidylester, 2-hydroxyethyl methacrylate, methyl methacrylate. May produce an allergic reaction.
- . **Classification system:**
- . **NFPA ratings (scale 0 - 4)**  


Health = 0  
Fire = 3  
Reactivity = 0
- . **HMIS-ratings (scale 0 - 4)**  


HEALTH 0 Health = 0  
FIRE 3 Fire = 3  
REACTIVITY 0 Reactivity = 0
- . **Other hazards**
- . **Results of PBT and vPvB assessment**
- . **PBT:** Not applicable.



Trade name: 613 DEEP BLUE

. vPvB: Not applicable.

(Contd. of page 1)

### 3 Composition/information on ingredients

. **Chemical characterization: Mixtures**

. **Description:** Mixture of the substances listed below with nonhazardous additions.

. **Dangerous components:**

123-86-4	n-butyl acetate	25-50%
1330-20-7	xylene	2.5-10%
108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
80-62-6	methyl methacrylate	½ 2.5%
26761-45-5	neodecansäureglycidylester	½ 2.5%
868-77-9	2-hydroxyethyl methacrylate	½ 2.5%

### 4 First aid measures

. **Description of first aid measures**

. **After inhalation:** Supply fresh air; consult doctor in case of complaints.

. **After skin contact:** Generally the product does not irritate the skin.

. **After eye contact:** Rinse opened eye for several minutes under running water.

. **After swallowing:** If symptoms persist consult doctor.

. **Information for doctor:**

. **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

. **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Firefighting measures

. **Extinguishing media**

. **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

. **For safety reasons unsuitable extinguishing agents:** Water with full jet

. **Special hazards arising from the substance or mixture** No further relevant information available.

. **Advice for firefighters**

. **Protective equipment:** No special measures required.

### 6 Accidental release measures

. **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

. **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

. **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

. **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

USA



**Trade name: 613 DEEP BLUE**

(Contd. of page 2)

See Section 13 for disposal information.

### 7 Handling and storage

- . **Handling:**
- . **Precautions for safe handling** No special precautions are necessary if used correctly.
- . **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- . **Conditions for safe storage, including any incompatibilities**
- . **Storage:**
- . **Requirements to be met by storerooms and receptacles:** No special requirements.
- . **Information about storage in one common storage facility:** Not required.
- . **Further information about storage conditions:** Keep receptacle tightly sealed.
- . **Storage class:** 3
- . **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- . **Additional information about design of technical systems:** No further data; see item 7.
- . **Control parameters**

. **Components with limit values that require monitoring at the workplace:**

**123-86-4 n-butyl acetate**

PEL	710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 713 mg/m <sup>3</sup> , 150 ppm

**1330-20-7 xylene**

PEL	435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	50 ppm
------	--------

- . **Additional information:** The lists that were valid during the creation were used as basis.

- . **Exposure controls**
- . **Personal protective equipment:**
- . **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- . **Breathing equipment:** Not required.
- . **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

. **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)



**Trade name: 613 DEEP BLUE**

(Contd. of page 3)

**. Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**. Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

**. Information on basic physical and chemical properties**

**. General Information**

**. Appearance:**

**Form:** Liquid

**Color:** Blue

**. Odor:** Characteristic

**. Odour threshold:** Not determined.

**. pH-value:** Not determined.

**. Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** 124°C (255 °F)

**. Flash point:** 25°C (77 °F)

**. Flammability (solid, gaseous):** Not applicable.

**. Ignition temperature:** 315°C (599 °F)

**. Decomposition temperature:** Not determined.

**. Auto igniting:** Product is not selfigniting.

**. Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**. Explosion limits:**

**Lower:** 1.2 Vol %

**Upper:** 7.5 Vol %

**. Vapor pressure at 20°C (68 °F):** 10.7 hPa (8 mm Hg)

**. Density at 20°C (68 °F):** 1.001 g/cm<sup>3</sup> (8.353 lbs/gal)

**. Relative density** Not determined.

**. Vapour density** Not determined.

**. Evaporation rate** Not determined.

**. Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

**. Partition coefficient (n-octanol/water):** Not determined.

**. Viscosity:**

**Dynamic:** Not determined.

**Kinematic:** Not determined.

**. Solvent content:**

**Organic solvents:** 46.5 %

**VOC content:** 46.5 %

465.9 g/l / 3.89 lb/gl

**Solids content:** 52.8 %

(Contd. on page 5)



**Trade name: 613 DEEP BLUE**

(Contd. of page 4)

**. Other information** No further relevant information available.

### 10 Stability and reactivity

- . **Reactivity**
- . **Chemical stability**
- . **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- . **Possibility of hazardous reactions** No dangerous reactions known.
- . **Conditions to avoid** No further relevant information available.
- . **Incompatible materials:** No further relevant information available.
- . **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- . **Information on toxicological effects**
- . **Acute toxicity:**
- . **LD/LC50 values that are relevant for classification:**

#### 1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- . **Primary irritant effect:**
- . **on the skin:** No irritant effect.
- . **on the eye:** No irritating effect.
- . **Sensitization:** No sensitizing effects known.
- . **Additional toxicological information:**

- . **Carcinogenic categories**

- . **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
80-62-6	methyl methacrylate	3
100-41-4	ethylbenzene	2B

- . **NTP (National Toxicology Program)**

None of the ingredients is listed.

### 12 Ecological information

- . **Toxicity**
- . **Aquatic toxicity:** No further relevant information available.
- . **Persistence and degradability** No further relevant information available.
- . **Behavior in environmental systems:**
- . **Bioaccumulative potential** No further relevant information available.
- . **Mobility in soil** No further relevant information available.
- . **Ecotoxic effects:**
- . **Remark:** Harmful to fish

(Contd. on page 6)



**Trade name: 613 DEEP BLUE**

(Contd. of page 5)

**. Additional ecological information:**

**. General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

**. Results of PBT and vPvB assessment**

**. PBT:** Not applicable.

**. vPvB:** Not applicable.

**. Other adverse effects** No further relevant information available.

**13 Disposal considerations**

**. Waste treatment methods**

**. Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**. Uncleaned packagings:**

**. Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

**. UN-Number**

**. DOT, ADR, IMDG, IATA** UN1263

**. UN proper shipping name**

**. DOT, IMDG, IATA** PAINT  
**. ADR** 1263 PAINT

**. Transport hazard class(es)**

**. DOT**



**. Class** 3 Flammable liquids.  
**. Label** 3

**. ADR, IMDG, IATA**



**. Class** 3 Flammable liquids  
**. Label** 3

**. Packing group**

**. DOT, ADR, IMDG, IATA** III

**. Environmental hazards:**

**. Marine pollutant:** No

**. Special precautions for user**

Warning: Flammable liquids

**. EMS Number:**

F-E,S-E

(Contd. on page 7)



**Trade name: 613 DEEP BLUE**

(Contd. of page 6)

**. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

**15 Regulatory information**

**. Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**. Sara**

**. Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

**. Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
-----------	--------

80-62-6	methyl methacrylate
---------	---------------------

100-41-4	ethylbenzene
----------	--------------

**. TSCA (Toxic Substances Control Act):**

All ingredients are listed.

**. Proposition 65**

**. Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

**. Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**. Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**. Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**. Carcinogenic categories**

**. EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

80-62-6	methyl methacrylate	NL
---------	---------------------	----

100-41-4	ethylbenzene	D
----------	--------------	---

**. TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
-----------	--------	----

80-62-6	methyl methacrylate	A4
---------	---------------------	----

100-41-4	ethylbenzene	A3
----------	--------------	----

77-58-7	dibutyltin dilaurate	A4
---------	----------------------	----

**. NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**. OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**. Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

**. Risk phrases:**

Flammable.

Harmful to aquatic organisms.

Vapours may cause drowsiness and dizziness.

**. Safety phrases:**

Keep out of the reach of children.

(Contd. on page 8)



# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/07/2012

Reviewed on 05/03/2012

**Trade name: 613 DEEP BLUE**

(Contd. of page 7)

*Avoid contact with eyes.*

*Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.*

*If swallowed, seek medical advice immediately and show this container or label.*

**. Special labeling of certain preparations:**

*Contains neodecansäureglycidylester, 2-hydroxyethyl methacrylate, methyl methacrylate. May produce an allergic reaction.*

**. Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

**. Department issuing MSDS:** *Product safety department*

**. Contact:** *Ms. Topaljikian*

USA