Printing date 10/14/2015

Reviewed on 05/02/2015

1 Identification

- · Product identifier
- Trade name: 622 MIXING GREEN
- · Article number: 622
- · Details of the supplier of the safety data sheet

Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product safety department

· Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

· Hazard-determining components of labeling:

n-butyl acetate Solvent naphtha (petroleum), light arom. methyl methacrylate 2,3-epoxypropyl neodecanoate 2-hydroxyethyl methacrylate

Hazard statements

Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness.


(Contd. on page 2)

[–] US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN



• **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-butyl acetate	25-50%
1330-20-7	xylene	10-25%
108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
80-62-6	methyl methacrylate	½ 2.5%
	(Cont	d. on page 3)

GENERAL

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

26761-45-5 2,3-epoxypropyl neodecanoate	
	½ 2.5%
868-77-9 2-hydroxyethyl methacrylate	½ 2.5%

4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

(Contd. on page 4)

US -

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

- PELLong-term value: 710 mg/m³, 150 ppmRELShort-term value: 950 mg/m³, 200 ppm
- Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

1330-20-7 xylene

- PEL Long-term value: 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
- TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL Long-term value: 50 ppm

Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

• Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

· Personal protective equipment:

- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to

Printing date 10/14/2015

RABUER

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

(Contd. of page 4)

- be checked prior to the application.
- · Penetration time of glove material
- The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- · Eye protection:



Tightly sealed goggles

 Information on basic physical and General Information 	chemical properties
· Appearance:	
Form:	Liquid
Color:	Green
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C (255 °F)
· Flash point:	25 °C (77 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	0.98 g/cm³ (8.178 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic: Kinematic:	Not determined. Not determined.

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

	ge 5)
43.6 %	
43.6 %	
426.8 g/l / 3.56 lb/gl	
426.8 g/l / 3.56 lb/gl	
55.8 %	
No further relevant information available.	
	43.6 % 426.8 g/l / 3.56 lb/gl 426.8 g/l / 3.56 lb/gl 55.8 %

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:	
--	--

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

· Primary irritant effect:

- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

· Additional toxicological information:

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)		
1330-20-7		3	
80-62-6	methyl methacrylate	3	
100-41-4	ethylbenzene	2B	
· NTP (National Toxicology Program)			
None of the	e ingredients is listed.		
	(Contd. on p	age 7)	

US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1263	
· UN proper shipping name		
DOT	Paint	
ADR	1263 Paint	
· IMDG, IATA	PAINT	

Printing date 10/14/2015

GENERAL

Reviewed on 05/02/2015

	(Contd. of page 7)
· Transport hazard class(es)	
· DOT	
Class	3 Flammable liquids
· Label	3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
	3
 Packing group DOT, ADR, IMDG, IATA 	111
 Environmental hazards: Marine pollutant: 	No
 Special precautions for user EMS Number: 	Warning: Flammable liquids F-E, <u>S-E</u>
 Transport in bulk according to Annex II MARPOL73/78 and the IBC Code 	of Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
 ADR Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
·IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1
 Excepted quantities (EQ) 	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1263, Paint, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

US -

Printing date 10/14/2015

GENERAL

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

Section 31	3 (Specific toxic chemical listings):	(Contd. of pag
1330-20-7		
	methyl methacrylate	
	ethylbenzene	
	ic Substances Control Act):	
•	n-butyl acetate	
1330-20-7		
	2-methoxy-1-methylethyl acetate	
	Solvent naphtha (petroleum), light arom.	
	methyl methacrylate	
	2,3-epoxypropyl neodecanoate	
	2-hydroxyethyl methacrylate	
	methacrylic acid	
	dibutyltin dilaurate	
	ZINC 2-ETHYLEXANOATE	
	ethylbenzene	
	n-butyl methacrylate	
	Solvent naphtha (petroleum), medium aliph.	
	octamethylcyclotetrasiloxane	
Propositio		
•	known to cause cancer:	
	thylbenzene	
	known to cause reproductive toxicity for females:	
	ingredients is listed.	
	known to cause reproductive toxicity for males:	
	ingredients is listed.	
	known to cause developmental toxicity:	
	ingredients is listed.	
None or the	ingreulents is listed.	
-	nic categories	
-	onmental Protection Agency)	
1330-20-7	-	Ι
	methyl methacrylate	E, 1
100-41-4	ethylbenzene	D
· TLV (Thres	hold Limit Value established by ACGIH)	
1330-20-7	xylene	
80-62-6	methyl methacrylate	
77-58-7	dibutyItin dilaurate	
100-41-4	ethylbenzene	
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
	ingredients is listed.	
None of the		

-US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

(Contd. of page 9) · Hazard pictograms GHS02 GHS07 · Signal word Warning Hazard-determining components of labeling: n-butvl acetate Solvent naphtha (petroleum), light arom. methyl methacrylate 2.3-epoxypropyl neodecanoate 2-hydroxyethyl methacrylate Hazard statements Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves / eye protection / face protection. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower. Specific treatment (see on this label). IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Take off contaminated clothing and wash it before reuse. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Ms. Topaljikian

· Date of preparation / last revision 10/14/2015 / -

(Contd. on page 11)



US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 622 MIXING GREEN

	(Contd. of page 10)
 Abbreviations and acronyms: 	
RID: Règlement international concernant le transport des marchandises dangereuses par che Concerning the International Transport of Dangerous Goods by Rail)	emin de fer (Regulations
ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Ag International Carriage of Dangerous Goods by Road)	greement concerning the
IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation	
IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative Flam. Lig. 3: Flammable liquids, Hazard Category 3	
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2	
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3	
	US

