



1 Identification

- **Product identifier**
- **Trade name:** 655 RUBY RED
- **Article number:** 655
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

n-butyl acetate

Solvent naphtha (petroleum), light arom.

- **Hazard statements**

Flammable liquid and vapor.

May cause drowsiness or dizziness.

- **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

(Contd. on page 2)



Trade name: 655 RUBY RED

(Contd. of page 1)

Use only outdoors or in a well-ventilated area.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell.
 In case of fire: Use for extinction: CO2, powder or water spray.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	25-50%
1330-20-7	xylene	2.5-10%
108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

US

(Contd. on page 3)



Trade name: 655 RUBY RED

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m ³ , 150 ppm

(Contd. on page 4)



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 655 RUBY RED

(Contd. of page 3)

TLV	Short-term value: (950) NIC-712 mg/m ³ , (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m ³ , (150) NIC-50 ppm
1330-20-7 xylene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
108-65-6 2-methoxy-1-methylethyl acetate	
WEEL	Long-term value: 50 ppm

· **Ingredients with biological limit values:**

1330-20-7 xylene	
BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Breathing equipment:** Not required.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Color:

According to product specification

(Contd. on page 5)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 655 RUBY RED

(Contd. of page 4)

· Odor:	<i>Characteristic</i>
· Odour threshold:	<i>Not determined.</i>
· pH-value:	<i>Not determined.</i>
· Change in condition	
Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>124 °C (255 °F)</i>
· Flash point:	<i>25 °C (77 °F)</i>
· Flammability (solid, gaseous):	<i>Not applicable.</i>
· Ignition temperature:	<i>315 °C (599 °F)</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/vapor mixtures are possible.</i>
· Explosion limits:	
Lower:	<i>1.2 Vol %</i>
Upper:	<i>7.5 Vol %</i>
· Vapor pressure at 20 °C (68 °F):	<i>10.7 hPa (8 mm Hg)</i>
· Density at 20 °C (68 °F):	<i>1.00185 g/cm³ (8.36 lbs/gal)</i>
· Relative density	<i>Not determined.</i>
· Vapour density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with	
Water:	<i>Not miscible or difficult to mix.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
Organic solvents:	<i>45.2 %</i>
Coating VOC content:	<i>45.2 %</i>
	<i>452.6 g/l / 3.78 lb/gl</i>
Material VOC content:	<i>452.6 g/l / 3.78 lb/gl</i>
· Solids content:	<i>54.7 %</i>
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*

(Contd. on page 6)



Trade name: 655 RUBY RED

(Contd. of page 5)

· **Hazardous decomposition products:** *No dangerous decomposition products known.*

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** *No irritant effect.*

· **on the eye:** *No irritating effect.*

· **Sensitization:** *No sensitizing effects known.*

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
80-62-6	methyl methacrylate	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** *No further relevant information available.*

· **Persistence and degradability** *No further relevant information available.*

· **Behavior in environmental systems:**

· **Bioaccumulative potential** *No further relevant information available.*

· **Mobility in soil** *No further relevant information available.*

· **Ecotoxicological effects:**

· **Remark:** *Harmful to fish*

· **Additional ecological information:**

· **General notes:** *Harmful to aquatic organisms*

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

· **Other adverse effects** *No further relevant information available.*

US

(Contd. on page 7)



Printing date 10/14/2015

Reviewed on 05/02/2015



Trade name: 655 RUBY RED

(Contd. of page 6)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

- | | |
|--|---|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1263 |
| · UN proper shipping name | |
| · DOT | Paint |
| · ADR | 1263 Paint |
| · IMDG, IATA | PAINT |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · ADR, IMDG, IATA | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · EMS Number: | F-E,S-E |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L |

(Contd. on page 8)



Trade name: 655 RUBY RED

(Contd. of page 7)

<ul style="list-style-type: none"> · ADR · Excepted quantities (EQ) 	<p>Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN1263, Paint, 3, III</p>

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
80-62-6	methyl methacrylate
872-50-4	N-methyl-2-pyrrolidone
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

872-50-4 N-methyl-2-pyrrolidone

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
80-62-6	methyl methacrylate	E, NL
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
80-62-6	methyl methacrylate	A4
100-41-4	ethylbenzene	A3
77-58-7	dibutyltin dilaurate	A4

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 655 RUBY RED

(Contd. of page 8)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word *Warning*

· Hazard-determining components of labeling:

n-butyl acetate

Solvent naphtha (petroleum), light arom.

· Hazard statements

Flammable liquid and vapor.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Use only outdoors or in a well-ventilated area.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: Ms. Topaljikian

· Date of preparation / last revision 10/14/2015 / -

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 10)



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 655 RUBY RED

(Contd. of page 9)

ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids, Hazard Category 3
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

US