Printing date 10/14/2015

Reviewed on 05/02/2015

1 Identification

- · Product identifier
- · Trade name: 700 CLEAR
- · Article number: 700
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product safety department

• Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2H351 Suspected of causing cancer.STOT RE 2H373 May cause damage to the hearing organs through prolonged or repeated exposure.

GHS07

Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: *n*-butyl acetate *ethylbenzene*
- Hazard statements Flammable liquid and vapor. Causes skin irritation.

(Contd. on page 2)

US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 700 CLEAR



3 Composition/i<u>nformation on ingredients</u>

· Chemical characterization: Mixtures

• **Description:** *Mixture of the substances listed below with nonhazardous additions.*

· Dangerous components:

123-86-4 n-butyl acetate

25-50% (Contd. on page 3)

- US

Printing date 10/14/2015

Trade name: 700 CLEAR

1330-20-7 xylene 10-25% 108-65-6 2-methoxy-1-methylethyl acetate 2.5-10% 100-41-4 ethylbenzene ½ 2.5%		(Con	td. of page 2)
	1330-20-7	xylene	10-25%
100-41-4 ethylbenzene ½ 2.5%	108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
	100-41-4	ethylbenzene	½ 2.5%

4 First-aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 700 CLEAR

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

Control parameters

· Compo	onents with limit values that require monitoring at the workplace:
123-86	-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
1330-2	0-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI
108-65	-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm
100-41	-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm BEI
· Ingred	ients with biological limit values:
1330-2	0-7 xylene
L	(Contd. on page 5)
	US



US

(Contd. on page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 700 CLEAR

BEI	(Contd. of page 4)
DEI	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
100	-41-4 ethylbenzene
BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	Parameter. Sum of manuelic acid and phenyigiyoxylic acid (nonspecific, semi-quantitative)
	-
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)
· Add	litional information: The lists that were valid during the creation were used as basis.
	osure controls
	sonal protective equipment:
	neral protective and hygienic measures:
	p away from foodstuffs, beverages and feed. sh hands before breaks and at the end of work.
	id contact with the eyes and skin.
	athing equipment:
	ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer
	osure use respiratory protective device that is independent of circulating air.
· Pro	tection of hands:
	\mathbf{m}
100	Protective gloves
The	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	to missing tests no recommendation to the glove material can be given for the product/ the
	paration/ the chemical mixture.
	ection of the glove material on consideration of the penetration times, rates of diffusion and the
	radation erial of gloves
	selection of the suitable gloves does not only depend on the material, but also on further marks of
	lity and varies from manufacturer to manufacturer. As the product is a preparation of several
	stances, the resistance of the glove material can not be calculated in advance and has therefore to
	shecked prior to the application.
	etration time of glove material
	exact break through time has to be found out by the manufacturer of the protective gloves and has e observed.
	protection:
_,•	
C	Tightly appled goggles
	Tightly sealed goggles

CENERAL

Printing date 10/14/2015

GENERAL

Reviewed on 05/02/2015

Trade name: 700 CLEAR

(Contd. of page 5)

9 Physical and chemical propert	ies
· Information on basic physical and cl	nemical properties
- General Information	
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition 	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C (255 °F)
· Flash point:	27 °C (81 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
 Explosion limits: 	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
· Density at 20 °C (68 °F):	0.955 g/cm³ (7.969 lbs/gal)
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
 Solubility in / Miscibility with 	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	71.1 %
Coating VOC content:	71.1 %
Material VOC content:	678.7 g/l / 5.66 lb/gl 678.7 g/l / 5.66 lb/gl
Solids content:	28.9 %
· Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 7)

US

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 700 CLEAR

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

1 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)

Dermal LD50 2000 mg/kg (rabbit)

- Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Carcinogenic categories

·Carcinoge	and categories	
•	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 700 CLEAR

· Other adverse effects No further relevant information available.

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1263	
 · UN proper shipping name · DOT · ADR · IMDG, IATA 	Paint 1263 Paint PAINT	
· Transport hazard class(es)		
· DOT		
Class Label	3 Flammable liquids 3	
· ADR, IMDG, IATA		
Class	3 Flammable liquids	
	3	
 Packing group DOT, ADR, IMDG, IATA 	III	
 Environmental hazards: Marine pollutant: 	No	
 Special precautions for user EMS Number: 	Warning: Flammable liquids F-E, <u>S-E</u>	
· Transport in bulk according to Annex	II of	



Printing date 10/14/2015

GENERAL

Reviewed on 05/02/2015

Trade name: 700 CLEAR

	(Contd. of page 8
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	
 Excepted quantities (EQ) 	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
 Limited quantities (LQ) 	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1263, Paint, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 35	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· TSCA (To	xic Substances Control Act):	
All ingredie	ents are listed.	
· Propositio		
	s known to cause cancer:	
100-41-4	ethylbenzene	
	s known to cause reproductive toxicity for females:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of the	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of the	e ingredients is listed.	
· Carcinoge	nic categories	
· EPA (Envi	ronmental Protection Agency)	
1330-20-7	-	Ι
100-41-4	ethylbenzene	D
· TLV (Thre	shold Limit Value established by ACGIH)	
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
	(Contd. on pa	
		— U

Printing date 10/14/2015

CENERAL

Reviewed on 05/02/2015

Trade name: 700 CLEAR

NIOSH-Ca (National Institute for Occupational Safety and Health)	(Contd. of page
None of the ingredients is listed.	
GHS label elements	
The product is classified and labeled according to the Globally Harmonized Syste	em (GHS)
Hazard pictograms	
$\wedge \wedge \wedge$	
$\langle \emptyset \rangle \langle \downarrow \rangle \langle I \rangle$	
GHS02 GHS07 GHS08	
Signal word Warning	
Hazard-determining components of labeling:	
n-butyl acetate	
ethylbenzene	
Hazard statements	
Flammable liquid and vapor.	
Causes skin irritation.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
May cause damage to the hearing organs through prolonged or repeated exposu	IIE.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wear protective gloves / eye protection / face protection.	
Ground/bond container and receiving equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.	Rinse skin with wat
shower.	
Specific treatment (see on this label).	
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortabl	le for breathing.
Call a poison center/doctor if you feel unwell.	
IF exposed or concerned: Get medical advice/attention.	
If skin irritation occurs: Get medical advice/attention.	
Get medical advice/attention if you feel unwell.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Take off contaminated clothing and wash it before reuse.	
Store locked up.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	anal ragulations
Dispose of contents/container in accordance with local/regional/national/internati	
Chemical safety assessment: A Chemical Safety Assessment has not been ca	rried out.

(Contd. on page 11)

(Contd. of page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 700 CLEAR

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Ms. Topaljikian
- Date of preparation / last revision 10/14/2015 / -

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids, Hazard Category 3 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Carc. 2: Carcinogenicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2