



1 Identification

- **Product identifier**
- **Trade name:** 772 PEARL WHITE
- **Article number:** 772
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. SAL
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- **Information department:** Product safety department
- **Emergency telephone number:** 1-800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

n-butyl acetate

ethylbenzene

Solvent naphtha (petroleum), light arom.

- **Hazard statements**

Flammable liquid and vapor.

Suspected of causing cancer.



Trade name: 772 PEARL WHITE

(Contd. of page 1)

May cause drowsiness or dizziness.
May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves / eye protection / face protection.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Use only outdoors or in a well-ventilated area.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a poison center/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
In case of fire: Use for extinction: CO2, powder or water spray.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



Other hazards

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

123-86-4	<i>n</i> -butyl acetate	50-100%
1330-20-7	xylene	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
100-41-4	ethylbenzene	½ 2.5%

US

(Contd. on page 3)



Trade name: 772 PEARL WHITE

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** *Supply fresh air; consult doctor in case of complaints.*
- **After skin contact:** *Generally the product does not irritate the skin.*
- **After eye contact:** *Rinse opened eye for several minutes under running water.*
- **After swallowing:** *If symptoms persist consult doctor.*
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** *CO₂, sand, extinguishing powder. Do not use water.*
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **Special hazards arising from the substance or mixture** *No further relevant information available.*
- **Advice for firefighters**
- **Protective equipment:** *No special measures required.*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents*
- **Reference to other sections**
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** *No special precautions are necessary if used correctly.*
- **Information about protection against explosions and fires:**
*Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:**
*Keep receptacle tightly sealed.
Protect from heat and direct sunlight.*
- **Storage class:** 3

(Contd. on page 4)



Trade name: 772 PEARL WHITE

(Contd. of page 3)

· **Specific end use(s)** *No further relevant information available.*

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** *No further data; see item 7.*

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m ³ , (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m ³ , (150) NIC-50 ppm

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

· **Ingredients with biological limit values:**

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** *The lists that were valid during the creation were used as basis.*

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** *Wash hands before breaks and at the end of work.*

· **Breathing equipment:** *Not required.*

(Contd. on page 5)



Trade name: 772 PEARL WHITE

(Contd. of page 4)

- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	<i>Fluid</i>
Color:	<i>According to product specification</i>
· Odor:	<i>Characteristic</i>
· Odour threshold:	<i>Not determined.</i>

- **pH-value:** *Not determined.*

- **Change in condition**

Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>124 °C (255 °F)</i>

- **Flash point:** *27 °C (81 °F)*

- **Flammability (solid, gaseous):** *Not applicable.*

- **Ignition temperature:** *370 °C (698 °F)*

- **Decomposition temperature:** *Not determined.*

- **Auto igniting:** *Product is not selfigniting.*

- **Danger of explosion:** *Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.*

- **Explosion limits:**

Lower:	<i>1.2 Vol %</i>
Upper:	<i>7.5 Vol %</i>

- **Vapor pressure at 20 °C (68 °F):** *10.7 hPa (8 mm Hg)*

- **Density at 20 °C (68 °F):** *0.965 g/cm³ (8.053 lbs/gal)*

- **Relative density** *Not determined.*

- **Vapour density** *Not determined.*

(Contd. on page 6)



Trade name: 772 PEARL WHITE

(Contd. of page 5)

· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with Water:	<i>Not miscible or difficult to mix.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
Organic solvents:	72.0 %
Coating VOC content:	72.0 %
	694.7 g/l / 5.80 lb/gl
Material VOC content:	694.7 g/l / 5.80 lb/gl
· Solids content:	28.0 %
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** *No irritant effect.*
- **on the eye:** *No irritating effect.*
- **Sensitization:** *No sensitizing effects known.*
- **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

(Contd. on page 7)



Trade name: 772 PEARL WHITE

(Contd. of page 6)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** *No further relevant information available.*

· **Persistence and degradability** *No further relevant information available.*

· **Behavior in environmental systems:**

· **Bioaccumulative potential** *No further relevant information available.*

· **Mobility in soil** *No further relevant information available.*

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** *Not applicable.*

· **vPvB:** *Not applicable.*

· **Other adverse effects** *No further relevant information available.*

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA** *UN1263*

· **UN proper shipping name**

· **DOT** *Paint*

· **ADR** *1263 Paint*

· **IMDG, IATA** *PAINT*

· **Transport hazard class(es)**

· **DOT**



· **Class** *3 Flammable liquids*

(Contd. on page 8)



Safety Data Sheet


acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 772 PEARL WHITE

(Contd. of page 7)

· Label	3
· ADR, IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1263, Paint, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

7664-38-2 phosphoric acid

· TSCA (Toxic Substances Control Act):

123-86-4 n-butyl acetate

1330-20-7 xylene

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 772 PEARL WHITE

(Contd. of page 8)

64742-95-6	Solvent naphtha (petroleum), light arom.
100-41-4	ethylbenzene
107-98-2	1-methoxy-2-propanol
108-65-6	2-methoxy-1-methylethyl acetate
7664-38-2	phosphoric acid

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

n-butyl acetate
ethylbenzene
Solvent naphtha (petroleum), light arom.

· **Hazard statements**

Flammable liquid and vapor.
Suspected of causing cancer.
May cause drowsiness or dizziness.
May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves / eye protection / face protection.
Ground/bond container and receiving equipment.

(Contd. on page 10)



Trade name: 772 PEARL WHITE

(Contd. of page 9)

Use only non-sparking tools.
Take precautionary measures against static discharge.
Use only outdoors or in a well-ventilated area.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a poison center/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** Ms. Topaljikian

• **Date of preparation / last revision** 10/14/2015 / -

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2