

Printing date 10/14/2015 Reviewed on 05/02/2015

1 Identification

· Product identifier

· Trade name: 775 FINE RUSSET

· Article number: 775

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623

Beirut LEBANON

info@generalpaint.biz

· Information department: Product safety department · Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

n-butyl acetate ethylbenzene

Solvent naphtha (petroleum), light arom.

· Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

(Contd. on page 2)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

(Contd. of page 1)

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *0 Fire = 3

Reactivity = 0

- Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-butyl acetate	50-100%
1330-20-7	xylene	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
100-41-4	ethylbenzene	½ 2.5%

03



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Do not flush with water or aqueous cleansing agents
- Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Storage class: 3

(Contd. on page 4)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

(Contd. of page 3)

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

- PEL Long-term value: 710 mg/m³, 150 ppm
- REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
- TLV Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

1330-20-7 xylene

- PEL Long-term value: 435 mg/m³, 100 ppm
- REL Short-term value: 655 mg/m³, 150 ppm
 - Long-term value: 435 mg/m³, 100 ppm
- TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI

100-41-4 ethylbenzene

- PEL Long-term value: 435 mg/m³, 100 ppm
- REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
- TLV Long-term value: 87 mg/m³, 20 ppm

BEI

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

(Contd. on page 5)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

(Contd. of page 4)

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical proper	ties
Information on basic physical and confidence of the confidence of	chemical properties
· Appearance: Form:	Liquid
Color:	Red
· Odor:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124 °C (255 °F)
· Flash point:	27 °C (81 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C (698 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F): Relative density	0.962 g/cm³ (8.028 lbs/gal) Not determined. Not determined.
· Vapour density	Not determined.

(Contd. on page 6)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

		(Contd. of page
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/	water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	72.0 %	
Coating VOC content:	72.0 %	
•	692.6 g/l / 5.78 lb/gl	
Material VOC content:	692.6 g/l / 5.78 lb/gl	
Solids content:	28.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:				
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6800 mg/kg (rat)		
Dermal	LD50	>3400 mg/kg (rab)		
Inhalative	LC50/4 h	>10.2 mg/l (rat)		

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
1330-20-	7 xylene	3
100-41-	4 ethylbenzene	2B

(Contd. on page 7)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

 · DOT
 Paint

 · ADR
 1263 Paint

 · IMDG, IATA
 PAINT

- · Transport hazard class(es)
- · DOT



· Class 3 Flammable liquids

(Contd. on page 8)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

(Contd. of page 7) 3 · Label · ADR, IMDG, IATA · Class 3 Flammable liquids · Label · Packing group DOT, ADR, IMDG, IATA III· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · EMS Number: F-E,S-E · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: Quantity limitations On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L · ADR Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · IMDG · Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

15 Regulatory information

· UN "Model Regulation":

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture

UN1263, Paint, 3, III

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

100-41-4 ethylbenzene

7664-38-2 phosphoric acid

· TSCA (Toxic Substances Control Act):

123-86-4 n-butyl acetate

1330-20-7 xylene

(Contd. on page 9)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

	(Contd. of page 8)
	Solvent naphtha (petroleum), light arom.
	ethylbenzene
	1-methoxy-2-propanol
	2-methoxy-1-methylethyl acetate
	phosphoric acid
Proposition 65	

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

· EPA (Envi	ronmental Protection Agency)	
1330-20-7	xylene	1
100-41-4	ethylbenzene	D
· TLV (Thre	shold Limit Value established by ACGIH)	
1330-20-7	xylene	A4
100 41 4	ethylbenzene	A3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

n-butyl acetate ethylbenzene

Solvent naphtha (petroleum), light arom.

· Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

(Contd. on page 10)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 775 FINE RUSSET

(Contd. of page 9)

Use only non-sparking tools.

Take precautionary measures against static discharge.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Ms. Topaljikian
- · Date of preparation / last revision 10/14/2015 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2