

Printing date 10/14/2015 Reviewed on 05/02/2015

1 Identification

· Product identifier

· Trade name: 776 SPARKLE RED

· Article number: 776

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: General Paint Co. SAL

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

· Information department: Product safety department · Emergency telephone number: 1-800-535-5053

Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

n-butyl acetate

ethylbenzene

Solvent naphtha (petroleum), light arom.

· Hazard statements

Flammable liquid and vapor.

(Contd. on page 2)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

(Contd. of page 1)

Causes skin irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1

Fire = 3

- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · vPvB: Not applicable.

Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- Dangerous components:

123-86-4 n-butyl acetate

25-50%

(Contd. on page 3)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

	(Con	td. of page 2)
1330-20-7	xylene	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
108-65-6	2-methoxy-1-methylethyl acetate	½ 2.5%
100-41-4	ethylbenzene	½ 2.5%

4 First-aid measures

- · Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

See Section 13 for disposal information.

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Contr	oi parameters			
· Components with limit values that require monitoring at the workplace:				
123-86	123-86-4 n-butyl acetate			
PEL	Long-term value: 710 mg/m³, 150 ppm			
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm			
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm			
1330-2	20-7 xylene			
PEL	Long-term value: 435 mg/m³, 100 ppm			
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm			
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI			
108-6	-6 2-methoxy-1-methylethyl acetate			
WEEL	Long-term value: 50 ppm			
100-41-4 ethylbenzene				
PEL	Long-term value: 435 mg/m³, 100 ppm			
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm			
TLV	Long-term value: 87 mg/m³, 20 ppm BEI			

(Contd. on page 5)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

(Contd. of page 4)

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

_

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

· Eye protection:

(Contd. of page 5)



Tightly sealed goggles

Physical and chemical prope	rties	
· Information on basic physical and chemical properties · General Information		
· Appearance: Form:	Liquid	
Color:	Red	
· Odor:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	124 °C (255 °F)	
· Flash point:	27 °C (81 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	370 °C (698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.	
· Explosion limits:		
Lower:	1.1 Vol %	
Upper:	7.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)	
· Density at 20 °C (68 °F):	0.9692 g/cm³ (8.088 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:	Maria de la	
Dynamic: Kinematic:	Not determined.	
	Not determined.	
· Solvent content:	72.5.0/	
Organic solvents: Coating VOC content:	73.5 % 73.5 %	
Southing 100 content.	73.3 % 712.2 g/l / 5.94 lb/gl	

(Contd. on page 7)

(Contd. of page 6)



Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

Material VOC content: 712.2 g/l / 5.94 lb/gl

Solids content: 26.5 %

No further relevant information available. · Other information

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 v	· LD/LC50 values that are relevant for classification:		
1330-20-7	1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
64742-95-	6 Solvent	naphtha (petroleum), light arom.	
Oral	LD50	>6800 mg/kg (rat)	
Dermal	LD50	>3400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
1330-20-7 xylene	3	
100-41-4 ethylbenzene	2B	
· NTP (National Toxicology Program)		
None of the ingredients is listed		

None of the ingrealents is listea.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

(Contd. of page 7)

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- General notes: Harmful to aquatic organisms
 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

		N 1 -		ber
	NI-	NI	ım	nor

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

- · Transport hazard class(es)
- · DOT



· Label 3

· ADR



· Class 3 Flammable liquids

(Contd. on page 9)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

	(Contd. of page
Label	3
· IMDG, IATA	
· Label	3
· Packing group · DOT, ADR, IMDG, IATA	III
Environmental hazards:Marine pollutant:	No
Special precautions for userEMS Number:	<i>Warning: Flammable liquids</i> F-E, <u>S-E</u>
 Transport in bulk according to Annex II MARPOL73/78 and the IBC Code 	of Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDGLimited quantities (LQ)Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN1263, Paint, 3, III

15 Regulatory information

None of the ingredients is listed.

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture

Sai	ra

Gara	
· Section 355 (extremely hazardous substances):	

· Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
100-41-4	ethylbenzene
7664-38-2	phosphoric acid

· TSCA (Toxic Substances Control Act):

123-86-4	n-butyl acetate
1330-20-7	xylene
9004-36-8	cellulose acetate butyrate
	(Contd. on page 1)

(Contd. on page 10)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

	(Contd. of page 9)
	Solvent naphtha (petroleum), light arom.
108-65-6	2-methoxy-1-methylethyl acetate
	ethylbenzene
107-98-2	1-methoxy-2-propanol
	phosphoric acid
	propane-1,2-diol
78-83-1	butanol

· Proposition 65

· Chemicals known to cause cancer: 100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

•	,	
1330-20-7	xylene A4	
100-41-4	ethylbenzene A3	

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

n-butyl acetate

ethylbenzene

Solvent naphtha (petroleum), light arom.

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 11)



Printing date 10/14/2015 Reviewed on 05/02/2015

Trade name: 776 SPARKLE RED

(Contd. of page 10)

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Ms. Topaljikian
- Date of preparation / last revision 10/14/2015 / -
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

LD50. Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2