Printing date 10/14/2015

Reviewed on 05/02/2015

1 Identification

- · Product identifier
- · Trade name: 875 XIRALLIC RED
- · Article number: 875
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: General Paint Co. SAL P.O. Box 7623 Beirut LEBANON info@generalpaint.biz

· Information department: Product safety department

• Emergency telephone number: 1-800-535-5053

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2H351 Suspected of causing cancer.STOT RE 2H373 May cause damage to the hearing organs through prolonged or repeated exposure.



STOT SE 3 H336 May cause drowsiness or dizziness.

Label elements

 GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
 Hazard pictograms



· Signal word Warning

- Hazard-determining components of labeling: n-butyl acetate ethylbenzene Solvent naphtha (petroleum), light arom.
- Hazard statements
 Flammable liquid and vapor.
 Suspected of causing cancer.

(Contd. on page 2)

US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

	(Contd. of page 1)
May cause drowsiness or dizziness.	
May cause damage to the hearing organs through prolonged or repeated exposure.	
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves / eye protection / face protection.	
Ground/bond container and receiving equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Use only outdoors or in a well-ventilated area.	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse	skin with water/
shower.	
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for b	reathina.
Call a poison center/doctor if you feel unwell.	0
IF exposed or concerned: Get medical advice/attention.	
Get medical advice/attention if you feel unwell.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store locked up.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Dispose of contents/container in accordance with local/regional/national/international re	gulations.
Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 0	
$\frac{3}{\text{Fire}} = 3$	
0 0 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
HEALTH * Health = *0	
FIRE 3 Fire = 3	
$\frac{1}{\text{Reactivity}} = 0$	
KEACHVITI 0 NOUGHVILY = 0	
· Other hazards	
 Results of PBT and vPvB assessment 	
• PBT: Not applicable.	
• vPvB: Not applicable.	
3 Composition/information on ingredients	
5 composition/mitor mation on ingredients	

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:	
123-86-4 n-butyl acetate	50-100%
1330-20-7 xylene	2.5-10%
64742-95-6 Solvent naphtha (petroleum), light arom.	2.5-10%
108-65-6 2-methoxy-1-methylethyl acetate	2.5-10%
· · · ·	(Contd. on page 3)



Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

100-41-4 ethylbenzene

(Contd. of page 2) 1/2 2.5%

4 First-aid measures

- Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Do not flush with water or aqueous cleansing agents
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

US

Printing date 10/14/2015

TERAL

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep receptacle tightly sealed.

· Storage class: 3

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

-	onents with limit values that require monitoring at the workplace:
	6-4 n-butyl acetate
PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm
	Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm
	20-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm
	Long-term value: 434 mg/m ³ , 100 ppm
	BEI
108-6	5-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm
100-4	1-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm
	BEI
Ingree	dients with biological limit values:
1330-2	20-7 xylene
	.5 g/g creatinine
	ledium: urine
7	ime: end of shift
F	Parameter: Methylhippuric acids
100-4	1-4 ethylbenzene
BEI 0	.7 g/g creatinine
	1edium: urine
	ime: end of shift at end of workweek
F	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
- Λ	ledium: end-exhaled air
	Time: not critical
F	Parameter: Ethyl benzene (semi-quantitative)
	ional information: The lists that were valid during the creation were used as basis.
	(Contd. o

(Contd. of page 3)

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

(Contd. of page 4)

- Personal protective equipment:
 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.

Protection of hands:

Exposure controls

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties		
General Information Appearance:		
· Appearance: Form:	Liquid	
Color:	Red	
· Odor:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 124 °C (255 °F)	
· Flash point:	27 °C (81 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	370 °C (698 °F)	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.	
	(Contd. on page 6)	

Printing date 10/14/2015

TERAL

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

		(Contd. of page
· Explosion limits:		
Lower:	1.2 Vol %	
Upper:	7.5 Vol %	
· Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)	
· Density at 20 °C (68 °F):	0.961 g/cm³ (8.02 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	74.3 %	
Coating VOC content:	74.3 %	
5	713.8 g/l / 5.96 lb/gl	
Material VOC content:	713.8 g/l / 5.96 lb/gl	
Solids content:	25.7 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

1330-20-7	' xylene		
Oral	LD50	4300 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
64742-95-	6 Solvent	naphtha (petroleum), light arom.	
Oral	LD50	>6800 mg/kg (rat)	
Dermal	LD50	>3400 mg/kg (rab)	
Inhalative	LC50/4 h	>10.2 mg/l (rat)	
	1		(Contd. on pag

(Contd. of page 6)

3

2B

Safety Data Sheet acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

- · OSHA-Ca (Occupational Safety & Health Administration)
- None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Harmful to aquatic organisms
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 8)

119

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

(Contd. of page 7)

UN-Number	
DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name	
DOT	Paint
ADR	1263 Paint
IMDG, IATA	PAINT
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
ADR, IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number:	Warning: Flammable liquids F-E,S-E
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	0 / 5/
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDC	
IMDG Limited quantities (LQ)	5L
Excepted quantities (EQ)	SL Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per unter packaging: 50 ml Maximum net quantity per outer packaging: 1000 ml



Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

· UN "Model Regulation":

UN1263, Paint, 3, III

15 Regulatory information

Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
1330-20-7 xylene	
100-41-4 ethylbenzene	
7664-38-2 phosphoric acid	
TSCA (Toxic Substances Control Act):	
123-86-4 n-butyl acetate	
1330-20-7 xylene	
64742-95-6 Solvent naphtha (petroleum), light arom.	
108-65-6 2-methoxy-1-methylethyl acetate	
100-41-4 ethylbenzene	
107-98-2 1-methoxy-2-propanol	
7664-38-2 phosphoric acid	
Proposition 65	
Chemicals known to cause cancer:	
100-41-4 ethylbenzene	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
1330-20-7 xylene	1
100-41-4 ethylbenzene	1
TLV (Threshold Limit Value established by ACGIH)	1
1330-20-7 xylene	A
100-41-4 ethylbenzene	A
NIOSH-Ca (National Institute for Occupational Safety and Health)	
	/




(Contd. of page 8)

US

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED



16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

- · Contact: Ms. Topaljikian
- · Date of preparation / last revision 10/14/2015 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 11)

US -

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 875 XIRALLIC RED

 IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids, Hazard Category 3 Carc. 2: Carcinogenicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 	(Contd. of page 10)
0 7	



US -