



### 1 Identification

- **Product identifier**
- **Trade name: 878 XIRALLIC BLUE**
- **Article number: 878**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. SAL  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department: Product safety department**
- **Emergency telephone number: 1-800-535-5053**

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word Warning**

- **Hazard-determining components of labeling:**

n-butyl acetate

ethylbenzene

Solvent naphtha (petroleum), light arom.

- **Hazard statements**

Flammable liquid and vapor.

Suspected of causing cancer.



# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 878 XIRALLIC BLUE

(Contd. of page 1)

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves / eye protection / face protection.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Use only outdoors or in a well-ventilated area.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 0

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*0

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

123-86-4	<i>n</i> -butyl acetate	50-100%
1330-20-7	xylene	2.5-10%
64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-10%
108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%

(Contd. on page 3)

US



Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 878 XIRALLIC BLUE

100-41-4 ethylbenzene

(Contd. of page 2)

½ 2.5%

#### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.

(Contd. on page 4)



**Trade name: 878 XIRALLIC BLUE**

(Contd. of page 3)

- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*
- **Storage class:** 3
- **Specific end use(s)** *No further relevant information available.*

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**123-86-4 n-butyl acetate**

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: (950) NIC-712 mg/m <sup>3</sup> , (200) NIC-150 ppm Long-term value: (713) NIC-238 mg/m <sup>3</sup> , (150) NIC-50 ppm

**1330-20-7 xylene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

**108-65-6 2-methoxy-1-methylethyl acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**100-41-4 ethylbenzene**

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

· **Ingredients with biological limit values:**

**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

- **Additional information:** *The lists that were valid during the creation were used as basis.*

(Contd. on page 5)



**Trade name: 878 XIRALLIC BLUE**

(Contd. of page 4)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
*Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.*
- **Breathing equipment:** *Not required.*
- **Protection of hands:**  
*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves**  
*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material**  
*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*
- **Eye protection:**



*Tightly sealed goggles*

**9 Physical and chemical properties**

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	Blue
- **Odor:** Characteristic
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C (255 °F)
- **Flash point:** 27 °C (81 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 370 °C (698 °F)
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.

(Contd. on page 6)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 878 XIRALLIC BLUE

(Contd. of page 5)

· <b>Explosion limits:</b>	
<b>Lower:</b>	1.2 Vol %
<b>Upper:</b>	7.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	10.7 hPa (8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.962 g/cm <sup>3</sup> (8.028 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	74.3 %
<b>Coating VOC content:</b>	74.3 %
	714.5 g/l / 5.96 lb/gl
<b>Material VOC content:</b>	714.5 g/l / 5.96 lb/gl
<b>Solids content:</b>	25.7 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

(Contd. on page 7)

-US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

Trade name: 878 XIRALLIC BLUE

(Contd. of page 6)

- **Primary irritant effect:**
- **on the skin:** *No irritant effect.*
- **on the eye:** *No irritating effect.*
- **Sensitization:** *No sensitizing effects known.*
- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

*None of the ingredients is listed.*

- **OSHA-Ca (Occupational Safety & Health Administration)**

*None of the ingredients is listed.*

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** *No further relevant information available.*
- **Persistence and degradability** *No further relevant information available.*
- **Behavior in environmental systems:**
- **Bioaccumulative potential** *No further relevant information available.*
- **Mobility in soil** *No further relevant information available.*
- **Ecotoxicological effects:**
- **Remark:** *Harmful to fish*
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water*  
*Do not allow product to reach ground water, water course or sewage system.*  
*Danger to drinking water if even small quantities leak into the ground.*  
*Harmful to aquatic organisms*
- **Results of PBT and vPvB assessment**
- **PBT:** *Not applicable.*
- **vPvB:** *Not applicable.*
- **Other adverse effects** *No further relevant information available.*

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

US




(Contd. on page 8)



Trade name: 878 XIRALLIC BLUE

(Contd. of page 7)

**14 Transport information**

· UN-Number · DOT, ADR, IMDG, IATA	UN1263
· UN proper shipping name · DOT · ADR · IMDG, IATA	Paint 1263 Paint PAINT
· Transport hazard class(es) · DOT	
	
· Class · Label	3 Flammable liquids 3
· ADR	
	
· Class · Label	3 Flammable liquids 3
· IMDG, IATA	
	
· Label	3
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · EMS Number:	Warning: Flammable liquids F-E, <u>S-E</u>
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)





**Trade name: 878 XIRALLIC BLUE**

(Contd. of page 8)

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>Limited quantities (LQ)</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul> | <p align="right">5L<br/>Code: E1<br/>Maximum net quantity per inner packaging: 30 ml<br/>Maximum net quantity per outer packaging: 1000 ml</p> |
| <ul style="list-style-type: none"> <li>· <b>UN "Model Regulation":</b></li> </ul>  | <p>UN1263, Paint, 3, III</p>   |

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

*None of the ingredients is listed.*

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
7664-38-2	phosphoric acid

· **TSCA (Toxic Substances Control Act):**

123-86-4	n-butyl acetate
1330-20-7	xylene
64742-95-6	Solvent naphtha (petroleum), light arom.
108-65-6	2-methoxy-1-methylethyl acetate
100-41-4	ethylbenzene
107-98-2	1-methoxy-2-propanol
7664-38-2	phosphoric acid

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

*None of the ingredients is listed.*

· **Chemicals known to cause reproductive toxicity for males:**

*None of the ingredients is listed.*

· **Chemicals known to cause developmental toxicity:**

*None of the ingredients is listed.*

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

*None of the ingredients is listed.*

(Contd. on page 10)



Trade name: 878 XIRALLIC BLUE

(Contd. of page 9)

· **GHS label elements**

*The product is classified and labeled according to the Globally Harmonized System (GHS).*

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Warning*

· **Hazard-determining components of labeling:**

*n-butyl acetate*

*ethylbenzene*

*Solvent naphtha (petroleum), light arom.*

· **Hazard statements**

*Flammable liquid and vapor.*

*Suspected of causing cancer.*

*May cause drowsiness or dizziness.*

*May cause damage to the hearing organs through prolonged or repeated exposure.*

· **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Do not breathe dust/fume/gas/mist/vapors/spray.*

*Wear protective gloves / eye protection / face protection.*

*Ground/bond container and receiving equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Use only outdoors or in a well-ventilated area.*

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*

*Call a poison center/doctor if you feel unwell.*

*IF exposed or concerned: Get medical advice/attention.*

*Get medical advice/attention if you feel unwell.*

*In case of fire: Use for extinction: CO2, powder or water spray.*

*Store locked up.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** *Product safety department*

· **Contact:** *Ms. Topaljikian*

· **Date of preparation / last revision** *10/14/2015 / -*

· **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

(Contd. on page 11)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2015

Reviewed on 05/02/2015

**Trade name: 878 XIRALLIC BLUE**

(Contd. of page 10)

*DOT: US Department of Transportation*  
*IATA: International Air Transport Association*  
*ACGIH: American Conference of Governmental Industrial Hygienists*  
*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*NFPA: National Fire Protection Association (USA)*  
*HMIS: Hazardous Materials Identification System (USA)*  
*VOC: Volatile Organic Compounds (USA, EU)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*Flam. Liq. 3: Flammable liquids, Hazard Category 3*  
*Carc. 2: Carcinogenicity, Hazard Category 2*  
*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*  
*STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2*

US