

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/01/2015

Reviewed on 04/01/2015


1 Identification

- **Product identifier**
- **Trade name:** *Optimum Compound (TM 2600)*
- **Article number:** 22759
- **Application of the substance / the mixture** Abrasive and polishing compound
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
wesmar Products
10729 47th Ave W
Mukilteo, WA 98275

- **Information department:** Product and Environmental Safety Department
- **Emergency telephone number:** +49 (0) 761 19240

2 Hazard(s) identification

- **Classification of the substance or mixture**
The product is not classified according to the Globally Harmonized System (GHS).
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- **Information concerning particular hazards for human and environment:**
The product has to be labeled due to the calculation procedure of international guidelines.
- **Classification system:**
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**
 Health = 0
Fire = 1
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**

HEALTH	0
FIRE	1
REACTIVITY	0

 Health = 0
Fire = 1
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: Optimum Compound (TM 2600)

(Contd. of page 1)

· Dangerous components:		
1344-28-1	aluminium oxide	10-<25%
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic ⚠ Asp. Tox. 1, H304	10-<25%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy ⚠ Xn R65 R52/53-66 ⚠ Asp. Tox. 1, H304	5-<20%
64742-94-5	Solvent naphtha (petroleum), heavy arom. ⚠ Xn R65; ⚠ N R51/53 R66-67 ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; H227	5-<20%
· Non hazardous ingredients		
9005-65-6	Sorbitan monooleate, ethoxylated	2.5-<10%
7732-18-5	water, distilled, conductivity or of similar purity	40-70%
	Acrylic polymer	1-<5%
102-71-6	2,2',2"-nitrilotriethanol	0.1-<1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
If symptoms persist consult doctor.
Rinse out mouth and then drink plenty of water.
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
Treat according to symptoms.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Water spray, foam, dry powder or carbon dioxide.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** Nitrogen oxides (NOx)
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Keep unnecessary personnel away. Ensure adequate ventilation. Use personal protection recommended in section 8.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: Optimum Compound (TM 2600)

(Contd. of page 2)

- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a well-ventilated place. Storage temperature: between 15 °C and 25 °C.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:	
1344-28-1 aluminium oxide	
PEL	Long-term value: 15*; 15** mg/m ³ *Total dust; ** Respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *Total dust **Respirable fraction
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction
64742-55-8 Distillates (petroleum), hydrotreated light paraffinic	
TWA	Long-term value: 5 mg/m ³

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
Do not eat, drink, smoke or sniff while working.
Keep away from foodstuffs, beverages and feed.

- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: Optimum Compound (TM 2600)

(Contd. of page 3)

Not necessary if room is well-ventilated.

Protection of hands:

Protective gloves are recommended.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Safety glasses

Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information
Appearance:
Form: Viscous

Color: White

Odor: Characteristic

Odour threshold: Not determined.

pH-value at 20 °C (68 °F): > 7

Change in condition
Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 100 °C (> 212 °F)

Flash point: > 100 °C (> 212 °F)

Flammability (solid, gaseous): Not applicable.

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Density at 20 °C (68 °F): 1.1 g/cm³ (9.18 lbs/gal)

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with
Water: Not miscible or difficult to mix.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:
Dynamic: Not determined.

Kinematic at 40 °C (104 °F): > 20.5 mm²/s

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: Optimum Compound (TM 2600)

(Contd. of page 4)

· Solvent content:	
· VOC content:	14.0 % 158.9 g/l / 1.33 lb/gl
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** None under normal conditions.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

LD/LC50 values that are relevant for classification:**64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy**

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2920 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

— USA —

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: *Optimum Compound (TM 2600)*

(Contd. of page 5)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name	
· DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	-

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
Regulation 1907/2006/EC, REACH concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
Regulation 453/2010/EU, REACH as amended.
Regulation 1272/2008/EC, on Classification, Labelling and Packaging of substances and mixtures.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/01/2015

Reviewed on 04/01/2015

Trade name: Optimum Compound (TM 2600)

(Contd. of page 6)

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

1344-28-1 aluminium oxide

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· GHS label elements Void

· Hazard pictograms Void

· Signal word Void

· Hazard statements Void

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Product and Environmental Safety Department

· Date of preparation / last revision 03/25/2014 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent