

OSHA Hazard Communication Standard 29 CFR 1900.1200
Prepared to GHS Rev. 4

**SAFETY
DATA SHEET**

SECTION 1- CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Elite Shine Slingless Tire Dressing
Product Use: Solvent Based Tire Dressing
Use Restrictions: For Industrial and Professional Use Only
Supplier: Wesmar Products Inc.
10729 47th Ave. W. Mukilteo, WA 98275
Phone:(425) 405-1405

Transportation Emergency: Emergency Response- PERS Chemical (800) 728-2482

SECTION 2- HAZARDS IDENTIFICATION

1) GHS Classification of the substance or mixture:

Aspiration Hazard- Category 1
Flammable Liquids- Category 2
Skin Irritation- Category 2
Specific Target Organ Toxicity, Single Exposure- Category 3

2) Label Elements:



Signal Word: DANGER

Hazard Statements:

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs (central and peripheral nervous system) through repeated or prolonged contact.

Precautionary Statements:

P102- Keep out of reach of children
P210- Keep away from heat, sparks, open flames, hot surfaces. No smoking.
P233- Keep container tightly closed.
P234- Keep only in original container
P240- Ground/bond container and receiving equipment.
P241- Use explosion proof electrical/ ventilating/lighting equipment.
P261- Avoid breathing fumes, mist, vapors, spray.

P264- Wash skin thoroughly after handling
P271- Use only outdoors or in well ventilated area.
P280- Wear chemical resistant protective gloves and splash proof eyewear

Response Statements:

P303+P353+P361+P363- IF ON SKIN (or hair): Rinse skin with water/shower. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.
P305+P351+P338- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present, and easy to do so. Continue Rinsing.
P304+P340+ IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do not induce vomiting.
P370+P378- IN CASE OF FIRE: Use dry sand, dry chemical or alcohol resistant foam for extinction.

Storage and Disposal Statements:

P233- Store in a well-ventilated place.
P235- Keep cool.
P403-Keep container tightly closed.
P405- Store locked up.
P501- Dispose of contents/container in accordance with local/regional/national regulation.

Other Hazards:

OSHA HCS 2012- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

HMIS Classification:

Health Hazard- 2
Chronic Health Hazard- 0
Flammability- 3

NFPA Classification:

Health- 2
Flammability- 3
Instability- 0

SECTION 3- COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical/Common Name</u>	<u>CAS #</u>	<u>PERCENTAGE</u>	<u>HAZARDOUS</u>
Heptane	142-82-5	35-45%	Yes
Aliphatic Hydrocarbon	64742-89-8	35-45%	Yes

SECTION 4- FIRST AID MEASURES

Inhalation: If affected, remove individual to fresh air. If breathing is difficult administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm and quiet and obtain medical attention.
Skin: Immediately flush affected area with lots of water for at least 2 minutes. Remove contaminated clothing and wash before reuse.
Eyes: Flush immediately with large quantities of running water for at least 5 minutes. Obtain medical attention.
Ingestion: Immediately give a lot of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain immediate medical attention.

SECTION 5-FIRE FIGHTING MEASURES

Flash Point: 25°F (T.C.C.)
Autoignition Temperature: Approximately 400°F
Lower Explosive Limit: 1% **Upper Explosive Limit:** 1%

General Hazards-

Fire: Product is flammable.
Suitable Extinguishing Media: Dry chemical, carbon dioxide, alcohol resistant foam.
Unsuitable Extinguishing Media: High volume water jet.
Fire Fighting Procedures: Wear self contained breathing apparatus for fire fighting if necessary.
Unusual Fire and Explosion Hazards: None known
Hazardous Combustion Products: Carbon oxides

SECTION 6- ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering.

Environmental precautions: Avoid run off to waterways and sewers.

Methods and material for containment and cleaning up: Stop leak if you can do it without risk. Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste disposal container.

SECTION 7- HANDLING AND STORAGE

Precautions for safe handling:

Avoid contact with skin and eyes by wearing protective clothing and equipment. Avoid inhalation of vapour or mist. Use only with adequate ventilation.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place. Store away from acids, acidic materials and oxidizers.

SECTION 8- EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters:

Component	CAS #	ACGIH Exposure Limits	OSHA Exposure Limits
n-heptane	142-82-5	400 ppm	500 ppm
Aliphatic Hydrocarbon	64742-89-8	400 ppm	500 ppm

Personal Protective Equipment-

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

Hand protection: Wear protective gloves made from the following materials- nitrile rubber or polyethylene. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye Protection: Wear safety glasses with side shields.

Skin and Body Protection: Where extensive dermal exposure may be expected, either a chemical suit or chemical apron will be needed.

Hygienic Practices: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES

Products Description:	Clear yellow liquid with characteristic odor.
Solubility in Water:	Insoluble
Boiling Point:	210°F
Specific Gravity (WATER=1):	0.75
Vapor Pressure (mmHg):	N/D
Vapor Density (AIR=1):	3.5
Percent Volatile by Volume (%):	> 85.00
Evaporation Rate (Butyl Acetate=1):	Approximately 3.0
Flash Point (T.C.C.):	25°F
pH (1% w/w in water):	N/A

SECTION 10- STABILITY AND REACTIVITY DATA

Stability: Stable under recommended storage conditions.

Material to Avoid: Avoid contact with acids and strong oxidizers such as permanganate, chlorine, etc.

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: Normal thermal byproducts of combustion i.e. carbon monoxide water.

SECTION 11- TOXICOLOGICAL INFORMATION

Heptane- (CAS 142-82-5)-

Acute Toxicity:

Acute oral toxicity- LD50 (rat, male and female): 5,000 mg/kg

Method: OECD Test Guideline 401

Symptoms: Salivation

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity- LC50 (rat, male and female): 73.5 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity- LD50 (rabbit, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

Skin Corrosion/Irritation:

Species: rabbit

Exposure time: 24 h

Method: OECD Test Guideline 404

Result: Irritating to skin.

GLP: yes

Remarks: Based on a similar product formulation.

Respiratory or skin sensitization:

Test Type: Maximization test

Species: guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitization.

Remarks: Based on a similar product formulation.

Germ Cell Mutagenicity:

Genotoxicity in vitro:

Test Type: Chromosome aberration test in vitro

Test species: Rat liver

Metabolic activation: Without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Reproductive Toxicity:

Effects on fertility:

Test Type: Two-generation study

Species: rat, male and female

Application Route: vapour

Dose: 0, 900, 3000, 9000 ppm

Frequency of Treatment: 5 days/week

General Toxicity - Parent: NOAEC: 3,000 ppm

General Toxicity F1: NOAEC: 3,000 ppm

Fertility: NOAEC: 9,000 ppm
Symptoms: Reduced maternal body weight gain. Reduced offspring weight gain.
Method: OECD Test Guideline 416
Result: No reproductive effects.

Effects on Foetal Development:

Species: mouse
Application Route: inhalation (vapour)
Dose: 0, 900, 3000, 9000 ppm
Duration of Single Treatment: 10 d
Frequency of Treatment: 6 hr/day
General Toxicity Maternal: NOAEC: 900 ppm
Developmental Toxicity: NOAEC: 3,000 ppm
Symptoms: Skeletal malformations.
Method: OECD Test Guideline 414
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

Further Information: Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Aliphatic Hydrocarbon (CAS 64742-89-8)-

TOXICITY-

Acute oral toxicity- LD50 (rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity- LC50 (rat, male and female): > 73.5 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity- LD50 (rabbit, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

SKIN CORROSION/IRRITATION-

Species: rabbit
Exposure time: 24 h
Method: OECD Test Guideline 404
Result: Irritating to skin.
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

SERIOUS EYE DAMAGE/EYE IRRITATION-

Result: No eye irritation

RESPIRATORY OR SKIN SENSITISATION-

Test Type: Maximization test
Species: guinea pig
Method: OECD Test Guideline 406
Result: Did not cause sensitisation on laboratory animals.
Remarks: Based on a similar product formulation.

GERM CELL MUTAGENICITY-

Result: Mutagenicity classification not possible from current data

CARCINOGENICITY-

Result: Not classifiable as a human carcinogen.

REPRODUCTIVE TOXICITY-

Effects on Fertility- Fertility classification not possible from current data. Embryotoxicity classification not possible from current data.

STOT-SINGLE EXPOSURE- Inhalation- (Central Nervous System): May cause drowsiness or dizziness. The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

REPEATED DOSE TOXICITY-

Species: rat, male

NOAEL: 12470 mg/m³

Application Route: inhalation (vapour)

Exposure time: 16 wks

Number of exposures: 12 h/d, 7 d/wk

Dose: 0, 12470 mg/m³

Remarks: Information given is based on data obtained from similar substances.

Species: rat, male and female

NOAEL: 1402

Application Route: inhalation (vapour)

Test atmosphere: vapour

Exposure time: 13 weeks

Number of exposures: 6 hours/day, 5 days/week

Dose: 322, 1402, 9869 mg/m³

GLP: yes

Target Organs: Kidney

Symptoms: Nasal and ocular discharge

Aspiration Toxicity: May be fatal if swallowed and enters airways.

Further information: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12- ECOLOGICAL INFORMATION

Heptane- (CAS 142-82-5)-

Ecotoxicity-

Toxicity to fish: LC50 (Carassius auratus (goldfish)): 4 mg/l

Exposure time: 24 h

Remarks: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 1.5

mg/l

Exposure time: 48 h

Test Type: static test

Remarks: Very toxic to aquatic organisms.

Persistence and Degradability-

Biodegradability: Primary biodegradation

Inoculum: activated sludge

Concentration: 100 mg/l

Biodegradation: 100 %

Testing period: 2 d

Exposure time: 25 d

Remarks: Readily biodegradable

Aliphatic Hydrocarbon (CAS 64742-89-8)-

ECOTOXICITY-

Toxicity to fish- LC50 (Carassius auratus (goldfish)): 4 mg/l

Exposure time: 24 h

Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates-EC50 (Daphnia magna (Water flea)): 1.5 mg/l

Exposure time: 48 h

Test Type: static test

Remarks: Information given is based on data obtained from similar substances.

Toxicity to algae-EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7 mg/l

Exposure time: 96 h

Test Type: static test

Ecotoxicology Assessment-

Acute aquatic toxicity: Very toxic to aquatic life.

Chronic aquatic toxicity: Very toxic to aquatic life with long lasting effects.

PERSISTENCE AND DEGRADABILITY-

Biodegradability: aerobic

Inoculum: activated sludge

Concentration: 20 mg/l

Biodegradation: 74.30 %

Exposure time: 56 d

GLP: yes

Remarks: Inherently biodegradable

BIOACCUMULATIVE POTENTIAL-

Partition coefficient (N-octanol/water): log Pow: 2.13 - 4.85 (25 °C)

REGULATION/REMARKS-

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances.

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A+B).

Additional Information: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

SECTION 13- DISPOSAL CONSIDERATIONS

Further information: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of as hazardous waste in compliance with local and national regulations.

SECTION 14- TRANSPORT INFORMATION

Transport in accordance with all federal, state and local regulations.

DOT (Department of Transportation)-

UN Number: UN 1268

UN proper shipping name: Petroleum Distillates, N.O.S., (Naphtha (Petroleum), Heavy Alkylate)

Hazard class: 3

Packing group: III

SECTION 15- REGULATORY INFORMATION

OSHA Hazards: Flammable liquid, Harmful by skin absorption., Moderate skin irritant, Moderate eye irritant, Carcinogen, Aspiration hazard.

SARA 304 Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a section 304 EHSRQ.

Massachusetts Right To Know:

Heptane	142-82-5	35-45%
Aliphatic Hydrocarbon	84742-89-8	35-45%

Pennsylvania Right To Know:

Heptane	142-82-5	35-45%
Aliphatic Hydrocarbon	84742-89-8	35-45%

New Jersey Right To Know:

Heptane	142-82-5	35-45%
Aliphatic Hydrocarbon	84742-89-8	35-45%

California Prop. 65 Components: WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16- OTHER INFORMATION

References: Not available

Other Special Considerations: Not available

Created: 10/17/19

Last Updated: NEW

DISCLAIMER:

The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable. Information is correct to the best of our knowledge at the date of the MSDS publication.