

SAFETY DATA SHEET

Date Prepared : 07/27/2005**SDS No :** WM 3926, 3927,
3931, 3932**Date-Revised :** 07/07/2015**Revision No :** 12

Reservoir Concentrate

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Reservoir Concentrate**PRODUCT CODE:** WM 3926, 3927, 2931, 3932**ALTERNATE TRADE NAME(S):** Methyl alcohol, Wood alcohol, Reagent ACS GRADE, Electronic Grade, Semi Grade, Mt. Hood Winter Wash**MANUFACTURER/DISTRIBUTOR**Wesmar Products
10729 47th Ave W
Mukilteo, WA 98275**Product Stewardship:** 425-405-1405**24 HR. EMERGENCY TELEPHONE NUMBERS****PERS Chemical (US Transportation) :**(800) 728-2482

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 3

Acute Toxicity (Inhalation), Category 3

Acute Toxicity (Dermal), Category 3

Target Organ Toxicity (Single exposure), Category 1

Physical:

Flammable Liquids, Category 2

GHS LABEL



Flame

Skull and
crossbonesHealth
hazard**SIGNAL WORD:** DANGER

HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H370: Causes damage to organs .

PRECAUTIONARY STATEMENT(S)

METHANOL**Prevention:**

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P270: Do not eat, drink or smoke when using this product.

P240: Ground/bond container and receiving equipment.

P102: Keep out of reach of children.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P304+P312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

P311: Call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403: Store in a well-ventilated place.

P234: Keep only in original container.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: DANGER! Highly Flammable liquid and vapor. Harmful or fatal if swallowed. Vapor harmful.

POTENTIAL HEALTH EFFECTS

EYES: Moderately irritating to the eyes.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: POISONOUS. May be fatal or cause blindness if swallowed. Ingestion may have a narcotic effect including signs of CNS depression such as dizziness, headache, drowsiness, loss of coordination, and fatigue.

INHALATION: Excessive exposure to this product may cause headache, CNS depression, drowsiness, dizziness, loss of appetite, irritation of the respiratory tract, drunkenness, unconsciousness, or death.

MEDICAL CONDITIONS AGGRAVATED: Preexisting diseases in or history of ailments involving skin, central nervous system, liver and kidney.

COMMENTS HEALTH: Can cause optic nerve damage (blindness).

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Methanol	99 - 100	67-56-1

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention.

SKIN: Remove contaminated clothing/shoes. Flush skin with water for at least 15 minutes. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

INGESTION: Call poison control center or get medical help immediately. If patient is conscious and alert, give 8 ounces of water or juice and induce vomiting, keeping patient's head below hips to prevent aspiration of liquid into lungs. Never induce vomiting on an unconscious person.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

METHANOL**SIGNS AND SYMPTOMS OF OVEREXPOSURE**

ACUTE TOXICITY: Shortness of breathing, confused behavior, redness of skin, swelling of tissues, watery eyes, and nausea.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, "alcohol" foam, dry chemical, or CO₂.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and unidentified organic compounds may be formed during combustion.

EXPLOSION HAZARDS: When heated above the flash point, this material emits flammable vapors which, when mixed with air, can burn or be explosive. Fine mists or sprays may be flammable at temperatures below the flash point.

FIRE FIGHTING PROCEDURES: WARNING! Flammable Liquid. Clear fire area of unprotected personnel. Do not enter confined fire space without full bunker gear, including a positive pressure NIOSH approved SCBA. Cool fire exposed containers with water.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: WARNING. Flammable. Ventilate area of leak or spill. Remove all sources of ignition. Clean-up personnel require protective clothing and respiratory protection from vapors. Only specially trained or qualified personnel should handle the emergency.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone.

STORAGE: Store away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Do not weld, cut, grind, solder, or drill on or near empty containers. Empty containers may contain explosive concentrations of product vapors.

COMMENTS: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition; they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Methanol	TWA	200	260	200	262
	STEL			250	328

ENGINEERING CONTROLS: Provide exhaust ventilation sufficient to keep the airborne concentration of this

METHANOL

product below its exposure limits. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical safety goggles and/or full face shield where splashing is possible. Contact lenses should not be worn when working with this material. Maintain eye wash fountain and quick-drench facilities in work areas.

SKIN: Wear resistant gloves (consult your safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: If exposure may or does exceed occupational exposure limits (Sec. 8) use a NIOSH approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

WORK HYGIENIC PRACTICES: Use good personal hygiene when handling this product. Wash hands after use, before eating, drinking, smoking, or using the toilet.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Pungent odor.

COLOR: Clear, colorless liquid.

pH: NA = Not Applicable

PERCENT VOLATILE: 100

FLASHPOINT AND METHOD: (52°F)

FLAMMABLE LIMITS: 0.06 to 0.36

AUTOIGNITION TEMPERATURE: (867°F)

VAPOR PRESSURE: 96 mm Hg

VAPOR DENSITY: Heavier than air.

BOILING POINT: (147°F)

FREEZING POINT: (-144°F)

SOLUBILITY IN WATER: Soluble

EVAPORATION RATE: Slower than ether.

DENSITY: 6.60

SPECIFIC GRAVITY: 0.79 to 0.80

MOLECULAR WEIGHT: 32.1

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Avoid heat, flame, and other sources of ignition.

CONDITIONS TO AVOID: Avoid strong alkalies and oxidizing agents.

METHANOL

HAZARDOUS DECOMPOSITION PRODUCTS: May form carbon dioxide, carbon monoxide, various hydrocarbons.

11. TOXICOLOGICAL INFORMATION

COMMENTS: Poison. May be fatal or cause blindness, if swallowed. Cannot be made nonpoisonous.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

EMPTY CONTAINER: KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)**

PROPER SHIPPING NAME: Methanol

PRIMARY HAZARD CLASS/DIVISION: 3

UN/NA NUMBER: UN 1230

PACKING GROUP: II

NAERG: 131

REPORTABLE QUANTITY (RQ) UNDER CERCLA: 5,000

LABEL: Flammable liquid

OTHER SHIPPING INFORMATION: If shipping over water use IMDG:

METHANOL

UN 1230, METHANOL, 3 (6.1), II

NAERG # 131

15. REGULATORY INFORMATION**UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

METHANOL



Flammable
Liquid



Skull and
crossbones

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: This product should be reported as an immediate (acute) health hazard, delayed (chronic) health hazard, and a fire hazard.

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

313 REPORTABLE INGREDIENTS: Methyl alcohol (CAS 67-56-1)

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA RQ: 5,000 lbs.

GENERAL COMMENTS: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. OTHER INFORMATION

REASON FOR ISSUE: Updated SDS information and changed to new format.


PREPARED BY: Compliance **Date-Revised:** 07/07/2015

REVISION SUMMARY: This SDS replaces the 05/26/2015 MSDS.

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY	<input type="checkbox"/>	3
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	H

NFPA CODES



MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, Wesmar Products makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Wesmar PProducts assumes no responsibility for injuries from the use of the product described herein.