SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME SYNONYMS PRODUCT USE SUPPLIER SUPPLIER'S ADDRESS	 DRYING AGENT Product is a mixture: No synonyms are available. Neutral pH Material Wesmar Co. Inc. 5720 204TH ST SW, Lynnwood, WA 98036 (206) 783-5344 	QUALITY • SERVICE • INTEGRITY
EMERGENCY RESPONSE PHONE NUMBER	: PERS: 1-800-633-8253	

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS U.S. – CLASSIFICATION	:	H302 H315 H319	Harmful if swallowed. Causes skin irritation Causes serious eye irritation		
LABEL ELEMENTS	:	GHS – US HA	AZARD PICTOGRAMS	The product is classified and labeled according to the Globally Harmonized System (GHS).	
HAZARD PICTOGRAMS	:				
SIGNAL WORD	:	WARNING			
HAZARD STATEMENTS (GHS-US)	:	H302	Harmful if swallowed.		
	:	H315	Causes skin irritation.		
	:	H319	Causes serious eye irri	tation.	
PRECAUTIONARY STATEMENTS (GHS-US)	:	P101	If medical advice is needed, have product container or label at hand		
	:	P102	Keep out of reach of c	hildren.	
	:	P103	Read label before use		
		P264		ninated clothing thoroughly after handling.	
		P270		noke when using this product.	
	:	P280		ive gloves/protective clothing/eye	
		0201	protection/face prote		
		P301+ P312	unwell.	POISON CENTER or doctor/physician if you feel	
		P302+P352		ith plenty of soap and water.	
		P305+351+		ously with water for several minutes. Remove	
		P338		ent and easy to do. Continue rinsing.	
	:	P332+P313	-	: Get medical advice/attention.	
	:	P337+P313	If eye irritation persist	s: Get medical advice/attention.	
	:	P501	-	ontainer in accordance with	
			local/regional/nationa	Il/international regulations	
CLASSIFICATION SYSTEM NFPA RATINGS (SCALE 0-4) HMIS RATINGS (SCALE 0-5)	:	Health = 2, Fi	Definitions: 0-Least, 1-Sl re = 0, Reactivity = 0 re = 0, Reactivity = 0	ight, 2-Moderate, 3-High, 4-Extreme.	

SECTION 3 - COMPOSITON/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTIC
DESCRIPTION

: Mixtures

:

Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS #	EC #	GHS CLASS
Mineral Oil	10-20	64741-44-2	265-044-7	Flamm Liq Cat 3, Acute Tox Oral Cat 4 Skin Irrit Cat 2, Eye Dam Cat 1
Ethylene Glycol Monobutyl Ether	1-5	111-76-2	203-905-0	Acute Oral Tox Cat 4, Eye Irrit Cat 2A, Skin Irrit Cat 2

Irrit = Irritation, Cor = Corrosive, Dam = Damage, Cat = Category, Tox = Toxic, STOT = Specific Target Organ Toxicity.

SECTION 4 – FIRST AID MEASURES

DESCRIPTION OF FIRST AID ME	ASURES
GENERAL	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice. Show the label where possible.
EYE CONTACT	: Immediately flush eyes with water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation persists, get immediate medical attention.
SKIN CONTACT	: Remove contaminated clothing and shoes. Wash affected skin area with soap and water. If irritation persists, get immediate medical attention.
SWALLOWING (INGESTION)	: If ingested, dilute swallowed material by drinking water. DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. Never give anything by mouth to an unconscious person. Get immediate medical attention.
INHALATION	: Remove to fresh air. Get immediate medical attention.
OTHER INSTRUCTIONS	: Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS	Dry chemical, foam, water or carbon dioxide. In the event of a fire, wear a NIOSH (USA) or CEN (EU) approved, positive press self-contained breathing apparatus (SCUBA) and full protective clothing. Evacuate non-essential personnel from the danger area.	
UNUSUAL FIRE AND EXPLOSION HAZARDS	No further relevant information is available.	

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES	:	Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.
ENVIRONMENTAL PROCEDURES	:	Keep spilled material away from sewage/drainage systems and waterways.
METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP	:	All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Neutralize spill and collect using an appropriate absorbent material such as clay or vermiculite. Place waste in an
		appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

SECTION 7 – HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING	: Use with adequate ventilation. Wear proper protective equipment. Do not mix with water or acids without proper dilution and agitation to prevent a potentially violent reaction.
CONDITIONS FOR SAFE STORAGE	: Store in closed, properly labeled containers. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

TLV (THRESHOLD LIMIT VALUE)

: The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	OSHA PEL – TWA	ACGIH – TLV	ACGIH – STEL
Mineral Oil	Not Established	Not Established	Not Established
Ethylene Glycol Monobutyl Ether	50 ppm	20 ppm	Not Established

EYE PROTECTION	: Wear chemical splash goggles or face shield.
SKIN PROTECTION	: Minimize contact with product. Wear chemical resistant coveralls, boots, gloves, apron and/or suitable long-sleeved clothing.
RESPIRATORY PROTECTION	 In case of brief exposure use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.
VENTILATION	: Ensure adequate ventilation.
ADDITIONAL MEASURES	: Emergency eyewash and safety shower facilities should be available in the immediate work area.
REQUIRED WORK/HYGIENE	: Wash hands thoroughly after handling. Keep away from all food stuffs, beverages and feed. Do not eat, drink or smoke in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	:	Light amber liquid.
	•	0 1
ODOR	:	Mild odor
ODOR THRESHOLD	:	Not available
РН	:	5.0 - 6.0 AS IS
MELTING POINT/FREEZING	:	Not available
POINT		
BOILING POINT	:	Approx. 212° F.
FLASH POINT	:	Non flammable, non combustible
EVAPORATION RATE	:	Not available
FLAMMABILITY	:	Non flammable-Non combustible
LOWER FLAMMABILITY LIMIT	:	Not available
UPPER FLAMMABILITY LIMIT	:	Not available
VAPOR PRESSURE	:	Not available
VAPOR DENSITY (AIR=1)	:	Not available
RELATIVE DESNITY	:	0.96
SOLUBILITY IN WATER	:	Soluble in water

PARTITION COEFFICIENT n-	:	Not available
OCTANOL/WATER		
AUTOIGNITION TEMPERATURE	:	Not available
DECOMPOSITION	:	Not available
TEMPERATURE		

SECTION 10 - STABILITY AND REACTIVITY

STABILITY HAZARDOUS CONDITONS TO AVOID	Stable under recommended storage conditions. No decomposition if used according to specifications
INCOMPATIBLE MATERIALS HAZARDOUS DECOMPOSITION PRODUCTS	Keep away from strong acids. No dangerous decomposition products known.

TOXICOLOGICAL INFORMATION ACUTE TOXICITY IRRITATION EFFECTS	:	Mineral Oil LD50 Oral (rat): > 2,000 mg/kg. LD50 Dermal (rabbit): > 2,000 mg/kg. LC50 Inhalation (rat): Near saturated vapor concentration: 1 hr. EYE EFFECTS: Essentially non-irritating to eyes. SKIN EFFECTS: May cause moderate irritation to skin. Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.
		REPEATED DOSE EFFECTS: Cardiovascular system: chronic abuse of similar materials has been associated with irregular heart rhythms and cardiac arrest. Central nervous system: repeated exposure affects the nervous system. Kidney: caused kidney effects in male rats which are not considered relevant to humans.
BIOACCUMULATION CARCINOGENICITY	:	No appreciable bio-concentration is expected in the environment. This product is not classified as a carcinogen by OSHA, IARC, ACGIH or NTP.
TOXICOLOGICAL INFORMATION ACUTE ORALTOXICITY	:	Ethylene Glycol Monobutyl Ether LD50 Oral: 1,414 mg/kg Species: guinea pig Remarks: Ingestion may cause weakness, confusion, anxiety, decreased blood pressure, and CNS depression with collapse and coma. LD50 Oral (rat): 1746 mg/kg.
ACUTE INHALATION TOXICITY	:	LC50: ~ 932 ppm Exposure time: 4 HOURS Species: guinea pig Remarks: Exposure to vapor may cause irritation of the eyes, nose, and respiratory tract. May cause nausea. May cause headaches. Extensive and prolonged contact with skin may cause confusion, anxiety, decreased blood pressure, and CNS depression with collapse and coma. LC50 Inhalation (rat) 7hr: ~ 700 ppm.
ACUTE DERMAL TOXICITY	:	LD50: > 2,000 mg/kg Species: guinea pig Remarks: Minimal hazard by skin contact with liquid or vapor. This material may be absorbed through the skin. High dermal doses (most likely achieved from exposure to undiluted liquid) may cause weakness, headache and nausea. Extensive and prolonged contact with skin may cause confusion, anxiety, decreased blood pressure, and CNS depression with collapse and coma.
IRRITATION	:	Skin: Repeated or prolonged contact may cause skin irritation. Eyes: Moderate to severe eye irritant.
SENSITISATION CARCINOGENICITY	:	Did not cause sensitization on lab animals. No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC, ACGIH, NTP, and OSHA.

	SECTION 12 – ECOLOGICAL INFORMATION	
ECOLOGICAL INFORMATION	: Mineral Oil	

ΑСUTE ΤΟΧΙΟΙΤΥ	:	Acute Toxicity for Naphtha (Petroleum), Heavy Alkylate: Fish: Low toxicity: LC/EC/IC50 greater than 1000 mg/l Aquatic Invertebrates: Low toxicity: LC/EC/IC50 greater than 1000 mg/l Algae: Low toxicity: LC/EC/IC50 greater than 1000 mg/l Microorganisms: Low toxicity: LC/EC/IC50 greater than 1000 mg/l		
ENVIRONMENTAL DATA	:	Oxidizes rapidly by photo-chemical reactions in air. Expected to be not inherently biodegradable.		
ECOTOXICOLOGICAL INFORMATION	:	Avoid uncontrolled releases of this material. Where spills are possible, a comprehensive spill response plan should be developed and implemented.		
BIOACCUMULATIVE POTENTIAL	:	Has potential to bio-accumulate.		
ECOLOGICAL INFORMATION ECOTOXICITY	:	Ethylene Glycol Monobutyl Ether Fish: 96h LC50:>100 mg/L (Oryzias latipes) Crustacea: 48h EC50:>1000 mg/L (Daphnia magna) Algae: 72h EC50:630 mg/L (Selenastrum capricornutum)		
PERSISTENCE AND	:	96.0% (by BOD), 96.0% (by TOC), 100% (by GC).		
DEGRADABILITY MOBILITY IN SOIL	:	No data available.		
	SECTION 13 – DISPOSAL CONSIDERATIONS			
WASTE DISPOSAL	:	This product must be disposed of in accordance with Federal, state and local environmental regulations. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.		

SECTION 14 – TRANSPORTATION INFORMATION

DOT/IMDG/ IATA PROPER SHIPPING NAME	:	Not Hazardous
HAZARD CLASS AND LABEL	:	Not Applicable.
UN NUMBER	:	Not Applicable.
PACKAGING GROUP	:	Not Applicable.
EPA REPORTABLE QUANTITY	:	Not Applicable.
(RQ)		
MARINE POLLUTANT	:	Not listed.
EMERGENCY RESPONSE GUIDE	:	Not Applicable.

SECTION 15 – REGULATORY INFORMATION

U.N. GHS CLASSIFICATION & LABELING INFORMATION: See Section 2 for GHS Hazard Information.

U.S. FEDERAL REGULATORY IN	IFORMATION:
LISTED CARCINOGEN	: Not listed.
TSCA STATUS	: The ingredients of this product are listed in TSCA inventory (40CFR 710.)
SARA SECTION 302	: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA SECTION 312	: Chronic health hazard (Glycol Ether EB).
SARA SECTION 313	 This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
NFPA HEALTH	: 2
NFPA FLAMMABILITY	: 0
NFPA REACTIVITY	: 0

EUROPEAN UNION REGULATOR	Y INF	ORMATION:
EC CLASSIFICATION	:	Xi: Irritant
DSD/DPD RISK (R) PHRASES	:	R22: Harmful is swallowed.
		R36/38: Irritating to eyes and skin.
DSD/DPD SAFETY (S) PHRASES	:	S1/2: Keep locked up and out of reach of children.
		S24/25: Avoid contact with eyes and skin.
		S26: In case of contact with eyes, rinse immediately with
		plenty of water and seek medical advice.
		S36/S37/39: Wear suitable protective clothing, gloves and
		eye/face protection.
		S45: In case of accidents or if you feel unwell, seek medical
		advice immediately. Show label where possible.
		S61: Avoid release to the environment. S62: If swallowed, do not induce vomiting.
		S64: If swallowed, rinse mouth with water if victim is
		conscious.
DSD/DPD HAZARD SYMBOL		Xi: Irritant
-,		
CANADIAN REGULATORY INFOR		
WHMIS CATEGORY	:	D2B: Materials that cause other toxic effects (TOXIC).
DOMESTIC SUBSTANCES LIST	:	Listed
(DSL)		
INGREDIENT DISCLOSURE LIST	:	Listed
		SECTION 16 – OTHER INFORMATION
		The information contained bracks have been accorded for a contract believed to be
DISCLAIMER	:	The information contained herein has been compiled from sources believed to be
		realiable and accurate to the best of our knowledge at this date. It is provided
		without warranty, expressed or implied, as to the results of use of this information
		or to the product to which it relates. Wesmar Co. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes
		the risk in their use of this product and should review the data and
		recommendations in the specific context of their intended use.
CERCLA	:	Comprehensive Environmental Response, Compensation, and Liability Act.
EINECS	:	European Inventory of Existing Commercial Chemical Substances
IMDG	•	International Maritime Code for Dangerous Goods
IARC		International Agency for Research on Cancer

	· International Martime code for Dangerous Goods
IARC	: International Agency for Research on Cancer
ΙΑΤΑ	: International Air Transportation Association
ACGIH	: American Conference of Governmental Industrial Hygienists
NFPA	: National Fire Protection Association (USA)
NTP	: National Toxicology Program
SARA	: Superfund Amendments and Reauthorization Act
TSCA	: Toxic Substances Control Act
HMIS	: Hazardous Materials Identification System (USA)
WHMIS	: Workplace Hazardous Materials Information System
LC50	: Lethal concentration, 50 percent
LD50	: Lethal dose, 50 percent
STOT	: Systemic Target Organ Toxicity
DATE PREPARED	: JAN 12, 2015
DATE REVISED	: JAN 12, 2015