

SAFETY DATA SHEET

SAP REMOVER

SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME : SAP REMOVER
SYNONYMS : Product is a mixture: No synonyms are available.
PRODUCT USE : Flammable Material
SUPPLIER : WESMAR CO. INC.
SUPPLIER'S ADDRESS :
5720 204TH ST. SW
LYNNWOOD, WA 98036
(206) 783-5344
EMERGENCY RESPONSE PHONE NUMBER : PERS: 1-800-633-8253



SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

GHS U.S. – CLASSIFICATION : H302 Harmful if swallowed.
H315 Causes skin irritation
H319 Causes serious eye irritation

LABEL ELEMENTS : **GHS – US HAZARD PICTOGRAMS** The product is classified and labeled according to the Globally Harmonized System (GHS).

HAZARD PICTOGRAMS :



SIGNAL WORD : DANGER

HAZARD STATEMENTS (GHS-US)

: H225 Highly flammable liquid and vapor
: H302 Harmful if swallowed.
: H315 Causes skin irritation.
: H319 Causes serious eye irritation.
: H336 May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS (SGS-US)

PREVENTION

: P101 If medical advice is needed, have product container or label at hand.
: P102 Keep out of reach of children.
: P103 Read label before use.
: P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking.
: P233 Keep container tightly closed.
: P240 Ground/bond container and receiving equipment.
: P241 Use explosion proof electrical/ventilation/light...equipment
: P242 Use only non-sparking tools.
: P243 Take precautionary measures against static discharge.
: P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
: P264 Wash skin and contaminated clothing thoroughly after handling.
: P270 Do not eat, drink or smoke when using this product.
: P271 Use only outdoors or in a well ventilated area.
: P280 Wear suitable protective gloves/protective clothing/eye protection/face protection.

RESPONSE

: P305+P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
+P338
: P337+P313 If eye irritation persists, get medical attention.

SAFETY DATA SHEET

SAP REMOVER

- : P303+P361 IF ON SKIN: Remove/Take off immediately all contaminated clothing.
 - +351 Rinse skin with water/shower.
 - : P304+P340 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable to breathing.
 - : P337+P313 If eye irritation persists: Get medical advice/attention.
 - : P403+P233 Store in a well ventilated place. Keep container tightly closed.
 - P403+P235 Store in a well ventilated place. Keep cool.
 - : P405 Store locked up.
 - : P501 Dispose of contents/container in accordance with local/regional/national/international regulations
- STORAGE**
- DISPOSAL**
- OSHA HAZARDS** : Isopropanol: Flammable liquid, Target Organ Effect, Irritant
- TARGET ORGANS** : Isopropanol: Cardiovascular system, Gastrointestinal tract, Kidney, Liver, Nerves.
- CLASSIFICATION SYSTEM** : NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.
- NFPA RATINGS (SCALE 0-4)** : Health = 2, Fire = 0, Reactivity = 0
- HMIS RATINGS (SCALE 0-5)** : Health = 2, Fire = 0, Reactivity = 0

CLASSIFICATION SYSTEM: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

NFPA ratings (scale 0-4):Health = 2, Fire = 2, Reactivity = 0

HMIS ratings (scale 0-5):Health = 2, Fire = 2, Reactivity = 0

SECTION 3 – COMPOSITON/INFORMATION ON INGREDIENTS

- CHEMICAL CHARACTERISTIC** : Mixtures
- DESCRIPTION** : Mixture of the substances listed below with nonhazardous additions.

| COMPONENT | PERCENT | CAS # | EC # | GHS CLASS |
|-------------------------------------|---------|-----------|-----------|--|
| Isopropanol (Isopropyl alcohol) | 60-80 | 67-63-0 | 200-661-7 | Eye Irrit Cat 2, Flam Liq Cat 2 STOT SE Cat 3 |
| Methyl-oxirane polymer with oxirane | 1-5 | 9003-11-6 | Not Found | No need for classification according to GHS criteria for this product. |

Irrit = Irritation, Cor = Corrosive, Dam = Damage, Cat = Category, Tox = Toxic, STOT = Specific Target Organ Toxicity.

SECTION 4 – FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

- GENERAL** : If you feel unwell, seek medical advice. Show the label where possible. Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area
- EYE CONTACT** : Immediately flush eyes with low pressure water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Remove contact lenses, if present and easy to do so. Continue rinsing. If irritation persists, get immediate medical attention.
- SKIN CONTACT** : Remove contaminated clothing and shoes. Wash affected skin area with soap and water. If irritation persists, get immediate medical attention. Wash contaminated clothing before reuse.
- SWALLOWING (INGESTION)** : If ingested, dilute swallowed material by drinking water. **DO NOT INDUCE VOMITING.** If vomiting occurs spontaneously, keep airway clear and have victim lean forward to prevent aspiration. Give more water when vomiting stops. Never give anything by mouth to an unconscious person. Get immediate medical attention.
- INHALATION** : Remove to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

SAFETY DATA SHEET

SAP REMOVER

OTHER INSTRUCTIONS : Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS : Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water
UNUSUAL FIRE AND EXPLOSION HAZARDS : Vapors may travel to source of ignition and flash back.
OSHA/NFPA (ISOPROPANOL) : Class 1B Flammable Liquid.
FLASH POINT (ISOPROPANOL) : 12°C/ 53°F Closed Cup.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT & EMERGENCY PROCEDURES : Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.
ENVIRONMENTAL PROCEDURES METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN-UP : Keep spilled material away from sewage/drainage systems and waterways.
 : All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Collect with an electrically protected vacuum cleaner or by wet-brushing and place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

SECTION 7 – HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING : Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.
ENVIRONMENTAL PRECAUTIONS : Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains.
CONDITIONS FOR SAFE STORAGE : Keep container tightly closed in a cool, dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Protect containers from heat, physical damage, ignition sources and incompatible materials. Have emergency equipment for fires and spills readily available.



SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

TLV (THRESHOLD LIMIT VALUE) : The TLV in section in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

| COMPONENT | OSHA PEL – TWA | ACGIH – TLV | ACGIH – STEL |
|---------------------------------|----------------|-------------|--------------|
| Isopropanol (Isopropyl alcohol) | 400 ppm | 200 ppm | 400 ppm |

SAFETY DATA SHEET

SAP REMOVER

| | | | |
|-------------------------------------|-----------------|-----------------|-----------------|
| Methyl-oxirane polymer with oxirane | Not Established | Not Established | Not Established |
|-------------------------------------|-----------------|-----------------|-----------------|

- EYE PROTECTION** : Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.
- SKIN PROTECTION** : Wear impervious, flame retardant, antistatic protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
- RESPIRATORY PROTECTION** : Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
- HAND PROTECTION** : Handle with gloves. Gloves must be inspected prior to use. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.
- APPROPRIATE ENGINEERING CONTROLS** : General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.
- ADDITIONAL MEASURES** : Emergency eyewash and safety shower facilities should be available in the immediate work area.
- REQUIRED WORK/HYGIENE** : Wash hands thoroughly after handling. Keep away from all food stuffs, beverages and feed. Do not eat, drink or smoke in work area.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

- APPEARANCE** : Clear colorless liquid with mild odor.
- ODOR** : Mild alcohol odor
- ODOR THRESHOLD** : Not available
- PH** : NOT EST.
- MELTING POINT/FREEZING POINT** : Not available
- BOILING POINT** : Approx. 212° F.
- FLASH POINT** : Non flammable, non combustible
- EVAPORATION RATE** : Not available
- FLAMMABILITY** : Non flammable-Non combustible
- LOWER FLAMMABILITY LIMIT** : Not available
- UPPER FLAMMABILITY LIMIT** : Not available
- VAPOR PRESSURE** : Not available
- VAPOR DENSITY (AIR=1)** : Not available
- RELATIVE DENSITY** : 0.8
- SOLUBILITY IN WATER** : Soluble in water
- PARTITION COEFFICIENT n-OCTANOL/WATER** : Not available
- AUTOIGNITION TEMPERATURE** : Not available
- DECOMPOSITION TEMPERATURE** : Not available

SECTION 10 – STABILITY AND REACTIVITY

- STABILITY** : Stable under recommended storage conditions.
- HAZARDOUS CONDITIONS TO AVOID** : Heat, flames, and sparks. Extreme temperatures and direct sunlight.
- INCOMPATIBLE MATERIALS** : Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids.

SAFETY DATA SHEET

SAP REMOVER

HAZARDOUS DECOMPOSITION PRODUCTS : Carbon oxides are expected to be, under fire conditions, the primary hazardous decomposition products.

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION : **Isopropanol (Isopropyl Alcohol)**

ACUTE TOXICITY : LD50 Oral (rat): 5045 mg/kg. LD50 Dermal (rabbit): 12,800 mg/kg. LC50 Inhalation (rat) 8hr: 16,000 mg/kg.

OTHER INFORMATION EYES : Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury

OTHER INFORMATION INGESTION : Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea.

OTHER INFORMATION INHALATION : Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness.

OTHER INFORMATION SKIN : May cause irritation with pain and stinging, especially if the skin is abraded. Isopropanol has a low potential to cause allergic skin reactions; however, rare cases of allergic contact dermatitis have been reported.

STOT SINGLE EXPOSURE CARCINOGENICITY : Inhalation - May cause drowsiness or dizziness. - Central Nervous System.
: IARC: Group 3: Not classifiable as to its carcinogenicity to humans. No component of this product, present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH, NTP or OSHA.

TOXICOLOGICAL INFORMATION : **Methyl-oxirane polymer with oxirane**

ACUTE ORAL TOXICITY : LD50 Oral (rat): > 2000 mg/kg, LD50 Dermal (rabbit): 10,200 mg/kg

SKIN AND EYE IRRITATION : Draize Test: Eyes: Non irritant, Skin: Non irritant.

SENSITISATION : Skin sensitizing effects were not observed in animal studies.

SYMPTOMS OF EXPOSURE : No significant symptoms are expected due to the non-classification of the product.

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION : **Isopropanol**

ACUTE FISH TOXICITY : LC50 / 96 hr: Pimephales promelas: 9,640 mg/L.

TOXICITY TO DAPHNIA : EC50 / 24 h / Water Flea - 5,102 mg/L.

TOXICITY TO PLANTS : EC50 / 72 hours Desmodemus subspicatus > 2,000 mg/L.

MOBILITY : This material is expected to have very high mobility in soil. It does not absorb to most soil types.

PERSISTENCE AND DEGRADABILITY : No data available.

BIOACCUMULATIVE POTENTIAL : No data available.

ECOLOGICAL INFORMATION : **Methyl-oxirane polymer with oxirane (25R2)**

ECOTOXICITY : Toxicity to fish: LC50 (96 h) 105 mg/l, Oncorhynchus mykiss
Aquatic invertebrates: EC50 (48 h) 1,033 mg/l, Daphnia magna
Aquatic plants: EC50 (72 h) 370 mg/l, algae

PERSISTENCE AND BIODEGRADABILITY : Assessment: Readily biodegradable (according to OECD criteria)

MOBILITY : The substance will not evaporate into the atmosphere from the water surface. Adsorption to solid soil phase is possible.

SECTION 13 – DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET

SAP REMOVER

WASTE DISPOSAL : This product must be disposed of in accordance with Federal, state and local environmental regulations. Discarded materials may be considered hazardous waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.

SECTION 14 – TRANSPORTATION INFORMATION

DOT/IMDG/ IATA PROPER SHIPPING NAME : Isopropanol, solution 3 UN-1219 PG-II
HAZARD CLASS AND LABEL : 3 (Flammable Liquid)
UN NUMBER : UN-1219
PACKAGING GROUP : PG - II
EPA REPORTABLE QUANTITY (RQ) : Not Applicable.
MARINE POLLUTANT : No
EMERGENCY RESPONSE GUIDE : ERG-129

SECTION 15 – REGULATORY INFORMATION

U.N. GHS CLASSIFICATION & LABELING INFORMATION: See Section 2 for GHS Hazard Information.

U.S. FEDERAL REGULATORY INFORMATION:

LISTED CARCINOGEN : Not listed.
TSCA STATUS : The ingredients of this product are listed in TSCA inventory (40CFR 710.)
SARA SECTION 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
SARA SECTION 312 : Dipropylene Glycol Methyl Ether : Chronic health hazard
Isopropanol : Acute health hazard, Chronic health hazard, Fire hazard.
SARA SECTION 313 : The following components are subject to reporting levels established by SARA title III, Section 313: ISOPROPANOL (CAS# 67-63-0)
CERCLA : No chemicals in this material with known CAS numbers are subject to the reporting requirements of CERCLA.
NFPA HEALTH : 2
NFPA FLAMMABILITY : 2
NFPA REACTIVITY : 0

EUROPEAN UNION REGULATORY INFORMATION:

EC CLASSIFICATION : Flammable, Xi: Irritant
DSD/DPD RISK (R) PHRASES : R11: Highly flammable. (Isopropanol)
R22: Harmful if swallowed.
R36: Irritating to skin.
R67: Vapors may cause drowsiness and dizziness.
DSD/DPD SAFETY (S) PHRASES : S2: Keep out of reach of children.
S7: Keep container tightly closed.
S16: Keep away from sources of ignition – No smoking
S24/25: Avoid contact with eyes and skin.



SAFETY DATA SHEET

SAP REMOVER

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/S37/39: Wear suitable protective clothing, gloves and eye/face protection.

S45: In case of accidents or if you feel unwell, seek medical advice immediately. Show label where possible.

S61: Avoid release to the environment.

S62: If swallowed, do not induce vomiting.

S64: If swallowed, rinse mouth with water if victim is conscious.



DSD/DPD HAZARD SYMBOL : F: Flammable, Xi: Irritant

CANADIAN REGULATORY INFORMATION:

WHMIS CATEGORY : Isopropanol: B2: Flammable Liquid

: Isopropanol: D2B: Materials that cause other toxic effects (TOXIC).

DOMESTIC SUBSTANCES LIST (DSL) : Listed

INGREDIENT DISCLOSURE LIST : Listed



SECTION 16 – OTHER INFORMATION

DISCLAIMER : The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Wesmar Co. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act.
EINECS : European Inventory of Existing Commercial Chemical Substances
IMDG : International Maritime Code for Dangerous Goods
IARC : International Agency for Research on Cancer
IATA : International Air Transportation Association
ACGIH : American Conference of Governmental Industrial Hygienists
NFPA : National Fire Protection Association (USA)
NTP : National Toxicology Program
SARA : Superfund Amendments and Reauthorization Act
TSCA : Toxic Substances Control Act
HMIS : Hazardous Materials Identification System (USA)
WHMIS : Workplace Hazardous Materials Information System
LC50 : Lethal concentration, 50 percent
LD50 : Lethal dose, 50 percent
STOT : Systemic Target Organ Toxicity
DATE PREPARED : MAR 1, 2008
DATE REVISED : JAN 12, 2015