

Safety Data Sheet ALUMA KLEEN

SECTION 1- PRODUCT IDENTIFICATION

PRODUCT NAME ALUMA KLEEN
SYNONYMS Product is a mixture: No synonyms are available
PRODUCT USE Highly Acidic Material
SUPPLIER WESMAR CO. INC.
SUPPLIER'S ADDRESS 5720 204TH ST. SW, LYNNWOOD, WA 98036
 (206) 783-5344
EMERGENCY RESPONSE PHONE PERS: 1-800-633-8253



SECTION 2 – HAZARD IDENTIFICATION

GHS – US CLASSIFICATION : H290 Metal corrosion Category 1
 H302 Harmful if swallowed
 : H314 Skin Corrosion Category 1A
 : H318 Serious Eye Damage Category 1
 : H370 STOT SE 1

HAZARD PICTOGRAMS :



SIGNAL WORD : **DANGER**

GHS LABEL ELEMENTS : The product is classified and labeled according to the Globally Harmonized System (GHS).

GHS PHYSICAL HAZARDS : H290 May be corrosive to metals.
GHS HEALTH HAZARDS : H302 Harmful if swallowed
 : H314 Causes severe skin burns and eye damage.
 : H318 Causes serious eye damage.
 : H370 Causes damage to respiratory system by inhalation.

GHS PRECAUTIONARY HAZARDS : P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read label before use.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 Wash skin and contaminated clothing thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P280 Wear suitable protective gloves/protective clothing/eye protection/face protection.
 P303+P361 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 +P353
 : P305+P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 +P338
 : P305+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position.
 : P310 Immediately call a POISON CENTER or doctor/physician.
 : P330 Rinse mouth if ingested.
 : P405 Store locked up.
 : P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

CLASSIFICATION SYSTEM: : NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.

Safety Data Sheet

ALUMA KLEEN

NFPA ratings (scale 0-4): : Health = 3, Fire = 0, Reactivity = 1

HMIS ratings (scale 0-5): : Health = 3, Fire = 0, Reactivity = 1

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERIZATION : Mixtures

DESCRIPTION : Mixture of the substances listed below with nonhazardous additions.

COMPONENT	PERCENT	CAS #	EC #	GHS CLASS
Phosphoric acid	20-40	7664-38-2	231-633-2	Skin Corr. Cat 1B, Eye Dam. Cat 1
Ammonium Hydrogen Difluoride	1-5	1341-49-7	215-676-4	Skin Corr Cat 1B, Eye Dam Cat 1 Acute Oral Toxicity Cat 3
Alcohol Ethoxylate	5-10	127087-87-0	500-315-8	Eye Dam Cat 1

Corr. = Corrosion, Cat. = Category, Tox = Toxicity, Inhal. = Inhalation

SECTION 4 – FIRST AID MEASURES

EYE CONTACT : Immediately flush eyes with water for at least 15 minutes. Hold eyelids open to ensure adequate flushing. Remove contact lenses, if present and easy to do so. Continue rinsing. Immediate call a POISON CENTER or doctor/physician.

SKIN CONTACT : Remove contaminated clothing and shoes. Wash affected skin area with water for at least 15 minutes. Delayed skin damage is possible if product is not completely washed off. Get immediate medical attention. Wash contaminated clothing before reuse.

SWALLOWING (INGESTION) : If ingested, dilute swallowed material by drinking water. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Immediate call a POISON CENTER or doctor/physician.

INHALATION : When symptoms occur, go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER/doctor/physician.

GENERAL MEASURES : Never give anything by mouth to an unconscious person. Rescue personnel must wear appropriate protective equipment during removal of victims from contaminated areas. Treat symptomatically and supportively.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA : Water spray, fog, carbon dioxide, foam, dry chemical

SPECIAL HAZARDS (FIRE) : Not flammable. Contains sodium hypochlorite which may act as an oxidizer in some cases intensifying a fire.

EXPLOSION HAZARDS : Product is not explosive.

REACTIVITY (FIRE) : Thermal decomposition generates: Corrosive vapors. If the product is involved in a fire, it can release explosive hydrogen gas. When heated to decomposition, emits toxic fumes. May be corrosive to metals.

SPECIAL INSTRUCTIONS TO FIRE FIGHTERS

PRECAUTIONARY MEASURES : Exercise caution when fighting any chemical fire.

FIRE FIGHTING INSTRUCTIONS : Use water spray or fog for cooling exposed containers.

PROTECTION DURING FIRE FIGHTING : Do not enter fire area without proper protective equipment, including respiratory protection.

HAZARDOUS COMBUSTION PRODUCTS : Potassium oxides. May liberate toxic gases. Sodium oxides. Phosphorous oxides. Nitrogen oxides. Carbon oxides (CO, CO₂). Explosive Hydrogen gas.

OTHER INFORMATION (FIRE) : Do not allow run-off from fire fighting to enter drains or water courses.

Safety Data Sheet ALUMA KLEEN

SECTION 6 – ACCIDENTAL RELEASE MEASURES

- PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES** : Restrict access to keep out unauthorized or unprotected personnel. Wear protective equipment. Avoid inhalation and direct contact.
- ENVIRONMENTAL PRECAUTIONS** : Keep spilled material away from sewage/drainage systems and waterways. If amounts exceeding the Reportable Quantity (5000 lbs. as phosphoric acid) are released, notification of the National Response Center (800) 424-8802 is required. See section 15 for more information.
- METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP** : All clean-up personnel must be properly trained. Confine the spill and remove incompatible materials and ignition sources. Ensure adequate ventilation. Secure the source of the leak if conditions are safe. Neutralize spill and collect using an appropriate absorbent material such as clay or vermiculite. Place waste in an appropriate container for disposal. Use care during clean-up to avoid exposure to the material and injury from broken containers.

SECTION 7 – HANDLING AND STORAGE

- PRECAUTIONS FOR SAFE HANDLING** : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.
- CONDITIONS FOR SAFE STORAGE** : Store in a dry, cool and well ventilated place. Keep container closed when not in use. Keep/store away from extremely high or low temperatures, direct sunlight, heat and incompatible materials (Strong acid, Strong oxidizers).



SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

- TLV (THRESHOLD LIMIT VALUE)** : The TLV in section III is the ACGIH/TLV-TWA (threshold limit value/time weighted average concentration for an eight hour work day). The STEL is the short term exposure limit and the (Ceil) is the ceiling limit.

COMPONENT	USA OSHA PEL – TWA	USA ACGIH TWA	USA ACGIH – STEL
Phosphoric Acid	1 mg/m ³	1mg/m ³	3mg/m ³
Ammonium Hydrogen Difluoride	2.5 mg/m ³	2.5 mg/m ³	Not Established
Alcohol Ethoxylate	Not Established	Not Established	Not Established

- EYE PROTECTION** : Wear chemical splash goggles or face shield.
- SKIN PROTECTION** : Minimize contact with product. Wear chemical resistant coveralls, boots, gloves, apron and/or suitable long-sleeved clothing.
- RESPIRATORY PROTECTION** : In case of brief exposure use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.
- VENTILATION** : Ensure adequate ventilation.
- ADDITIONAL MEASURES** : Emergency eyewash and safety shower facilities should be available in the immediate work area.
- REQUIRED WORK/HYGIENE** : Wash hands thoroughly after handling. Keep away from all food stuffs, beverages and feed. Do not eat, drink or smoke in work area.

Safety Data Sheet

ALUMA KLEEN

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	: Clear liquid with distinct odor
ODOR	: Distinct odor
ODOR THRESHOLD	: Not available
PH	: 2.3 (1% SOLUTION), APPX 1.0 AS IS
MELTING POINT/FREEZING POINT	: Not available
BOILING POINT	: Not available
FLASHPOINT	: Not applicable
EVAPORATION RATE	: Not available
FLAMMABILITY	: Non flammable, Non combustible
LOWER FLAMMABILITY LIMIT	: Not applicable
UPPER FLAMMABILITY LIMIT	: Not applicable
VAPOR PRESSURE	: Not available
VAPOR DENSITY (AIR=1)	: Not available
RELATIVE DENSITY	: 1.15
SOLUBILITY IN WATER	: Soluble in water
PARTITION COEFFICIENT n-OCTANOL/WATER	: Not available
AUTOIGNITION TEMPERATURE	: Not available
DECOMPOSITION TEMPERATURE	: Not available

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY	: Thermal decomposition generates: Corrosive vapors. If the product is involved in a fire, it can release explosion hydrogen gas. When heated to decomposition, emits toxic fumes. May be corrosive to metals.
STABILITY	: Stable under recommended storage conditions.
HAZARDOUS CONDITIONS TO AVOID	: Direct sunlight. Extremely high or low temperatures. Heat. Combustible materials. Incompatible materials.
INCOMPATIBLE MATERIALS	: Chlorinated products such as bleach, alkaline materials, metals, metal powder, carbides, chlorates, fumigates, nitrates, picrates, strong oxidizers, reducing or combustible organic material. Hazardous gases are evolved on contact with chemicals such as chlorine bleach, cyanides, sulfides and carbides.
HAZARDOUS DECOMPOSITION PRODUCTS	: Carbon oxides (CO, CO ₂). Thermal decomposition generates: Corrosive vapors. Toxic gases. Hydrogen gas. Nitrogen oxides. Phosphorous oxides. Sodium oxides. Potassium oxides.

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION	: Phosphoric Acid
ACUTE ORAL TOXICITY	: LD50 (rat) is greater than 1,530 mg/kg; not acutely toxic by oral exposure. (TFI Product Testing Results, OECD Guideline 425).
ACUTE DERMAL TOXICITY	: LD50 (rat) is greater than 3,160 mg/kg (ppm); not acutely toxic by dermal exposure. (TFI Product Testing Results, OECD Guideline 402).
ACUTE INHALATION TOXICITY	: LC50 (guinea pig, mouse, rat, rabbit) is 61-1,689 mg/m ³ ; highly toxic by inhalation. (TFI Product Testing Results)
ACUTE FISH TOXICITY	: 96-hour LC ₅₀ is 3.0-3.5 mg/L (ppm); moderate toxicity to aquatic organisms. (TFI Product testing Results, OECD Guideline 203).
TOXICOLOGICAL INFORMATION	: Ammonium Hydrogen Difluoride
ACUTE TOXICITY	: Eyes, Skin, Ingestion, Inhalation: Not available LD50 Oral (rat): 60 mg/kg.

Safety Data Sheet

ALUMA KLEEN

CARCINOGENICITY (IARC)	:	3 - Group 3: Not classifiable as to its carcinogenicity to humans (Ammonium Bifluoride).
CARCINOGENICITY	:	No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, ACGIH, OSHA
CHRONIC TOXICITY	:	Causes damage to following organs: lungs, mucous membranes.
TOXICOLOGICAL INFORMATION	:	Ethoxylated Alcohol N-12
ACUTE TOXICITY	:	LD50 Oral (rat): 3,989-5,000 mg/kg,
INHALATION LC50	:	No data available.
DERMAL LD50	:	LD50 Dermal (rabbit): 3,228-5,000 mg/kg.
SENSITIZATION SKIN	:	For this family of materials: Did not cause allergic skin reactions when tested in humans.
REPEATED DOSE TOXICITY	:	For this family of materials: In animals, effects have been reported on the following organs: Heart.

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION	:	Phosphoric Acid
AQUATIC TOXICITY	:	Mild water pollutant (surface water). May cause eutrophication. Toxic to plankton. Slightly harmful to bacteria. Slightly harmful to aquatic organisms. pH shift. Insufficient data available on eco-toxicity. LC50/96hour:138mg/L (Gambusia Afinis).
PERSISTENCE AND DEGRADABILITY	:	No relevant information available.
BIOACCUMULATIVE POTENTIAL	:	No relevant information available.
NOTES	:	Water hazard class 1 (Self assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of this product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or un-neutralized. Rinsing larger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms.
ECOLOGICAL INFORMATION	:	Ammonium Hydrogen Difluoride
AQUATIC TOXICITY	:	LC50 Fish 237 mg/L.
ENVIRONMENTAL FATE	:	No information found
ECOLOGICAL INFORMATION	:	Ethoxylated Alcohol NP-12
ECOTOXICITY	:	For this family of materials: Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in most sensitive species tested).
FISH ACUTE AND PROLONGED TOXICITY	:	For this family of materials: LC50, fathead minnow (Pimephales promelas), 96 h: 1.6 - 24 mg/l
AQUATIC INVERTEBRATE ACUTE TOXICITY	:	For this family of materials: LC50, water flea Daphnia magna, 48 h: 23.1 - 71.8 mg/L For this family of materials: EC50, water flea Daphnia magna, 48 h, immobilization: 23.1 mg/L.
PERSISTENCE AND DEGRADABILITY	:	No data available For this family of materials: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL RECOMMENDATIONS	:	This product must be disposed of in accordance with Federal, state and local environmental regulations. Discarded materials may be considered hazardous
---------------------------------------	---	---------------------------------------------------------------------------------------------------------------------------------------------------------

Safety Data Sheet

ALUMA KLEEN

waste due to pH/corrosivity. It is the responsibility of the product user to determine at the time of disposal whether a material containing, or derived from this product, should be classified as a hazardous waste.

ECOLOGY-WASTE MATERIALS : This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14 – TRANSPORTATION INFORMATION

DOT/IMDG/ IATA PROPER SHIPPING NAME : UN-2922, CORROSIVE LIQUID, TOXIC, N.O.S. (PHOSPHORIC ACID, AMMONIUM HYDROGEN DIFLUORIDE) 8, 6.1 PG-II

HAZARD CLASS AND LABEL : 8 (Corrosive)

UN NUMBER : UN-2922

PACKAGING GROUP : PG-II

EPA REPORTABLE QUANTITY (RQ) : 5000 LBS. (454 KG) as Phosphoric acid 100%.

MARINE POLLUTANT : Marine Pollutant

EMERGENCY RESPONSE GUIDE : ERG-154



SECTION 15 – REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION:

LISTED CARCINOGEN : Not listed

TSC STATUS : The ingredients of this product are listed on TSCA (Toxic Substances Control Act) inventory (40CFR 710.)

SARA SECTION 302 : None

SARA SECTION 311/312 : Immediate (acute) health hazard.

HAZARD CLASS

SARA SECTION 313 : Not Listed

NFPA HEALTH : 3

NFPA FLAMMABILITY : 0

NFPA REACTIVITY : 1

EUROPEAN UNION REGULATORY INFORMATION:

EC CLASSIFICATION : C: Corrosive, Xn: Harmful.

DSD/DPD RISK (R) PHRASES : R34: Causes severe burns.
R22: Harmful if swallowed.

DSD/DPD SAFETY (S) PHRASES : S1/2: Keep locked up and out of reach of children.
S18: Handle and open containers with care.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/S37/39: Wear suitable protective clothing, gloves and eye/face protection.
S45: In case of accidents or if you feel unwell, seek medical advice immediately. Show label where possible.
S61: Avoid release to the environment.
S64: If swallowed, rinse mouth with water if victim is conscious.

DSD/DPD HAZARD SYMBOL : C: Corrosive, Xn: Harmful



CANADIAN REGULATORY INFORMATION

WHMIS CATEGORY : Class E: Corrosive, Class D2B: Materials that cause other toxic effects (TOXIC).



Safety Data Sheet

ALUMA KLEEN

- DOMESTIC SUBSTANCES LIST (DSL)** : Listed
- INGREDIENT DISCLOSURE LIST** : Listed, This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the sds contains all of the information required by the CPR.



SECTION 16 – OTHER INFORMATION

- DISCLAIMER** : The information contained herein has been compiled from sources believed to be reliable and accurate to the best of our knowledge at this date. It is provided without warranty, expressed or implied, as to the results of use of this information or to the product to which it relates. Wesmar Co. assumes no responsibility for injury to any person or property resulting from any use of the material. Each user assumes the risk in their use of this product and should review the data and recommendations in the specific context of their intended use.
- IMDG** : International Maritime Code for Dangerous Goods
- DOT** : US Department of Transportation
- IATA** : International Air Transportation Association
- ACGIH** : American Conference of Governmental Industrial Hygienists
- NFPA** : National Fire Protection Association (USA)
- HMIS** : Hazardous Materials Identification System (USA)
- LC50** : Lethal concentration, 50 percent
- LD50** : Lethal dose, 50 percent
- STOT** : Specific Target Organ Toxicity
- DATE PREPARED** : JAN 12, 2011
- DATE REVISED** : AUG 29, 2014